
Resolutions

Release 10.4.rc1

The Sage Development Team

Jun 27, 2024

CONTENTS

1 Free resolutions	3
2 Graded free resolutions	9
3 Indices and Tables	15
Python Module Index	17
Index	19

Free and graded resolutions are tools for commutative algebra and algebraic geometry.

FREE RESOLUTIONS

Let R be a commutative ring. A finite free resolution of an R -module M is a chain complex of free R -modules

$$0 \rightarrow R^{n_k} \xrightarrow{d_k} \dots \xrightarrow{d_2} R^{n_1} \xrightarrow{d_1} R^{n_0}$$

terminating with a zero module at the end that is exact (all homology groups are zero) such that the image of d_1 is M .

EXAMPLES:

```
sage: from sage.homology.free_resolution import FreeResolution
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: m = matrix(S, 1, [z^2 - y*w, y*z - x*w, y^2 - x*z]).transpose()
sage: r = FreeResolution(m, name='S'); r
S^1 <-- S^3 <-- S^2 <-- 0

sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.free_resolution(); r
S^1 <-- S^3 <-- S^2 <-- 0
```

```
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution(); r
S(0) <-- S(-2)⊕S(-2)⊕S(-2) <-- S(-3)⊕S(-3) <-- 0
```

An example of a minimal free resolution from [CLO2005]:

```
sage: R.<x,y,z,w> = QQ[]
sage: I = R.ideal([y*z - x*w, y^3 - x^2*z, x*z^2 - y^2*w, z^3 - y*w^2])
sage: r = I.free_resolution(); r
S^1 <-- S^4 <-- S^4 <-- S^1 <-- 0
sage: len(r)
3
sage: r.matrix(2)
[-z^2 -x*z  y*w -y^2]
[  y  0  -x  0]
[-w  y  z  x]
[  0  w  0  z]
```

AUTHORS:

- Kwankyu Lee (2022-05-13): initial version
- Travis Scrimshaw (2022-08-23): refactored for free module inputs

class `sage.homology.free_resolution.FiniteFreeResolution` (*module*, *name='S'*, ***kws*)

Bases: `FreeResolution`

Finite free resolutions.

The matrix at index i in the list defines the differential map from $(i + 1)$ -th free module to the i -th free module over the base ring by multiplication on the left. The number of matrices in the list is the length of the resolution. The number of rows and columns of the matrices define the ranks of the free modules in the resolution.

Note that the first matrix in the list defines the differential map at homological index 1.

A subclass must provide a `_maps` attribute that contains a list of the maps defining the resolution.

A subclass can define `_initial_differential` attribute that contains the 0-th differential map whose codomain is the target of the free resolution.

EXAMPLES:

```
sage: from sage.homology.free_resolution import FreeResolution
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = FreeResolution(I)
sage: r.differential(0)
Coercion map:
From: Ambient free module of rank 1 over the integral domain
      Multivariate Polynomial Ring in x, y, z, w over Rational Field
To:    Quotient module by
      Submodule of Ambient free module of rank 1 over the integral domain
      Multivariate Polynomial Ring in x, y, z, w over Rational Field
      Generated by the rows of the matrix:
      [-z^2 + y*w]
      [ y*z - x*w]
      [-y^2 + x*z]
```

chain_complex()

Return this resolution as a chain complex.

A chain complex in Sage has its own useful methods.

EXAMPLES:

```
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution()
sage: unicode_art(r.chain_complex())
```

$$0 \longleftarrow C_0 \longleftarrow \begin{matrix} (z^2 - y*w & y*z - x*w & y^2 - x*z) \\ \begin{matrix} (-y & x) \\ z & -y \\ -w & z \end{matrix} \end{matrix} C_1 \longleftarrow C_2 \longleftarrow 0$$

differential(i)

Return the i -th differential map.

INPUT:

- i – a positive integer

EXAMPLES:


```

sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution()
sage: r
S(0) <-- S(-2)⊕S(-2)⊕S(-2) <-- S(-3)⊕S(-3) <-- 0
sage: r.differential(3)
Free module morphism defined as left-multiplication by the matrix
[]
Domain: Ambient free module of rank 0 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
Codomain: Ambient free module of rank 2 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
sage: r.differential(2)
Free module morphism defined as left-multiplication by the matrix
[-y x]
[ z -y]
[-w z]
Domain: Ambient free module of rank 2 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
Codomain: Ambient free module of rank 3 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
sage: r.differential(1)
Free module morphism defined as left-multiplication by the matrix
[z^2 - y*w y*z - x*w y^2 - x*z]
Domain: Ambient free module of rank 3 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
Codomain: Ambient free module of rank 1 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
sage: r.differential(0)
Coercion map:
From: Ambient free module of rank 1 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
To: Quotient module by
Submodule of Ambient free module of rank 1 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
Generated by the rows of the matrix:
[-z^2 + y*w]
[ y*z - x*w]
[-y^2 + x*z]

```

matrix (i)

Return the matrix representing the i -th differential map.

INPUT:

- i – a positive integer

EXAMPLES:

```

sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution(); r
S(0) <-- S(-2)⊕S(-2)⊕S(-2) <-- S(-3)⊕S(-3) <-- 0
sage: r.matrix(3)
[]
sage: r.matrix(2)
[-y x]
[ z -y]

```

(continues on next page)

(continued from previous page)

```
[-w z]
sage: r.matrix(1)
[z^2 - y*w y*z - x*w y^2 - x*z]
```

```
class sage.homology.free_resolution.FiniteFreeResolution_free_module(module,
                                                                    name='S',
                                                                    **kwds)
```

Bases: *FiniteFreeResolution*

Free resolutions of a free module.

INPUT:

- *module* – a free module or ideal over a PID
- *name* – the name of the base ring

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: M = R^3
sage: v = M([x^2, 2*x^2, 3*x^2])
sage: w = M([0, x, 2*x])
sage: S = M.submodule([v, w]); S
Free module of degree 3 and rank 2 over
Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[ x^2 2*x^2 3*x^2]
[ 0 x 2*x]
sage: res = S.free_resolution(); res
S^3 <-- S^2 <-- 0
sage: ascii_art(res.chain_complex())
      [ x^2 0]
      [2*x^2 x]
      [3*x^2 2*x]
0 <-- C_0 <----- C_1 <-- 0

sage: R.<x> = PolynomialRing(QQ)
sage: I = R.ideal([x^4 + 3*x^2 + 2])
sage: res = I.free_resolution(); res
S^1 <-- S^1 <-- 0
```

```
class sage.homology.free_resolution.FiniteFreeResolution_singular(module, name='S',
                                                                    algorithm='heuristic',
                                                                    **kwds)
```

Bases: *FiniteFreeResolution*

Minimal free resolutions of ideals or submodules of free modules of multivariate polynomial rings implemented in Singular.

INPUT:

- *module* – a submodule of a free module M of rank n over S or an ideal of a multi-variate polynomial ring
- *name* – string (optional); name of the base ring
- *algorithm* – (default: 'heuristic') Singular algorithm to compute a resolution of ideal

OUTPUT: a minimal free resolution of the ideal

If `module` is an ideal of S , it is considered as a submodule of a free module of rank 1 over S .

The available algorithms and the corresponding Singular commands are shown below:

algorithm	Singular commands
minimal	<code>mres(ideal)</code>
shreyer	<code>minres(sres(std(ideal)))</code>
standard	<code>minres(nres(std(ideal)))</code>
heuristic	<code>minres(res(std(ideal)))</code>

EXAMPLES:

```
sage: from sage.homology.free_resolution import FreeResolution
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = FreeResolution(I); r
S^1 <-- S^3 <-- S^2 <-- 0
sage: len(r)
2
```

```
sage: FreeResolution(I, algorithm='minimal')
S^1 <-- S^3 <-- S^2 <-- 0
sage: FreeResolution(I, algorithm='shreyer')
S^1 <-- S^3 <-- S^2 <-- 0
sage: FreeResolution(I, algorithm='standard')
S^1 <-- S^3 <-- S^2 <-- 0
sage: FreeResolution(I, algorithm='heuristic')
S^1 <-- S^3 <-- S^2 <-- 0
```

We can also construct a resolution by passing in a matrix defining the initial differential:

```
sage: m = matrix(S, 1, [z^2 - y*w, y*z - x*w, y^2 - x*z]).transpose()
sage: r = FreeResolution(m, name='S'); r
S^1 <-- S^3 <-- S^2 <-- 0
sage: r.matrix(1)
[z^2 - y*w y*z - x*w y^2 - x*z]
```

An additional construction is using a submodule of a free module:

```
sage: M = m.image()
sage: r = FreeResolution(M, name='S'); r
S^1 <-- S^3 <-- S^2 <-- 0
```

A nonhomogeneous ideal:

```
sage: I = S.ideal([z^2 - y*w, y*z - x*w, y^2 - x])
sage: R = FreeResolution(I); R
S^1 <-- S^3 <-- S^3 <-- S^1 <-- 0
sage: R.matrix(2)
[ y*z - x*w    y^2 - x          0]
[-z^2 + y*w      0    y^2 - x]
[      0 -z^2 + y*w -y*z + x*w]
sage: R.matrix(3)
[   y^2 - x]
[-y*z + x*w]
[ z^2 - y*w]
```

class sage.homology.free_resolution.**FreeResolution** (*module*, *name='S'*, ***kws*)

Bases: SageObject

A free resolution.

Let R be a commutative ring. A *free resolution* of an R -module M is a (possibly infinite) chain complex of free R -modules

$$\dots \rightarrow R^{n_k} \xrightarrow{d_k} \dots \xrightarrow{d_2} R^{n_1} \xrightarrow{d_1} R^{n_0}$$

that is exact (all homology groups are zero) such that the image of d_1 is M .

differential (*i*)

Return the i -th differential map.

INPUT:

- i – a positive integer

target ()

Return the codomain of the 0-th differential map.

The codomain of the 0-th differential map is the cokernel of the first differential map.

EXAMPLES:

```
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution()
sage: r
S(0) <-- S(-2)⊕S(-2)⊕S(-2) <-- S(-3)⊕S(-3) <-- 0
sage: r.target()
Quotient module by
Submodule of Ambient free module of rank 1 over the integral domain
Multivariate Polynomial Ring in x, y, z, w over Rational Field
Generated by the rows of the matrix:
[-z^2 + y*w]
[ y*z - x*w]
[-y^2 + x*z]
```

GRADED FREE RESOLUTIONS

Let R be a commutative ring. A graded free resolution of a graded R -module M is a *free resolution* such that all maps are homogeneous module homomorphisms.

EXAMPLES:

```
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution(algorithm='minimal')
sage: r
S(0) <-- S(-2)⊗S(-2)⊗S(-2) <-- S(-3)⊗S(-3) <-- 0
sage: I.graded_free_resolution(algorithm='shreyer')
S(0) <-- S(-2)⊗S(-2)⊗S(-2) <-- S(-3)⊗S(-3) <-- 0
sage: I.graded_free_resolution(algorithm='standard')
S(0) <-- S(-2)⊗S(-2)⊗S(-2) <-- S(-3)⊗S(-3) <-- 0
sage: I.graded_free_resolution(algorithm='heuristic')
S(0) <-- S(-2)⊗S(-2)⊗S(-2) <-- S(-3)⊗S(-3) <-- 0
```

```
sage: d = r.differential(2)
sage: d
Free module morphism defined as left-multiplication by the matrix
 [ y  x]
 [-z -y]
 [ w  z]
Domain: Ambient free module of rank 2 over the integral domain
         Multivariate Polynomial Ring in x, y, z, w over Rational Field
Codomain: Ambient free module of rank 3 over the integral domain
          Multivariate Polynomial Ring in x, y, z, w over Rational Field
sage: d.image()
Submodule of Ambient free module of rank 3 over the integral domain
         Multivariate Polynomial Ring in x, y, z, w over Rational Field
Generated by the rows of the matrix:
 [ y -z  w]
 [ x -y  z]
sage: m = d.image()
sage: m.graded_free_resolution(shifts=(2,2,2))
S(-2)⊗S(-2)⊗S(-2) <-- S(-3)⊗S(-3) <-- 0
```

An example of multigraded resolution from Example 9.1 of [MilStu2005]:

```
sage: R.<s,t> = QQ[]
sage: S.<a,b,c,d> = QQ[]
sage: phi = S.hom([s, s*t, s*t^2, s*t^3])
sage: I = phi.kernel(); I
↳needs sage.rings.function_field
```

(continues on next page)

(continued from previous page)

```

Ideal (c^2 - b*d, b*c - a*d, b^2 - a*c) of
Multivariate Polynomial Ring in a, b, c, d over Rational Field
sage: P3 = ProjectiveSpace(S)
sage: C = P3.subscheme(I) # twisted cubic curve
sage: r = I.graded_free_resolution(degrees=[(1,0), (1,1), (1,2), (1,3)])
sage: r
S((0, 0)) <-- S((-2, -4))⊕S((-2, -3))⊕S((-2, -2)) <-- S((-3, -5))⊕S((-3, -4)) <-- 0
sage: r.K_polynomial(names='s,t')
s^3*t^5 + s^3*t^4 - s^2*t^4 - s^2*t^3 - s^2*t^2 + 1

```

AUTHORS:

- Kwankyu Lee (2022-05): initial version
- Travis Scrimshaw (2022-08-23): refactored for free module inputs

```

class sage.homology.graded_resolution.GradedFiniteFreeResolution(module,
                                                                    degrees=None,
                                                                    shifts=None,
                                                                    name='S', **kws)

```

Bases: *FiniteFreeResolution*

Graded finite free resolutions.

INPUT:

- *module* – a homogeneous submodule of a free module M of rank n over S or a homogeneous ideal of a multivariate polynomial ring S
- *degrees* – (default: a list with all entries 1) a list of integers or integer vectors giving degrees of variables of S
- *shifts* – a list of integers or integer vectors giving shifts of degrees of n summands of the free module M ; this is a list of zero degrees of length n by default
- *name* – a string; name of the base ring

K_polynomial (*names=None*)

Return the K-polynomial of this resolution.

INPUT:

- *names* – (optional) a string of names of the variables of the K-polynomial

EXAMPLES:

```

sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution()
sage: r.K_polynomial()
2*t^3 - 3*t^2 + 1

```

betti (*i, a=None*)

Return the i -th Betti number in degree a .

INPUT:

- i – nonnegative integer
- a – a degree; if *None*, return Betti numbers in all degrees

EXAMPLES:

```

sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution()
sage: r.betti(0)
{0: 1}
sage: r.betti(1)
{2: 3}
sage: r.betti(2)
{3: 2}
sage: r.betti(1, 0)
0
sage: r.betti(1, 1)
0
sage: r.betti(1, 2)
3

```

shifts (*i*)

Return the shifts of self.

EXAMPLES:

```

sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution()
sage: r.shifts(0)
[0]
sage: r.shifts(1)
[2, 2, 2]
sage: r.shifts(2)
[3, 3]
sage: r.shifts(3)
[]

```

class sage.homology.graded_resolution.**GradedFiniteFreeResolution_free_module** (*module*, *degrees=None*, **args*, ***kwds*)

Bases: *GradedFiniteFreeResolution*, *FiniteFreeResolution_free_module*

Graded free resolution of free modules.

EXAMPLES:

```

sage: from sage.homology.free_resolution import FreeResolution
sage: R.<x> = QQ[]
sage: M = matrix([[x^3, 3*x^3, 5*x^3],
....:             [0, x, 2*x]])
sage: res = FreeResolution(M, graded=True); res
S(0)⊕S(0)⊕S(0) <-- S(-3)⊕S(-1) <-- 0

```

```
class sage.homology.graded_resolution.GradedFiniteFreeResolution_singular (mod-
                                                                    ule,
                                                                    de-
                                                                    grees=None,
                                                                    shifts=None,
                                                                    name='S',
                                                                    algo-
                                                                    rithm='heuris-
                                                                    tic',
                                                                    **kws)
```

Bases: *GradedFiniteFreeResolution, FiniteFreeResolution_singular*

Graded free resolutions of submodules and ideals of multivariate polynomial rings implemented using Singular.

INPUT:

- `module` – a homogeneous submodule of a free module M of rank n over S or a homogeneous ideal of a multivariate polynomial ring S
- `degrees` – (default: a list with all entries 1) a list of integers or integer vectors giving degrees of variables of S
- `shifts` – a list of integers or integer vectors giving shifts of degrees of n summands of the free module M ; this is a list of zero degrees of length n by default
- `name` – a string; name of the base ring
- `algorithm` – Singular algorithm to compute a resolution of `ideal`

OUTPUT: a graded minimal free resolution of `ideal`

If `module` is an ideal of S , it is considered as a submodule of a free module of rank 1 over S .

The degrees given to the variables of S are integers or integer vectors of the same length. In the latter case, S is said to be multigraded, and the resolution is a multigraded free resolution. The standard grading where all variables have degree 1 is used if the degrees are not specified.

A summand of the graded free module M is a shifted (or twisted) module of rank one over S , denoted $S(-d)$ with shift d .

The computation of the resolution is done by using `libSingular`. Different Singular algorithms can be chosen for best performance. The available algorithms and the corresponding Singular commands are shown below:

algorithm	Singular commands
<code>minimal</code>	<code>mres(ideal)</code>
<code>shreyer</code>	<code>minres(sres(std(ideal)))</code>
<code>standard</code>	<code>minres(nres(std(ideal)))</code>
<code>heuristic</code>	<code>minres(res(std(ideal)))</code>

EXAMPLES:

```
sage: S.<x,y,z,w> = PolynomialRing(QQ)
sage: I = S.ideal([y*w - z^2, -x*w + y*z, x*z - y^2])
sage: r = I.graded_free_resolution(); r
S(0) <-- S(-2)@S(-2)@S(-2) <-- S(-3)@S(-3) <-- 0
sage: len(r)
2
```

(continues on next page)

(continued from previous page)

```
sage: I = S.ideal([z^2 - y*w, y*z - x*w, y - x])
sage: I.is_homogeneous()
True
sage: r = I.graded_free_resolution(); r
S(0) <-- S(-1)⊕S(-2)⊕S(-2) <-- S(-3)⊕S(-3)⊕S(-4) <-- S(-5) <-- 0
```


INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

h

`sage.homology.free_resolution`, 3
`sage.homology.graded_resolution`, 9

INDEX

B

`betti()` (*sage.homology.graded_resolution.GradedFiniteFreeResolution method*), 10

C

`chain_complex()` (*sage.homology.free_resolution.FiniteFreeResolution method*), 4

D

`differential()` (*sage.homology.free_resolution.FiniteFreeResolution method*), 4

`differential()` (*sage.homology.free_resolution.FreeResolution method*), 8

F

`FiniteFreeResolution` (*class in sage.homology.free_resolution*), 3

`FiniteFreeResolution_free_module` (*class in sage.homology.free_resolution*), 6

`FiniteFreeResolution_singular` (*class in sage.homology.free_resolution*), 6

`FreeResolution` (*class in sage.homology.free_resolution*), 7

G

`GradedFiniteFreeResolution` (*class in sage.homology.graded_resolution*), 10

`GradedFiniteFreeResolution_free_module` (*class in sage.homology.graded_resolution*), 11

`GradedFiniteFreeResolution_singular` (*class in sage.homology.graded_resolution*), 11

K

`K_polynomial()` (*sage.homology.graded_resolution.GradedFiniteFreeResolution method*), 10

M

`matrix()` (*sage.homology.free_resolution.FiniteFreeResolution method*), 5

module
 sage.homology.free_resolution, 3

sage.homology.graded_resolution, 9

S

sage.homology.free_resolution
 module, 3

sage.homology.graded_resolution
 module, 9

`shifts()` (*sage.homology.graded_resolution.GradedFiniteFreeResolution method*), 11

T

`target()` (*sage.homology.free_resolution.FreeResolution method*), 8