
General Rings, Ideals, and Morphisms

Release 10.4.rc1

The Sage Development Team

Jun 27, 2024

CONTENTS

1	Base Classes for Rings, Algebras and Fields	1
2	Ideals	23
3	Ring Morphisms	43
4	Quotient Rings	65
5	Fraction Fields	83
6	Localization	95
7	Ring Extensions	105
8	Generic Data Structures and Algorithms for Rings	141
9	Utilities	145
10	Derivation	157
11	Indices and Tables	173
	Python Module Index	175
	Index	177

BASE CLASSES FOR RINGS, ALGEBRAS AND FIELDS

1.1 Rings

This module provides the abstract base class *Ring* from which all rings in Sage (used to) derive, as well as a selection of more specific base classes.

Warning: Those classes, except maybe for the lowest ones like *CommutativeRing* and *Field*, are being progressively deprecated in favor of the corresponding categories. which are more flexible, in particular with respect to multiple inheritance.

The class inheritance hierarchy is:

- *Ring* (to be deprecated)
 - *Algebra* (to be deprecated)
 - *CommutativeRing*
 - * *NoetherianRing* (deprecated)
 - * *CommutativeAlgebra* (deprecated and essentially removed)
 - * *IntegralDomain* (deprecated)
 - *DedekindDomain* (deprecated and essentially removed)
 - *PrincipalIdealDomain* (deprecated and essentially removed)

Subclasses of *CommutativeRing* are

- *Field*
 - *FiniteField*

Some aspects of this structure may seem strange, but this is an unfortunate consequence of the fact that Cython classes do not support multiple inheritance.

(A distinct but equally awkward issue is that sometimes we may not know *in advance* whether or not a ring belongs in one of these classes; e.g. some orders in number fields are Dedekind domains, but others are not, and we still want to offer a unified interface, so orders are never instances of the deprecated *DedekindDomain* class.)

AUTHORS:

- David Harvey (2006-10-16): changed *CommutativeAlgebra* to derive from *CommutativeRing* instead of from *Algebra*.
- David Loeffler (2009-07-09): documentation fixes, added to reference manual.

- Simon King (2011-03-29): Proper use of the category framework for rings.
- Simon King (2011-05-20): Modify multiplication and `_ideal_class_` to support ideals of non-commutative rings.

class sage.rings.ring.**Algebra**

Bases: *Ring*

Generic algebra

class sage.rings.ring.**CommutativeAlgebra**

Bases: *CommutativeRing*

class sage.rings.ring.**CommutativeRing**

Bases: *Ring*

Generic commutative ring.

extension (*poly*, *name=None*, *names=None*, ***kws*)

Algebraically extends self by taking the quotient $\text{self}[x] / (f(x))$.

INPUT:

- *poly* – A polynomial whose coefficients are coercible into self
- *name* – (optional) name for the root of *f*

Note: Using this method on an algebraically complete field does *not* return this field; the construction $\text{self}[x] / (f(x))$ is done anyway.

EXAMPLES:

```
sage: R = QQ['x']
sage: y = polygen(R)
sage: R.extension(y^2 - 5, 'a') #_
↳needs sage.libs.pari
Univariate Quotient Polynomial Ring in a over
Univariate Polynomial Ring in x over Rational Field with modulus a^2 - 5
```

```
sage: # needs sage.rings.finite_rings
sage: P.<x> = PolynomialRing(GF(5))
sage: F.<a> = GF(5).extension(x^2 - 2)
sage: P.<t> = F[]
sage: R.<b> = F.extension(t^2 - a); R
Univariate Quotient Polynomial Ring in b over
Finite Field in a of size 5^2 with modulus b^2 + 4*a
```

fraction_field()

Return the fraction field of self.

EXAMPLES:

```
sage: R = Integers(389)['x,y']
sage: Frac(R)
Fraction Field of Multivariate Polynomial Ring in x, y over Ring of integers_
↳modulo 389
sage: R.fraction_field()
Fraction Field of Multivariate Polynomial Ring in x, y over Ring of integers_
↳modulo 389
```

ideal_monoid()

Return the monoid of ideals of this ring.

EXAMPLES:

```
sage: ZZ.ideal_monoid()
Monoid of ideals of Integer Ring
sage: R.<x>=QQ[]; R.ideal_monoid()
Monoid of ideals of Univariate Polynomial Ring in x over Rational Field
```

is_commutative()

Return True, since this ring is commutative.

EXAMPLES:

```
sage: QQ.is_commutative()
True
sage: ZpCA(7).is_commutative() #_
↪needs sage.rings.padics
True
sage: A = QuaternionAlgebra(QQ, -1, -3, names=('i', 'j', 'k')); A #_
↪needs sage.combinat sage.modules
Quaternion Algebra (-1, -3) with base ring Rational Field
sage: A.is_commutative() #_
↪needs sage.combinat sage.modules
False
```

krull_dimension()

Return the Krull dimension of this commutative ring.

The Krull dimension is the length of the longest ascending chain of prime ideals.

localization (*additional_units*, *names=None*, *normalize=True*, *category=None*)Return the localization of *self* at the given additional units.

EXAMPLES:

```
sage: R.<x, y> = GF(3)[]
sage: R.localization((x*y, x**2 + y**2)) #_
↪needs sage.rings.finite_rings
Multivariate Polynomial Ring in x, y over Finite Field of size 3
localized at (y, x, x^2 + y^2)
sage: ~y in _ #_
↪needs sage.rings.finite_rings
True
```

class sage.rings.ring.DedekindDomainBases: *CommutativeRing***class** sage.rings.ring.FieldBases: *CommutativeRing*

Generic field

algebraic_closure()Return the algebraic closure of *self*.**Note:** This is only implemented for certain classes of field.

EXAMPLES:

```
sage: K = PolynomialRing(QQ, 'x').fraction_field(); K
Fraction Field of Univariate Polynomial Ring in x over Rational Field
sage: K.algebraic_closure()
Traceback (most recent call last):
...
NotImplementedError: Algebraic closures of general fields not implemented.
```

divides (*x*, *y*, *coerce=True*)

Return True if *x* divides *y* in this field (usually True in a field!). If *coerce* is True (the default), first coerce *x* and *y* into self.

EXAMPLES:

```
sage: QQ.divides(2, 3/4)
True
sage: QQ.divides(0, 5)
False
```

fraction_field ()

Return the fraction field of self.

EXAMPLES:

Since fields are their own field of fractions, we simply get the original field in return:

```
sage: QQ.fraction_field()
Rational Field
sage: RR.fraction_field() #_
↪needs sage.rings.real_mpfr
Real Field with 53 bits of precision
sage: CC.fraction_field() #_
↪needs sage.rings.real_mpfr
Complex Field with 53 bits of precision

sage: x = polygen(ZZ, 'x')
sage: F = NumberField(x^2 + 1, 'i') #_
↪needs sage.rings.number_field
sage: F.fraction_field() #_
↪needs sage.rings.number_field
Number Field in i with defining polynomial x^2 + 1
```

ideal (**gens*, ***kws*)

Return the ideal generated by *gens*.

EXAMPLES:

```
sage: QQ.ideal(2)
Principal ideal (1) of Rational Field
sage: QQ.ideal(0)
Principal ideal (0) of Rational Field
```

integral_closure ()

Return this field, since fields are integrally closed in their fraction field.

EXAMPLES:


```
sage: QQ.integral_closure()
Rational Field
sage: Frac(ZZ['x,y']).integral_closure()
Fraction Field of Multivariate Polynomial Ring in x, y over Integer Ring
```

is_field(*proof=True*)

Return True since this is a field.

EXAMPLES:

```
sage: Frac(ZZ['x,y']).is_field()
True
```

is_integrally_closed()

Return True since fields are trivially integrally closed in their fraction field (since they are their own fraction field).

EXAMPLES:

```
sage: Frac(ZZ['x,y']).is_integrally_closed()
True
```

is_noetherian()

Return True since fields are Noetherian rings.

EXAMPLES:

```
sage: QQ.is_noetherian()
True
```

krull_dimension()

Return the Krull dimension of this field, which is 0.

EXAMPLES:

```
sage: QQ.krull_dimension()
0
sage: Frac(QQ['x,y']).krull_dimension()
0
```

prime_subfield()

Return the prime subfield of *self*.

EXAMPLES:

```
sage: k = GF(9, 'a') #_
↪needs sage.rings.finite_rings
sage: k.prime_subfield() #_
↪needs sage.rings.finite_rings
Finite Field of size 3
```

class `sage.rings.ring.IntegralDomain`

Bases: *CommutativeRing*

Generic integral domain class.

This class is deprecated. Please use the `sage.categories.integral_domains.IntegralDomains` category instead.

is_field(*proof=True*)

Return True if this ring is a field.

EXAMPLES:

```
sage: GF(7).is_field()
True
```

The following examples have their own `is_field` implementations:

```
sage: ZZ.is_field(); QQ.is_field()
False
True
sage: R.<x> = PolynomialRing(QQ); R.is_field()
False
```

is_integrally_closed()

Return True if this ring is integrally closed in its field of fractions; otherwise return False.

When no algorithm is implemented for this, then this function raises a `NotImplementedError`.

Note that `is_integrally_closed` has a naive implementation in fields. For every field F , F is its own field of fractions, hence every element of F is integral over F .

EXAMPLES:

```
sage: ZZ.is_integrally_closed()
True
sage: QQ.is_integrally_closed()
True
sage: QQbar.is_integrally_closed() #_
↪needs sage.rings.number_field
True
sage: GF(5).is_integrally_closed()
True
sage: Z5 = Integers(5); Z5
Ring of integers modulo 5
sage: Z5.is_integrally_closed()
Traceback (most recent call last):
...
AttributeError: 'IntegerModRing_generic_with_category' object has no_
↪attribute 'is_integrally_closed'...
```

class sage.rings.ring.NoetherianRing

Bases: *CommutativeRing*

class sage.rings.ring.PrincipalIdealDomain

Bases: *CommutativeRing*

class sage.rings.ring.Ring

Bases: *ParentWithGens*

Generic ring class.

base_extend(R)

EXAMPLES:

```

sage: QQ.base_extend(GF(7))
Traceback (most recent call last):
...
TypeError: no base extension defined
sage: ZZ.base_extend(GF(7))
Finite Field of size 7

```

category()

Return the category to which this ring belongs.

Note: This method exists because sometimes a ring is its own base ring. During initialisation of a ring R , it may be checked whether the base ring (hence, the ring itself) is a ring. Hence, it is necessary that `R.category()` tells that R is a ring, even *before* its category is properly initialised.

EXAMPLES:

```

sage: FreeAlgebra(QQ, 3, 'x').category() # todo: use a ring which is not an
↪ algebra! # needs sage.combinat sage.modules
Category of algebras with basis over Rational Field

```

Since a quotient of the integers is its own base ring, and during initialisation of a ring it is tested whether the base ring belongs to the category of rings, the following is an indirect test that the `category()` method of rings returns the category of rings even before the initialisation was successful:

```

sage: I = Integers(15)
sage: I.base_ring() is I
True
sage: I.category()
Join of Category of finite commutative rings
and Category of subquotients of monoids
and Category of quotients of semigroups
and Category of finite enumerated sets

```

epsilon()

Return the precision error of elements in this ring.

EXAMPLES:

```

sage: RDF.epsilon()
2.220446049250313e-16
sage: ComplexField(53).epsilon() #_
↪ needs sage.rings.real_mpr
2.22044604925031e-16
sage: RealField(10).epsilon() #_
↪ needs sage.rings.real_mpr
0.0020

```

For exact rings, zero is returned:

```

sage: ZZ.epsilon()
0

```

This also works over derived rings:

```
sage: RR['x'].epsilon() #_
↳needs sage.rings.real_mpr
2.22044604925031e-16
sage: QQ['x'].epsilon()
0
```

For the symbolic ring, there is no reasonable answer:

```
sage: SR.epsilon() #_
↳needs sage.symbolic
Traceback (most recent call last):
...
NotImplementedError
```

ideal (*args, **kws)

Return the ideal defined by x , i.e., generated by x .

INPUT:

- x – list or tuple of generators (or several input arguments)
- *coerce* – bool (default: True); this must be a keyword argument. Only set it to False if you are certain that each generator is already in the ring.
- *ideal_class* – callable (default: `self._ideal_class()`); this must be a keyword argument. A constructor for ideals, taking the ring as the first argument and then the generators. Usually a subclass of *Ideal_generic* or *Ideal_nc*.
- Further named arguments (such as *side* in the case of non-commutative rings) are forwarded to the ideal class.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: R.ideal(x,y)
Ideal (x, y) of Multivariate Polynomial Ring in x, y over Rational Field
sage: R.ideal(x+y^2)
Ideal (y^2 + x) of Multivariate Polynomial Ring in x, y over Rational Field
sage: R.ideal( [x^3,y^3+x^3] )
Ideal (x^3, x^3 + y^3) of Multivariate Polynomial Ring in x, y over Rational_
↳Field
```

Here is an example over a non-commutative ring:

```
sage: A = SteenrodAlgebra(2) #_
↳needs sage.combinat sage.modules
sage: A.ideal(A.1, A.2^2) #_
↳needs sage.combinat sage.modules
Twosided Ideal (Sq(2), Sq(2,2)) of mod 2 Steenrod algebra, milnor basis
sage: A.ideal(A.1, A.2^2, side='left') #_
↳needs sage.combinat sage.modules
Left Ideal (Sq(2), Sq(2,2)) of mod 2 Steenrod algebra, milnor basis
```

ideal_monoid()

Return the monoid of ideals of this ring.

EXAMPLES:

```

sage: # needs sage.combinat sage.modules
sage: F.<x,y,z> = FreeAlgebra(ZZ, 3)
sage: I = F * [x*y + y*z, x^2 + x*y - y*x - y^2] * F
sage: Q = F.quotient(I)
sage: Q.ideal_monoid()
Monoid of ideals of Quotient of Free Algebra on 3 generators (x, y, z)
over Integer Ring by the ideal (x*y + y*z, x^2 + x*y - y*x - y^2)
sage: F.<x,y,z> = FreeAlgebra(ZZ, implementation='letterplace')
sage: I = F * [x*y + y*z, x^2 + x*y - y*x - y^2] * F
sage: Q = F.quo(I)
sage: Q.ideal_monoid()
Monoid of ideals of Quotient of Free Associative Unital Algebra
on 3 generators (x, y, z) over Integer Ring
by the ideal (x*y + y*z, x*x + x*y - y*x - y*y)

```

is_exact()

Return True if elements of this ring are represented exactly, i.e., there is no precision loss when doing arithmetic.

Note: This defaults to True, so even if it does return True you have no guarantee (unless the ring has properly overloaded this).

EXAMPLES:

```

sage: QQ.is_exact()      # indirect doctest
True
sage: ZZ.is_exact()
True
sage: Qp(7).is_exact() #_
↪needs sage.rings.padics
False
sage: Zp(7, type='capped-abs').is_exact() #_
↪needs sage.rings.padics
False

```

is_field(proof=True)

Return True if this ring is a field.

INPUT:

- `proof` – (default: True) Determines what to do in unknown cases

ALGORITHM:

If the parameter `proof` is set to True, the returned value is correct but the method might throw an error. Otherwise, if it is set to False, the method returns True if it can establish that self is a field and False otherwise.

EXAMPLES:

```

sage: QQ.is_field()
True
sage: GF(9, 'a').is_field() #_
↪needs sage.rings.finite_rings
True
sage: ZZ.is_field()
False

```

(continues on next page)

(continued from previous page)

```
sage: QQ['x'].is_field()
False
sage: Frac(QQ['x']).is_field()
True
```

This illustrates the use of the `proof` parameter:

```
sage: R.<a,b> = QQ[]
sage: S.<x,y> = R.quo((b^3)) #_
↪needs sage.libs.singular
sage: S.is_field(proof=True) #_
↪needs sage.libs.singular
Traceback (most recent call last):
...
NotImplementedError
sage: S.is_field(proof=False) #_
↪needs sage.libs.singular
False
```

`is_prime_field()`

Return True if this ring is one of the prime fields \mathbf{Q} or \mathbf{F}_p .

EXAMPLES:

```
sage: QQ.is_prime_field()
True
sage: GF(3).is_prime_field()
True
sage: GF(9, 'a').is_prime_field() #_
↪needs sage.rings.finite_rings
False
sage: ZZ.is_prime_field()
False
sage: QQ['x'].is_prime_field()
False
sage: Qp(19).is_prime_field() #_
↪needs sage.rings.padics
False
```

`is_subring(other)`

Return True if the canonical map from `self` to `other` is injective.

Raises a `NotImplementedError` if not known.

EXAMPLES:

```
sage: ZZ.is_subring(QQ)
True
sage: ZZ.is_subring(GF(19))
False
```

`one()`

Return the one element of this ring (cached), if it exists.

EXAMPLES:

```
sage: ZZ.one()
1
sage: QQ.one()
1
sage: QQ['x'].one()
1
```

The result is cached:

```
sage: ZZ.one() is ZZ.one()
True
```

order()

The number of elements of self.

EXAMPLES:

```
sage: GF(19).order()
19
sage: QQ.order()
+Infinity
```

principal_ideal (*gen, coerce=True*)

Return the principal ideal generated by gen.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: R.principal_ideal(x+2*y)
Ideal (x + 2*y) of Multivariate Polynomial Ring in x, y over Integer Ring
```

random_element (*bound=2*)

Return a random integer coerced into this ring, where the integer is chosen uniformly from the interval $[-bound, bound]$.

INPUT:

- bound – integer (default: 2)

ALGORITHM:

Uses Python's randint.

unit_ideal ()

Return the unit ideal of this ring.

EXAMPLES:

```
sage: Zp(7).unit_ideal() #_
↪needs sage.rings.padics
Principal ideal (1 + O(7^20)) of 7-adic Ring with capped relative precision 20
```

zero ()

Return the zero element of this ring (cached).

EXAMPLES:

```
sage: ZZ.zero()
0
sage: QQ.zero()
0
sage: QQ['x'].zero()
0
```

The result is cached:

```
sage: ZZ.zero() is ZZ.zero()
True
```

zero_ideal()

Return the zero ideal of this ring (cached).

EXAMPLES:

```
sage: ZZ.zero_ideal()
Principal ideal (0) of Integer Ring
sage: QQ.zero_ideal()
Principal ideal (0) of Rational Field
sage: QQ['x'].zero_ideal()
Principal ideal (0) of Univariate Polynomial Ring in x over Rational Field
```

The result is cached:

```
sage: ZZ.zero_ideal() is ZZ.zero_ideal()
True
```

zeta (n=2, all=False)

Return a primitive n -th root of unity in `self` if there is one, or raise a `ValueError` otherwise.

INPUT:

- `n` – positive integer
- `all` – bool (default: `False`); whether to return a list of all primitive n -th roots of unity. If `True`, raise a `ValueError` if `self` is not an integral domain.

OUTPUT:

Element of `self` of finite order

EXAMPLES:

```
sage: QQ.zeta()
-1
sage: QQ.zeta(1)
1
sage: CyclotomicField(6).zeta(6) #_
↪needs sage.rings.number_field
zeta6
sage: CyclotomicField(3).zeta(3) #_
↪needs sage.rings.number_field
zeta3
sage: CyclotomicField(3).zeta(3).multiplicative_order() #_
↪needs sage.rings.number_field
3
```

(continues on next page)

(continued from previous page)

```

sage: # needs sage.rings.finite_rings
sage: a = GF(7).zeta(); a
3
sage: a.multiplicative_order()
6
sage: a = GF(49,'z').zeta(); a
z
sage: a.multiplicative_order()
48
sage: a = GF(49,'z').zeta(2); a
6
sage: a.multiplicative_order()
2

sage: QQ.zeta(3)
Traceback (most recent call last):
...
ValueError: no n-th root of unity in rational field
sage: Zp(7, prec=8).zeta() #_
↳needs sage.rings.padics
3 + 4*7 + 6*7^2 + 3*7^3 + 2*7^5 + 6*7^6 + 2*7^7 + O(7^8)

```

zeta_order()

Return the order of the distinguished root of unity in *self*.

EXAMPLES:

```

sage: CyclotomicField(19).zeta_order() #_
↳needs sage.rings.number_field
38
sage: GF(19).zeta_order()
18
sage: GF(5^3,'a').zeta_order() #_
↳needs sage.rings.finite_rings
124
sage: Zp(7, prec=8).zeta_order() #_
↳needs sage.rings.padics
6

```

sage.rings.ring.is_Ring(x)

Return True if *x* is a ring.

EXAMPLES:

```

sage: from sage.rings.ring import is_Ring
sage: is_Ring(ZZ)
True
sage: MS = MatrixSpace(QQ, 2) #_
↳needs sage.modules
sage: is_Ring(MS) #_
↳needs sage.modules
True

```

1.2 Abstract base classes for rings

class sage.rings.abc.**AlgebraicField**

Bases: *AlgebraicField_common*

Abstract base class for *AlgebraicField*.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(QQbar, sage.rings.abc.AlgebraicField) #_
↪needs sage.rings.number_field
True
sage: isinstance(AA, sage.rings.abc.AlgebraicField) #_
↪needs sage.rings.number_field
False
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.AlgebraicField.__subclasses__() #_
↪needs sage.rings.number_field
[<class 'sage.rings.qqbar.AlgebraicField'>]

sage: len(sage.rings.abc.AlgebraicField.__subclasses__()) <= 1
True
```

class sage.rings.abc.**AlgebraicField_common**

Bases: *Field*

Abstract base class for *AlgebraicField_common*.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(QQbar, sage.rings.abc.AlgebraicField_common) #_
↪needs sage.rings.number_field
True
sage: isinstance(AA, sage.rings.abc.AlgebraicField_common) #_
↪needs sage.rings.number_field
True
```

By design, other than the abstract subclasses *AlgebraicField* and *AlgebraicRealField*, there is only one direct implementation subclass:

```
sage: sage.rings.abc.AlgebraicField_common.__subclasses__() #_
↪needs sage.rings.number_field
[<class 'sage.rings.abc.AlgebraicField'>,
 <class 'sage.rings.abc.AlgebraicRealField'>,
 <class 'sage.rings.qqbar.AlgebraicField_common'>]

sage: len(sage.rings.abc.AlgebraicField_common.__subclasses__()) <= 3
True
```

class sage.rings.abc.**AlgebraicRealField**

Bases: *AlgebraicField_common*

Abstract base class for *AlgebraicRealField*.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(QQbar, sage.rings.abc.AlgebraicRealField) #_
↳needs sage.rings.number_field
False
sage: isinstance(AA, sage.rings.abc.AlgebraicRealField) #_
↳needs sage.rings.number_field
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.AlgebraicRealField.__subclasses__() #_
↳needs sage.rings.number_field
[<class 'sage.rings.qqbar.AlgebraicRealField'>]

sage: len(sage.rings.abc.AlgebraicRealField.__subclasses__()) <= 1
True
```

class sage.rings.abc.**CallableSymbolicExpressionRing**

Bases: *SymbolicRing*

Abstract base class for *CallableSymbolicExpressionRing_class*.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: f = x.function(x).parent() #_
↳needs sage.symbolic
sage: isinstance(f, sage.rings.abc.CallableSymbolicExpressionRing) #_
↳needs sage.symbolic
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.CallableSymbolicExpressionRing.__subclasses__() #_
↳needs sage.symbolic
[<class 'sage.symbolic.callable.CallableSymbolicExpressionRing_class'>]

sage: len(sage.rings.abc.CallableSymbolicExpressionRing.__subclasses__()) <= 1
True
```

class sage.rings.abc.**ComplexBallField**

Bases: *Field*

Abstract base class for *ComplexBallField*.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(CBF, sage.rings.abc.ComplexBallField) #_
↪needs sage.libs.flint
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.ComplexBallField.__subclasses__() #_
↪needs sage.libs.flint
[<class 'sage.rings.complex_arb.ComplexBallField'>]

sage: len(sage.rings.abc.ComplexBallField.__subclasses__()) <= 1
True
```

class sage.rings.abc.ComplexDoubleField

Bases: *Field*

Abstract base class for `ComplexDoubleField_class`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(CDF, sage.rings.abc.ComplexDoubleField) #_
↪needs sage.rings.complex_double
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.ComplexDoubleField.__subclasses__() #_
↪needs sage.rings.complex_double
[<class 'sage.rings.complex_double.ComplexDoubleField_class'>]

sage: len(sage.rings.abc.ComplexDoubleField.__subclasses__()) <= 1
True
```

class sage.rings.abc.ComplexField

Bases: *Field*

Abstract base class for `ComplexField_class`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(CC, sage.rings.abc.ComplexField) #_
↪needs sage.rings.real_mpfr
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.ComplexField.__subclasses__() #_
↪needs sage.rings.real_mpfr
[<class 'sage.rings.complex_mpfr.ComplexField_class'>]

sage: len(sage.rings.abc.ComplexField.__subclasses__()) <= 1
True
```

class sage.rings.abc.ComplexIntervalField

Bases: *Field*

Abstract base class for `ComplexIntervalField_class`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(CIF, sage.rings.abc.ComplexIntervalField) #_
↪needs sage.rings.complex_interval_field
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.ComplexIntervalField.__subclasses__() #_
↪needs sage.rings.complex_interval_field
[<class 'sage.rings.complex_interval_field.ComplexIntervalField_class'>]

sage: len(sage.rings.abc.ComplexIntervalField.__subclasses__()) <= 1
True
```

class sage.rings.abc.IntegerModRing

Bases: `object`

Abstract base class for `IntegerModRing_generic`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(Integers(7), sage.rings.abc.IntegerModRing)
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.IntegerModRing.__subclasses__()
[<class 'sage.rings.finite_rings.integer_mod_ring.IntegerModRing_generic'>]

sage: len(sage.rings.abc.IntegerModRing.__subclasses__()) <= 1
True
```

class sage.rings.abc.NumberField_cyclotomic

Bases: *Field*

Abstract base class for `NumberField_cyclotomic`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: K.<zeta> = CyclotomicField(15) #_
↪needs sage.rings.number_field
sage: isinstance(K, sage.rings.abc.NumberField_cyclotomic) #_
↪needs sage.rings.number_field
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.NumberField_cyclotomic.__subclasses__() #_
↳needs sage.rings.number_field
[<class 'sage.rings.number_field.number_field.NumberField_cyclotomic'>]

sage: len(sage.rings.abc.NumberField_cyclotomic.__subclasses__()) <= 1
True
```

class sage.rings.abc.NumberField_quadratic

Bases: *Field*

Abstract base class for *NumberField_quadratic*.

This class is defined for the purpose of *isinstance* tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: K.<sqrt2> = QuadraticField(2) #_
↳needs sage.rings.number_field
sage: isinstance(K, sage.rings.abc.NumberField_quadratic) #_
↳needs sage.rings.number_field
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.NumberField_quadratic.__subclasses__() #_
↳needs sage.rings.number_field
[<class 'sage.rings.number_field.number_field.NumberField_quadratic'>]

sage: len(sage.rings.abc.NumberField_quadratic.__subclasses__()) <= 1
True
```

class sage.rings.abc.Order

Bases: object

Abstract base class for *Order*.

This class is defined for the purpose of *isinstance* tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: x = polygen(ZZ, 'x')
sage: K.<a> = NumberField(x^2 + 1); O = K.order(2*a) #_
↳needs sage.rings.number_field
sage: isinstance(O, sage.rings.abc.Order) #_
↳needs sage.rings.number_field
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.Order.__subclasses__() #_
↳needs sage.rings.number_field
[<class 'sage.rings.number_field.order.Order'>]

sage: len(sage.rings.abc.Order.__subclasses__()) <= 1
True
```

class sage.rings.abc.RealBallField

Bases: *Field*

Abstract base class for `RealBallField`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(RBF, sage.rings.abc.RealBallField) #_
↳needs sage.libs.flint
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.RealBallField.__subclasses__() #_
↳needs sage.libs.flint
[<class 'sage.rings.real_arb.RealBallField'>]

sage: len(sage.rings.abc.RealBallField.__subclasses__()) <= 1
True
```

class sage.rings.abc.RealDoubleField

Bases: *Field*

Abstract base class for `RealDoubleField_class`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(RDF, sage.rings.abc.RealDoubleField)
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.RealDoubleField.__subclasses__()
[<class 'sage.rings.real_double.RealDoubleField_class'>]

sage: len(sage.rings.abc.RealDoubleField.__subclasses__()) <= 1
True
```

class sage.rings.abc.RealField

Bases: *Field*

Abstract base class for `RealField_class`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(RR, sage.rings.abc.RealField) #_
↳needs sage.rings.real_mpr
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.RealField.__subclasses__() #_
↳needs sage.rings.real_mpfr
[<class 'sage.rings.real_mpfr.RealField_class'>]

sage: len(sage.rings.abc.RealField.__subclasses__()) <= 1
True
```

class sage.rings.abc.**RealIntervalField**

Bases: *Field*

Abstract base class for `RealIntervalField_class`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(RIF, sage.rings.abc.RealIntervalField) #_
↳needs sage.rings.real_interval_field
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.RealIntervalField.__subclasses__() #_
↳needs sage.rings.real_interval_field
[<class 'sage.rings.real_mpfi.RealIntervalField_class'>]

sage: len(sage.rings.abc.RealIntervalField.__subclasses__()) <= 1
True
```

class sage.rings.abc.**SymbolicRing**

Bases: *CommutativeRing*

Abstract base class for `SymbolicRing`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(SR, sage.rings.abc.SymbolicRing) #_
↳needs sage.symbolic
True
```

By design, other than the abstract subclass `CallableSymbolicExpressionRing`, there is only one direct implementation subclass:

```
sage: sage.rings.abc.SymbolicRing.__subclasses__() #_
↳needs sage.symbolic
[<class 'sage.rings.abc.CallableSymbolicExpressionRing'>,
 <class 'sage.symbolic.ring.SymbolicRing'>]

sage: len(sage.rings.abc.SymbolicRing.__subclasses__()) <= 2
True
```

class sage.rings.abc.**UniversalCyclotomicField**

Bases: *Field*

Abstract base class for `UniversalCyclotomicField`.

This class is defined for the purpose of `isinstance()` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: K = UniversalCyclotomicField() #_
↳needs sage.libs.gap sage.rings.number_field
sage: isinstance(K, sage.rings.abc.UniversalCyclotomicField) #_
↳needs sage.libs.gap sage.rings.number_field
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.UniversalCyclotomicField.__subclasses__() #_
↳needs sage.libs.gap sage.rings.number_field
[<class 'sage.rings.universal_cyclotomic_field.UniversalCyclotomicField'>]

sage: len(sage.rings.abc.NumberField_cyclotomic.__subclasses__()) <= 1
True
```

class `sage.rings.abc.pAdicField`

Bases: *Field*

Abstract base class for `pAdicFieldGeneric`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(Zp(5), sage.rings.abc.pAdicField) #_
↳needs sage.rings.padics
False
sage: isinstance(Qp(5), sage.rings.abc.pAdicField) #_
↳needs sage.rings.padics
True
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.pAdicField.__subclasses__() #_
↳needs sage.rings.padics
[<class 'sage.rings.padics.generic_nodes.pAdicFieldGeneric'>]

sage: len(sage.rings.abc.pAdicField.__subclasses__()) <= 1
True
```

class `sage.rings.abc.pAdicRing`

Bases: *IntegralDomain*

Abstract base class for `pAdicRingGeneric`.

This class is defined for the purpose of `isinstance` tests. It should not be instantiated.

EXAMPLES:

```
sage: import sage.rings.abc
sage: isinstance(Zp(5), sage.rings.abc.pAdicRing) #_
↳needs sage.rings.padics
True
sage: isinstance(Qp(5), sage.rings.abc.pAdicRing) #_
```

(continues on next page)

(continued from previous page)

```
↪needs sage.rings.padics  
False
```

By design, there is a unique direct subclass:

```
sage: sage.rings.abc.pAdicRing.__subclasses__() #  
↪needs sage.rings.padics  
[<class 'sage.rings.padics.generic_nodes.pAdicRingGeneric'>]  
  
sage: len(sage.rings.abc.pAdicRing.__subclasses__()) <= 1  
True
```

2.1 Ideals of commutative rings

Sage provides functionality for computing with ideals. One can create an ideal in any commutative or non-commutative ring R by giving a list of generators, using the notation `R.ideal([a,b,...])`. The case of non-commutative rings is implemented in `noncommutative_ideals`.

A more convenient notation may be $R^*[a,b,\dots]$ or $[a,b,\dots]*R$. If R is non-commutative, the former creates a left and the latter a right ideal, and $R^*[a,b,\dots]*R$ creates a two-sided ideal.

```
sage.rings.ideal.Cyclic(R, n=None, homog=False, singular=None)
```

Ideal of cyclic n -roots from 1-st n variables of R if R is coercible to `Singular`.

INPUT:

- `R` – base ring to construct ideal for
- `n` – number of cyclic roots (default: `None`). If `None`, then `n` is set to `R.ngens()`.
- `homog` – (default: `False`) if `True` a homogeneous ideal is returned using the last variable in the ideal
- `singular` – `singular` instance to use

Note: `R` will be set as the active ring in `Singular`

EXAMPLES:

An example from a multivariate polynomial ring over the rationals:

```
sage: P.<x,y,z> = PolynomialRing(QQ, 3, order='lex')
sage: I = sage.rings.ideal.Cyclic(P); I #_
↳needs sage.libs.singular
Ideal (x + y + z, x*y + x*z + y*z, x*y*z - 1)
of Multivariate Polynomial Ring in x, y, z over Rational Field
sage: I.groebner_basis() #_
↳needs sage.libs.singular
[x + y + z, y^2 + y*z + z^2, z^3 - 1]
```

We compute a Groebner basis for cyclic 6, which is a standard benchmark and test ideal:

```
sage: R.<x,y,z,t,u,v> = QQ['x,y,z,t,u,v']
sage: I = sage.rings.ideal.Cyclic(R, 6) #_
↳needs sage.libs.singular
sage: B = I.groebner_basis() #_
```

(continues on next page)

(continued from previous page)

```
↪needs sage.libs.singular
sage: len(B) #_
↪needs sage.libs.singular
45
```

sage.rings.ideal.**FieldIdeal**(*R*)

Let $q = R.\text{base_ring}().\text{order}()$ and $(x_0, \dots, x_n) = R.\text{gens}()$ then if q is finite this constructor returns

$$\langle x_0^q - x_0, \dots, x_n^q - x_n \rangle.$$

We call this ideal the field ideal and the generators the field equations.

EXAMPLES:

The field ideal generated from the polynomial ring over two variables in the finite field of size 2:

```
sage: P.<x,y> = PolynomialRing(GF(2), 2)
sage: I = sage.rings.ideal.FieldIdeal(P); I
Ideal (x^2 + x, y^2 + y) of
Multivariate Polynomial Ring in x, y over Finite Field of size 2
```

Another, similar example:

```
sage: Q.<x1,x2,x3,x4> = PolynomialRing(GF(2^4, name='alpha'), 4) #_
↪needs sage.rings.finite_rings
sage: J = sage.rings.ideal.FieldIdeal(Q); J #_
↪needs sage.rings.finite_rings
Ideal (x1^16 + x1, x2^16 + x2, x3^16 + x3, x4^16 + x4) of
Multivariate Polynomial Ring in x1, x2, x3, x4
over Finite Field in alpha of size 2^4
```

sage.rings.ideal.**Ideal**(*args, **kws)

Create the ideal in ring with given generators.

There are some shorthand notations for creating an ideal, in addition to using the *Ideal()* function:

- $R.\text{ideal}(\text{gens}, \text{coerce}=\text{True})$
- $\text{gens} * R$
- $R * \text{gens}$

INPUT:

- R – A ring (optional; if not given, will try to infer it from gens)
- gens – list of elements generating the ideal
- coerce – bool (default: True); whether gens need to be coerced into the ring.

OUTPUT: The ideal of ring generated by gens.

EXAMPLES:

```
sage: R.<x> = ZZ[]
sage: I = R.ideal([4 + 3*x + x^2, 1 + x^2])
sage: I
Ideal (x^2 + 3*x + 4, x^2 + 1) of Univariate Polynomial Ring in x over Integer_
↪Ring
sage: Ideal(R, [4 + 3*x + x^2, 1 + x^2])
```

(continues on next page)

(continued from previous page)

```

Ideal (x^2 + 3*x + 4, x^2 + 1) of Univariate Polynomial Ring in x over Integer
↪Ring
sage: Ideal((4 + 3*x + x^2, 1 + x^2))
Ideal (x^2 + 3*x + 4, x^2 + 1) of Univariate Polynomial Ring in x over Integer
↪Ring
    
```

```

sage: ideal(x^2-2*x+1, x^2-1)
Ideal (x^2 - 2*x + 1, x^2 - 1) of Univariate Polynomial Ring in x over Integer
↪Ring
sage: ideal([x^2-2*x+1, x^2-1])
Ideal (x^2 - 2*x + 1, x^2 - 1) of Univariate Polynomial Ring in x over Integer
↪Ring
sage: l = [x^2-2*x+1, x^2-1]
sage: ideal(f^2 for f in l)
Ideal (x^4 - 4*x^3 + 6*x^2 - 4*x + 1, x^4 - 2*x^2 + 1) of
Univariate Polynomial Ring in x over Integer Ring
    
```

This example illustrates how Sage finds a common ambient ring for the ideal, even though 1 is in the integers (in this case).

```

sage: R.<t> = ZZ['t']
sage: i = ideal(1,t,t^2)
sage: i
Ideal (1, t, t^2) of Univariate Polynomial Ring in t over Integer Ring
sage: ideal(1/2,t,t^2)
Principal ideal (1) of Univariate Polynomial Ring in t over Rational Field
    
```

This shows that the issues at [Issue #1104](#) are resolved:

```

sage: Ideal(3, 5)
Principal ideal (1) of Integer Ring
sage: Ideal(ZZ, 3, 5)
Principal ideal (1) of Integer Ring
sage: Ideal(2, 4, 6)
Principal ideal (2) of Integer Ring
    
```

You have to provide enough information that Sage can figure out which ring to put the ideal in.

```

sage: I = Ideal([])
Traceback (most recent call last):
...
ValueError: unable to determine which ring to embed the ideal in

sage: I = Ideal()
Traceback (most recent call last):
...
ValueError: need at least one argument
    
```

Note that some rings use different ideal implementations than the standard, even if they are PIDs.:

```

sage: R.<x> = GF(5)[[]]
sage: I = R * (x^2 + 3)
sage: type(I)
<class 'sage.rings.polynomial.ideal.Ideal_1poly_field'>
    
```

You can also pass in a specific ideal type:

```
sage: from sage.rings.ideal import Ideal_pid
sage: I = Ideal(x^2+3, ideal_class=Ideal_pid)
sage: type(I)
<class 'sage.rings.ideal.Ideal_pid'>
```

class sage.rings.ideal.Ideal_fractional (ring, gens, coerce=True, **kwds)

Bases: *Ideal_generic*

Fractional ideal of a ring.

See *Ideal()*.

class sage.rings.ideal.Ideal_generic (ring, gens, coerce=True, **kwds)

Bases: *MonoidElement*

An ideal.

See *Ideal()*.

absolute_norm()

Returns the absolute norm of this ideal.

In the general case, this is just the ideal itself, since the ring it lies in can't be implicitly assumed to be an extension of anything.

We include this function for compatibility with cases such as ideals in number fields.

Todo: Implement this method.

EXAMPLES:

```
sage: R.<t> = GF(9, names='a')[] #_
↳needs sage.rings.finite_rings
sage: I = R.ideal(t^4 + t + 1) #_
↳needs sage.rings.finite_rings
sage: I.absolute_norm() #_
↳needs sage.rings.finite_rings
Traceback (most recent call last):
...
NotImplementedError
```

apply_morphism (*phi*)

Apply the morphism *phi* to every element of this ideal. Returns an ideal in the domain of *phi*.

EXAMPLES:

```
sage: # needs sage.rings.real_mpr
sage: psi = CC['x'].hom([-CC['x'].0])
sage: J = ideal([CC['x'].0 + 1]); J
Principal ideal (x + 1.000000000000000) of Univariate Polynomial Ring in x
over Complex Field with 53 bits of precision
sage: psi(J)
Principal ideal (x - 1.000000000000000) of Univariate Polynomial Ring in x
over Complex Field with 53 bits of precision
sage: J.apply_morphism(psi)
Principal ideal (x - 1.000000000000000) of Univariate Polynomial Ring in x
over Complex Field with 53 bits of precision
```

```

sage: psi = ZZ['x'].hom([-ZZ['x'].0])
sage: J = ideal([ZZ['x'].0, 2]); J
Ideal (x, 2) of Univariate Polynomial Ring in x over Integer Ring
sage: psi(J)
Ideal (-x, 2) of Univariate Polynomial Ring in x over Integer Ring
sage: J.apply_morphism(psi)
Ideal (-x, 2) of Univariate Polynomial Ring in x over Integer Ring
    
```

associated_primes()

Return the list of associated prime ideals of this ideal.

EXAMPLES:

```

sage: R = ZZ['x']
sage: I = R.ideal(7)
sage: I.associated_primes()
Traceback (most recent call last):
...
NotImplementedError
    
```

base_ring()

Returns the base ring of this ideal.

EXAMPLES:

```

sage: R = ZZ
sage: I = 3*R; I
Principal ideal (3) of Integer Ring
sage: J = 2*I; J
Principal ideal (6) of Integer Ring
sage: I.base_ring(); J.base_ring()
Integer Ring
Integer Ring
    
```

We construct an example of an ideal of a quotient ring:

```

sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: I = R.ideal(x^2 - 2)
sage: I.base_ring()
Rational Field
    
```

And p -adic numbers:

```

sage: R = Zp(7, prec=10); R #_
↪needs sage.rings.padics
7-adic Ring with capped relative precision 10
sage: I = 7*R; I #_
↪needs sage.rings.padics
Principal ideal (7 + O(7^11)) of 7-adic Ring with capped relative precision 10
sage: I.base_ring() #_
↪needs sage.rings.padics
7-adic Ring with capped relative precision 10
    
```

category()

Return the category of this ideal.

Note: category is dependent on the ring of the ideal.

EXAMPLES:

```
sage: P.<x> = ZZ[]
sage: I = ZZ.ideal(7)
sage: J = P.ideal(7, x)
sage: K = P.ideal(7)
sage: I.category()
Category of ring ideals in Integer Ring
sage: J.category()
Category of ring ideals in Univariate Polynomial Ring in x
over Integer Ring
sage: K.category()
Category of ring ideals in Univariate Polynomial Ring in x
over Integer Ring
```

embedded_primes()

Return the list of embedded primes of this ideal.

EXAMPLES:

```
sage: R.<x, y> = QQ[]
sage: I = R.ideal(x^2, x*y)
sage: I.embedded_primes() #_
↳needs sage.libs.singular
[Ideal (y, x) of Multivariate Polynomial Ring in x, y over Rational Field]
```

free_resolution(*args, **kws)

Return a free resolution of `self`.

For input options, see `FreeResolution`.

EXAMPLES:

```
sage: R.<x> = PolynomialRing(QQ)
sage: I = R.ideal([x^4 + 3*x^2 + 2])
sage: I.free_resolution() #_
↳needs sage.modules
S^1 <-- S^1 <-- 0
```

gen(i)

Return the *i*-th generator in the current basis of this ideal.

EXAMPLES:

```
sage: P.<x, y> = PolynomialRing(QQ, 2)
sage: I = Ideal([x, y+1]); I
Ideal (x, y + 1) of Multivariate Polynomial Ring in x, y over Rational Field
sage: I.gen(1)
y + 1

sage: ZZ.ideal(5, 10).gen()
5
```

gens()

Return a set of generators / a basis of `self`.

This is the set of generators provided during creation of this ideal.

EXAMPLES:

```
sage: P.<x,y> = PolynomialRing(QQ,2)
sage: I = Ideal([x,y+1]); I
Ideal (x, y + 1) of Multivariate Polynomial Ring in x, y over Rational Field
sage: I.gens()
[x, y + 1]
```

```
sage: ZZ.ideal(5,10).gens()
(5,)
```

gens_reduced()

Same as `gens()` for this ideal, since there is currently no special `gens_reduced` algorithm implemented for this ring.

This method is provided so that ideals in \mathbf{Z} have the method `gens_reduced()`, just like ideals of number fields.

EXAMPLES:

```
sage: ZZ.ideal(5).gens_reduced()
(5,)
```

graded_free_resolution(*args, **kws)

Return a graded free resolution of `self`.

For input options, see `GradedFiniteFreeResolution`.

EXAMPLES:

```
sage: R.<x> = PolynomialRing(QQ)
sage: I = R.ideal([x^3])
sage: I.graded_free_resolution()
↪needs sage.modules
S(0) <-- S(-3) <-- 0
```

is_maximal()

Return True if the ideal is maximal in the ring containing the ideal.

Todo: This is not implemented for many rings. Implement it!

EXAMPLES:

```
sage: R = ZZ
sage: I = R.ideal(7)
sage: I.is_maximal()
True
sage: R.ideal(16).is_maximal()
False
sage: S = Integers(8)
sage: S.ideal(0).is_maximal()
False
sage: S.ideal(2).is_maximal()
True
```

(continues on next page)

(continued from previous page)

```
sage: S.ideal(4).is_maximal()
False
```

is_primary ($P=None$)

Returns True if this ideal is primary (or P -primary, if a prime ideal P is specified).

Recall that an ideal I is primary if and only if I has a unique associated prime (see page 52 in [AM1969]). If this prime is P , then I is said to be P -primary.

INPUT:

- P – (default: None) a prime ideal in the same ring

EXAMPLES:

```
sage: R.<x, y> = QQ[]
sage: I = R.ideal([x^2, x*y])
sage: I.is_primary() #_
↳needs sage.libs.singular
False
sage: J = I.primary_decomposition()[1]; J #_
↳needs sage.libs.singular
Ideal (y, x^2) of Multivariate Polynomial Ring in x, y over Rational Field
sage: J.is_primary() #_
↳needs sage.libs.singular
True
sage: J.is_prime() #_
↳needs sage.libs.singular
False
```

Some examples from the Macaulay2 documentation:

```
sage: # needs sage.rings.finite_rings
sage: R.<x, y, z> = GF(101)[]
sage: I = R.ideal([y^6])
sage: I.is_primary() #_
↳needs sage.libs.singular
True
sage: I.is_primary(R.ideal([y])) #_
↳needs sage.libs.singular
True
sage: I = R.ideal([x^4, y^7])
sage: I.is_primary() #_
↳needs sage.libs.singular
True
sage: I = R.ideal([x*y, y^2])
sage: I.is_primary() #_
↳needs sage.libs.singular
False
```

Note: This uses the list of associated primes.

is_prime ()

Return True if this ideal is prime.

EXAMPLES:

```

sage: R.<x, y> = QQ[]
sage: I = R.ideal([x, y])
sage: I.is_prime() # a maximal ideal #_
↳needs sage.libs.singular
True
sage: I = R.ideal([x^2 - y])
sage: I.is_prime() # a non-maximal prime ideal #_
↳needs sage.libs.singular
True
sage: I = R.ideal([x^2, y])
sage: I.is_prime() # a non-prime primary ideal #_
↳needs sage.libs.singular
False
sage: I = R.ideal([x^2, x*y])
sage: I.is_prime() # a non-prime non-primary ideal #_
↳needs sage.libs.singular
False

sage: S = Integers(8)
sage: S.ideal(0).is_prime()
False
sage: S.ideal(2).is_prime()
True
sage: S.ideal(4).is_prime()
False

```

Note that this method is not implemented for all rings where it could be:

```

sage: R.<x> = ZZ[]
sage: I = R.ideal(7)
sage: I.is_prime() # when implemented, should be True
Traceback (most recent call last):
...
NotImplementedError

```

Note: For general rings, uses the list of associated primes.

`is_principal()`

Returns True if the ideal is principal in the ring containing the ideal.

Todo: Code is naive. Only keeps track of ideal generators as set during initialization of the ideal. (Can the base ring change? See example below.)

EXAMPLES:

```

sage: R.<x> = ZZ[]
sage: I = R.ideal(2, x)
sage: I.is_principal()
Traceback (most recent call last):
...
NotImplementedError
sage: J = R.base_extend(QQ).ideal(2, x)
sage: J.is_principal()
True

```

is_trivial()

Return True if this ideal is (0) or (1).

minimal_associated_primes()

Return the list of minimal associated prime ideals of this ideal.

EXAMPLES:

```
sage: R = ZZ['x']
sage: I = R.ideal(7)
sage: I.minimal_associated_primes()
Traceback (most recent call last):
...
NotImplementedError
```

ngens()

Return the number of generators in the basis.

EXAMPLES:

```
sage: P.<x,y> = PolynomialRing(QQ,2)
sage: I = Ideal([x,y+1]); I
Ideal (x, y + 1) of Multivariate Polynomial Ring in x, y over Rational Field
sage: I.ngens()
2

sage: ZZ.ideal(5,10).ngens()
1
```

norm()

Returns the norm of this ideal.

In the general case, this is just the ideal itself, since the ring it lies in can't be implicitly assumed to be an extension of anything.

We include this function for compatibility with cases such as ideals in number fields.

EXAMPLES:

```
sage: R.<t> = GF(8, names='a')[] #_
↳needs sage.rings.finite_rings
sage: I = R.ideal(t^4 + t + 1) #_
↳needs sage.rings.finite_rings
sage: I.norm() #_
↳needs sage.rings.finite_rings
Principal ideal (t^4 + t + 1) of Univariate Polynomial Ring in t
over Finite Field in a of size 2^3
```

primary_decomposition()

Return a decomposition of this ideal into primary ideals.

EXAMPLES:

```
sage: R = ZZ['x']
sage: I = R.ideal(7)
sage: I.primary_decomposition()
Traceback (most recent call last):
...
NotImplementedError
```

random_element (*args, **kws)

Return a random element in this ideal.

EXAMPLES:

```
sage: P.<a,b,c> = GF(5)[[]]
sage: I = P.ideal([a^2, a*b + c, c^3])
sage: I.random_element() # random
2*a^5*c + a^2*b*c^4 + ... + O(a, b, c)^13
```

reduce (f)

Return the reduction of the element of f modulo self .

This is an element of R that is equivalent modulo I to f where I is self .

EXAMPLES:

```
sage: ZZ.ideal(5).reduce(17)
2
sage: parent(ZZ.ideal(5).reduce(17))
Integer Ring
```

ring ()

Return the ring containing this ideal.

EXAMPLES:

```
sage: R = ZZ
sage: I = 3*R; I
Principal ideal (3) of Integer Ring
sage: J = 2*I; J
Principal ideal (6) of Integer Ring
sage: I.ring(); J.ring()
Integer Ring
Integer Ring
```

Note that $\text{self.ring}()$ is different from $\text{self.base_ring}()$

```
sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: I = R.ideal(x^2 - 2)
sage: I.base_ring()
Rational Field
sage: I.ring()
Univariate Polynomial Ring in x over Rational Field
```

Another example using polynomial rings:

```
sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: I = R.ideal(x^2 - 3)
sage: I.ring()
Univariate Polynomial Ring in x over Rational Field
sage: Rbar = R.quotient(I, names='a') #_
↪needs sage.libs.pari
sage: S = PolynomialRing(Rbar, 'y'); y = Rbar.gen(); S #_
↪needs sage.libs.pari
Univariate Polynomial Ring in y over
Univariate Quotient Polynomial Ring in a over Rational Field with modulus x^
↪2 - 3
```

(continues on next page)

(continued from previous page)

```
sage: J = S.ideal(y^2 + 1) #_
↳needs sage.libs.pari
sage: J.ring() #_
↳needs sage.libs.pari
Univariate Polynomial Ring in y over
Univariate Quotient Polynomial Ring in a over Rational Field with modulus x^
↳2 - 3
```

class sage.rings.ideal.**Ideal_pid**(ring, gens, coerce=True, **kwds)

Bases: *Ideal_principal*

An ideal of a principal ideal domain.

See *Ideal()*.

EXAMPLES:

```
sage: I = 8*ZZ
sage: I
Principal ideal (8) of Integer Ring
```

gcd(other)

Returns the greatest common divisor of the principal ideal with the ideal *other*; that is, the largest principal ideal contained in both the ideal and *other*

Todo: This is not implemented in the case when *other* is neither principal nor when the generator of *self* is contained in *other*. Also, it seems that this class is used only in PIDs—is this redundant?

Note: The second example is broken.

EXAMPLES:

An example in the principal ideal domain **Z**:

```
sage: R = ZZ
sage: I = R.ideal(42)
sage: J = R.ideal(70)
sage: I.gcd(J)
Principal ideal (14) of Integer Ring
sage: J.gcd(I)
Principal ideal (14) of Integer Ring
```

is_maximal()

Returns whether this ideal is maximal.

Principal ideal domains have Krull dimension 1 (or 0), so an ideal is maximal if and only if it's prime (and nonzero if the ring is not a field).

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: R.<t> = GF(5)[]
sage: p = R.ideal(t^2 + 2)
sage: p.is_maximal()
```

(continues on next page)

(continued from previous page)

```

True
sage: p = R.ideal(t^2 + 1)
sage: p.is_maximal()
False
sage: p = R.ideal(0)
sage: p.is_maximal()
False
sage: p = R.ideal(1)
sage: p.is_maximal()
False

```

is_prime()

Return True if the ideal is prime.

This relies on the ring elements having a method `is_irreducible()` implemented, since an ideal (a) is prime iff a is irreducible (or 0).

EXAMPLES:

```

sage: ZZ.ideal(2).is_prime()
True
sage: ZZ.ideal(-2).is_prime()
True
sage: ZZ.ideal(4).is_prime()
False
sage: ZZ.ideal(0).is_prime()
True
sage: R.<x> = QQ[]
sage: P = R.ideal(x^2 + 1); P
Principal ideal (x^2 + 1) of Univariate Polynomial Ring in x over Rational_
↪Field
sage: P.is_prime() #_
↪needs sage.libs.pari
True

```

In fields, only the zero ideal is prime:

```

sage: RR.ideal(0).is_prime()
True
sage: RR.ideal(7).is_prime()
False

```

reduce(f)

Return the reduction of f modulo `self`.

EXAMPLES:

```

sage: I = 8*ZZ
sage: I.reduce(10)
2
sage: n = 10; n.mod(I)
2

```

residue_field()

Return the residue class field of this ideal, which must be prime.

Todo: Implement this for more general rings. Currently only defined for \mathbf{Z} and for number field orders.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: P = ZZ.ideal(61); P
Principal ideal (61) of Integer Ring
sage: F = P.residue_field(); F
Residue field of Integers modulo 61
sage: pi = F.reduction_map(); pi
Partially defined reduction map:
  From: Rational Field
  To:   Residue field of Integers modulo 61
sage: pi(123/234)
6
sage: pi(1/61)
Traceback (most recent call last):
...
ZeroDivisionError: Cannot reduce rational 1/61 modulo 61: it has negative
↳valuation
sage: lift = F.lift_map(); lift
Lifting map:
  From: Residue field of Integers modulo 61
  To:   Integer Ring
sage: lift(F(12345/67890))
33
sage: (12345/67890) % 61
33
```

class `sage.rings.ideal.Ideal_principal` (*ring, gens, coerce=True, **kwds*)

Bases: *Ideal_generic*

A principal ideal.

See *Ideal()*.

divides (*other*)

Return True if self divides other.

EXAMPLES:

```
sage: P.<x> = PolynomialRing(QQ)
sage: I = P.ideal(x)
sage: J = P.ideal(x^2)
sage: I.divides(J)
True
sage: J.divides(I)
False
```

gen (*i=0*)

Return the generator of the principal ideal.

The generator is an element of the ring containing the ideal.

EXAMPLES:

A simple example in the integers:


```

sage: R = ZZ
sage: I = R.ideal(7)
sage: J = R.ideal(7, 14)
sage: I.gen(); J.gen()
7
7
    
```

Note that the generator belongs to the ring from which the ideal was initialized:

```

sage: R.<x> = ZZ[]
sage: I = R.ideal(x)
sage: J = R.base_extend(QQ).ideal(2, x)
sage: a = I.gen(); a
x
sage: b = J.gen(); b
1
sage: a.base_ring()
Integer Ring
sage: b.base_ring()
Rational Field
    
```

`is_principal()`

Returns `True` if the ideal is principal in the ring containing the ideal. When the ideal construction is explicitly principal (i.e. when we define an ideal with one element) this is always the case.

EXAMPLES:

Note that Sage automatically coerces ideals into principal ideals during initialization:

```

sage: R.<x> = ZZ[]
sage: I = R.ideal(x)
sage: J = R.ideal(2, x)
sage: K = R.base_extend(QQ).ideal(2, x)
sage: I
Principal ideal (x) of Univariate Polynomial Ring in x
over Integer Ring
sage: J
Ideal (2, x) of Univariate Polynomial Ring in x over Integer Ring
sage: K
Principal ideal (1) of Univariate Polynomial Ring in x
over Rational Field
sage: I.is_principal()
True
sage: K.is_principal()
True
    
```

`sage.rings.ideal.Katsura` (R , $n=None$, $homog=False$, $singular=None$)

n -th katsura ideal of R if R is coercible to `Singular`.

INPUT:

- R – base ring to construct ideal for
- n – (default: `None`) which katsura ideal of R . If `None`, then n is set to `R.ngens()`.
- `homog` – if `True` a homogeneous ideal is returned using the last variable in the ideal (default: `False`)
- `singular` – singular instance to use

EXAMPLES:

```
sage: P.<x,y,z> = PolynomialRing(QQ, 3)
sage: I = sage.rings.ideal.Katsura(P, 3); I #_
↳needs sage.libs.singular
Ideal (x + 2*y + 2*z - 1, x^2 + 2*y^2 + 2*z^2 - x, 2*x*y + 2*y*z - y)
of Multivariate Polynomial Ring in x, y, z over Rational Field
```

```
sage: Q.<x> = PolynomialRing(QQ, implementation="singular") #_
↳needs sage.libs.singular
sage: J = sage.rings.ideal.Katsura(Q,1); J #_
↳needs sage.libs.singular
Ideal (x - 1) of Multivariate Polynomial Ring in x over Rational Field
```

`sage.rings.ideal.is_Ideal(x)`

Return True if object is an ideal of a ring.

EXAMPLES:

A simple example involving the ring of integers. Note that Sage does not interpret rings objects themselves as ideals. However, one can still explicitly construct these ideals:

```
sage: from sage.rings.ideal import is_Ideal
sage: R = ZZ
sage: is_Ideal(R)
False
sage: 1*R; is_Ideal(1*R)
Principal ideal (1) of Integer Ring
True
sage: 0*R; is_Ideal(0*R)
Principal ideal (0) of Integer Ring
True
```

Sage recognizes ideals of polynomial rings as well:

```
sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: I = R.ideal(x^2 + 1); I
Principal ideal (x^2 + 1) of Univariate Polynomial Ring in x over Rational Field
sage: is_Ideal(I)
True
sage: is_Ideal((x^2 + 1)*R)
True
```

2.2 Monoid of ideals in a commutative ring

WARNING: This is used by some rings that are not commutative!

```
sage: MS = MatrixSpace(QQ, 3, 3) #_
↳needs sage.modules
sage: type(MS.ideal(MS.one()).parent()) #_
↳needs sage.modules
<class 'sage.rings.ideal_monoid.IdealMonoid_c_with_category'>
```

`sage.rings.ideal_monoid.IdealMonoid(R)`

Return the monoid of ideals in the ring R.

EXAMPLES:

```

sage: R = QQ['x']
sage: from sage.rings.ideal_monoid import IdealMonoid
sage: IdealMonoid(R)
Monoid of ideals of Univariate Polynomial Ring in x over Rational Field
    
```

class sage.rings.ideal_monoid.IdealMonoid_c(*R*)

Bases: `Parent`

The monoid of ideals in a commutative ring.

Element

alias of `Ideal_generic`

ring()

Return the ring of which this is the ideal monoid.

EXAMPLES:

```

sage: R = QuadraticField(-23, 'a') #_
↪needs sage.rings.number_field
sage: from sage.rings.ideal_monoid import IdealMonoid
sage: M = IdealMonoid(R); M.ring() is R #_
↪needs sage.rings.number_field
True
    
```

2.3 Ideals of non-commutative rings

Generic implementation of one- and two-sided ideals of non-commutative rings.

AUTHOR:

- Simon King (2011-03-21), <simon.king@uni-jena.de>, Issue #7797.

EXAMPLES:

```

sage: MS = MatrixSpace(ZZ, 2, 2)
sage: MS*MS([0, 1, -2, 3])
Left Ideal
(
 [ 0  1]
 [-2  3]
)
of Full MatrixSpace of 2 by 2 dense matrices over Integer Ring
sage: MS([0, 1, -2, 3])*MS
Right Ideal
(
 [ 0  1]
 [-2  3]
)
of Full MatrixSpace of 2 by 2 dense matrices over Integer Ring
sage: MS*MS([0, 1, -2, 3])*MS
Twosided Ideal
(
 [ 0  1]
 [-2  3]
)
of Full MatrixSpace of 2 by 2 dense matrices over Integer Ring
    
```

See `letterplace_ideal` for a more elaborate implementation in the special case of ideals in free algebras.

class `sage.rings.noncommutative_ideals.IdealMonoid_nc` (*R*)

Bases: `IdealMonoid_c`

Base class for the monoid of ideals over a non-commutative ring.

Note: This class is essentially the same as `IdealMonoid_c`, but does not complain about non-commutative rings.

EXAMPLES:

```
sage: MS = MatrixSpace(ZZ,2,2)
sage: MS.ideal_monoid()
Monoid of ideals of Full MatrixSpace of 2 by 2 dense matrices over Integer Ring
```

class `sage.rings.noncommutative_ideals.Ideal_nc` (*ring, gens, coerce=True, side='twosided'*)

Bases: `Ideal_generic`

Generic non-commutative ideal.

All fancy stuff such as the computation of Groebner bases must be implemented in sub-classes. See `LetterplaceIdeal` for an example.

EXAMPLES:

```
sage: MS = MatrixSpace(QQ,2,2)
sage: I = MS*[MS.1,MS.2]; I
Left Ideal
(
  [0 1]
  [0 0],

  [0 0]
  [1 0]
)
of Full MatrixSpace of 2 by 2 dense matrices over Rational Field
sage: [MS.1,MS.2]*MS
Right Ideal
(
  [0 1]
  [0 0],

  [0 0]
  [1 0]
)
of Full MatrixSpace of 2 by 2 dense matrices over Rational Field
sage: MS*[MS.1,MS.2]*MS
Twosided Ideal
(
  [0 1]
  [0 0],

  [0 0]
  [1 0]
)
of Full MatrixSpace of 2 by 2 dense matrices over Rational Field
```

side()

Return a string that describes the sidedness of this ideal.

EXAMPLES:

```
sage: # needs sage.combinat
sage: A = SteenrodAlgebra(2)
sage: IL = A*[A.1+A.2,A.1^2]
sage: IR = [A.1+A.2,A.1^2]*A
sage: IT = A*[A.1+A.2,A.1^2]*A
sage: IL.side()
'left'
sage: IR.side()
'right'
sage: IT.side()
'twosided'
```


RING MORPHISMS

3.1 Homomorphisms of rings

We give a large number of examples of ring homomorphisms.

EXAMPLES:

Natural inclusion $\mathbf{Z} \hookrightarrow \mathbf{Q}$:

```
sage: H = Hom(ZZ, QQ)
sage: phi = H([1])
sage: phi(10)
10
sage: phi(3/1)
3
sage: phi(2/3)
Traceback (most recent call last):
...
TypeError: 2/3 fails to convert into the map's domain Integer Ring,
but a `pushforward` method is not properly implemented
```

There is no homomorphism in the other direction:

```
sage: H = Hom(QQ, ZZ)
sage: H([1])
Traceback (most recent call last):
...
ValueError: relations do not all (canonically) map to 0
under map determined by images of generators
```

EXAMPLES:

Reduction to finite field:

```
sage: # needs sage.rings.finite_rings
sage: H = Hom(ZZ, GF(9, 'a'))
sage: phi = H([1])
sage: phi(5)
2
sage: psi = H([4])
sage: psi(5)
2
```

Map from single variable polynomial ring:

```

sage: R.<x> = ZZ[]
sage: phi = R.hom([2], GF(5)); phi
Ring morphism:
  From: Univariate Polynomial Ring in x over Integer Ring
  To:   Finite Field of size 5
  Defn: x |--> 2
sage: phi(x + 12)
4

```

Identity map on the real numbers:

```

sage: # needs sage.rings.real_mpfr
sage: f = RR.hom([RR(1)]); f
Ring endomorphism of Real Field with 53 bits of precision
  Defn: 1.000000000000000 |--> 1.000000000000000
sage: f(2.5)
2.500000000000000
sage: f = RR.hom([2.0])
Traceback (most recent call last):
...
ValueError: relations do not all (canonically) map to 0
under map determined by images of generators

```

Homomorphism from one precision of field to another.

From smaller to bigger doesn't make sense:

```

sage: R200 = RealField(200) #_
↳needs sage.rings.real_mpfr
sage: f = RR.hom( R200 ) #_
↳needs sage.rings.real_mpfr
Traceback (most recent call last):
...
TypeError: natural coercion morphism from Real Field with 53 bits of precision
to Real Field with 200 bits of precision not defined

```

From bigger to small does:

```

sage: f = RR.hom(RealField(15)) #_
↳needs sage.rings.real_mpfr
sage: f(2.5) #_
↳needs sage.rings.real_mpfr
2.500
sage: f(RR.pi()) #_
↳needs sage.rings.real_mpfr
3.142

```

Inclusion map from the reals to the complexes:

```

sage: # needs sage.rings.real_mpfr
sage: i = RR.hom([CC(1)]); i
Ring morphism:
  From: Real Field with 53 bits of precision
  To:   Complex Field with 53 bits of precision
  Defn: 1.000000000000000 |--> 1.000000000000000
sage: i(RR('3.1'))
3.100000000000000

```


A map from a multivariate polynomial ring to itself:

```
sage: R.<x,y,z> = PolynomialRing(QQ, 3)
sage: phi = R.hom([y, z, x^2]); phi
Ring endomorphism of Multivariate Polynomial Ring in x, y, z over Rational Field
Defn: x |--> y
      y |--> z
      z |--> x^2
sage: phi(x + y + z)
x^2 + y + z
```

An endomorphism of a quotient of a multi-variate polynomial ring:

```
sage: # needs sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ)
sage: S.<a,b> = quo(R, ideal(1 + y^2))
sage: phi = S.hom([a^2, -b]); phi
Ring endomorphism of Quotient of Multivariate Polynomial Ring in x, y
over Rational Field by the ideal (y^2 + 1)
Defn: a |--> a^2
      b |--> -b
sage: phi(b)
-b
sage: phi(a^2 + b^2)
a^4 - 1
```

The reduction map from the integers to the integers modulo 8, viewed as a quotient ring:

```
sage: R = ZZ.quo(8*ZZ)
sage: pi = R.cover(); pi
Ring morphism:
From: Integer Ring
To:   Ring of integers modulo 8
Defn: Natural quotient map
sage: pi.domain()
Integer Ring
sage: pi.codomain()
Ring of integers modulo 8
sage: pi(10)
2
sage: pi.lift()
Set-theoretic ring morphism:
From: Ring of integers modulo 8
To:   Integer Ring
Defn: Choice of lifting map
sage: pi.lift(13)
5
```

Inclusion of $\text{GF}(2)$ into $\text{GF}(4, 'a')$:

```
sage: # needs sage.rings.finite_rings
sage: k = GF(2)
sage: i = k.hom(GF(4, 'a'))
sage: i
Ring morphism:
From: Finite Field of size 2
To:   Finite Field in a of size 2^2
Defn: 1 |--> 1
```

(continues on next page)

(continued from previous page)

```
sage: i(0)
0
sage: a = i(1); a.parent()
Finite Field in a of size 2^2
```

We next compose the inclusion with reduction from the integers to $GF(2)$:

```
sage: # needs sage.rings.finite_rings
sage: pi = ZZ.hom(k); pi
Natural morphism:
  From: Integer Ring
  To:   Finite Field of size 2
sage: f = i * pi; f
Composite map:
  From: Integer Ring
  To:   Finite Field in a of size 2^2
  Defn: Natural morphism:
        From: Integer Ring
        To:   Finite Field of size 2
  then
  Ring morphism:
  From: Finite Field of size 2
  To:   Finite Field in a of size 2^2
  Defn: 1 |--> 1
sage: a = f(5); a
1
sage: a.parent()
Finite Field in a of size 2^2
```

Inclusion from \mathbb{Q} to the 3-adic field:

```
sage: # needs sage.rings.padic
sage: phi = QQ.hom(Qp(3, print_mode='series'))
sage: phi
Ring morphism:
  From: Rational Field
  To:   3-adic Field with capped relative precision 20
sage: phi.codomain()
3-adic Field with capped relative precision 20
sage: phi(394)
1 + 2*3 + 3^2 + 2*3^3 + 3^4 + 3^5 + O(3^20)
```

An automorphism of a quotient of a univariate polynomial ring:

```
sage: # needs sage.libs.pari
sage: R.<x> = PolynomialRing(QQ)
sage: S.<sqrt2> = R.quo(x^2 - 2)
sage: sqrt2^2
2
sage: (3+sqrt2)^10
993054*sqrt2 + 1404491
sage: c = S.hom([-sqrt2])
sage: c(1+sqrt2)
-sqrt2 + 1
```

Note that Sage verifies that the morphism is valid:

```

sage: (1 - sqrt2)^2
↪needs sage.libs.pari
-2*sqrt2 + 3
sage: c = S.hom([1 - sqrt2])      # this is not valid
↪needs sage.libs.pari
Traceback (most recent call last):
...
ValueError: relations do not all (canonically) map to 0
under map determined by images of generators
    
```

Endomorphism of power series ring:

```

sage: R.<t> = PowerSeriesRing(QQ, default_prec=10); R
Power Series Ring in t over Rational Field
sage: f = R.hom([t^2]); f
Ring endomorphism of Power Series Ring in t over Rational Field
Defn: t |--> t^2
sage: s = 1/(1 + t); s
1 - t + t^2 - t^3 + t^4 - t^5 + t^6 - t^7 + t^8 - t^9 + O(t^10)
sage: f(s)
1 - t^2 + t^4 - t^6 + t^8 - t^10 + t^12 - t^14 + t^16 - t^18 + O(t^20)
    
```

Frobenius on a power series ring over a finite field:

```

sage: R.<t> = PowerSeriesRing(GF(5))
sage: f = R.hom([t^5]); f
Ring endomorphism of Power Series Ring in t over Finite Field of size 5
Defn: t |--> t^5
sage: a = 2 + t + 3*t^2 + 4*t^3 + O(t^4)
sage: b = 1 + t + 2*t^2 + t^3 + O(t^5)
sage: f(a)
2 + t^5 + 3*t^10 + 4*t^15 + O(t^20)
sage: f(b)
1 + t^5 + 2*t^10 + t^15 + O(t^25)
sage: f(a*b)
2 + 3*t^5 + 3*t^10 + t^15 + O(t^20)
sage: f(a)*f(b)
2 + 3*t^5 + 3*t^10 + t^15 + O(t^20)
    
```

Homomorphism of Laurent series ring:

```

sage: R.<t> = LaurentSeriesRing(QQ, 10)
sage: f = R.hom([t^3 + t]); f
Ring endomorphism of Laurent Series Ring in t over Rational Field
Defn: t |--> t + t^3
sage: s = 2/t^2 + 1/(1 + t); s
2*t^-2 + 1 - t + t^2 - t^3 + t^4 - t^5 + t^6 - t^7 + t^8 - t^9 + O(t^10)
sage: f(s)
2*t^-2 - 3 - t + 7*t^2 - 2*t^3 - 5*t^4 - 4*t^5 + 16*t^6 - 9*t^7 + O(t^8)
sage: f = R.hom([t^3]); f
Ring endomorphism of Laurent Series Ring in t over Rational Field
Defn: t |--> t^3
sage: f(s)
2*t^-6 + 1 - t^3 + t^6 - t^9 + t^12 - t^15 + t^18 - t^21 + t^24 - t^27 + O(t^30)
    
```

Note that the homomorphism must result in a converging Laurent series, so the valuation of the image of the generator must be positive:

```
sage: R.hom([1/t])
Traceback (most recent call last):
...
ValueError: relations do not all (canonically) map to 0
under map determined by images of generators
sage: R.hom([1])
Traceback (most recent call last):
...
ValueError: relations do not all (canonically) map to 0
under map determined by images of generators
```

Complex conjugation on cyclotomic fields:

```
sage: # needs sage.rings.number_field
sage: K.<zeta7> = CyclotomicField(7)
sage: c = K.hom([1/zeta7]); c
Ring endomorphism of Cyclotomic Field of order 7 and degree 6
Defn: zeta7 |--> -zeta7^5 - zeta7^4 - zeta7^3 - zeta7^2 - zeta7 - 1
sage: a = (1+zeta7)^5; a
zeta7^5 + 5*zeta7^4 + 10*zeta7^3 + 10*zeta7^2 + 5*zeta7 + 1
sage: c(a)
5*zeta7^5 + 5*zeta7^4 - 4*zeta7^2 - 5*zeta7 - 4
sage: c(zeta7 + 1/zeta7) # this element is obviously fixed by inversion
-zeta7^5 - zeta7^4 - zeta7^3 - zeta7^2 - 1
sage: zeta7 + 1/zeta7
-zeta7^5 - zeta7^4 - zeta7^3 - zeta7^2 - 1
```

Embedding a number field into the reals:

```
sage: # needs sage.rings.number_field
sage: R.<x> = PolynomialRing(QQ)
sage: K.<beta> = NumberField(x^3 - 2)
sage: alpha = RR(2)^(1/3); alpha
1.25992104989487
sage: i = K.hom([alpha],check=False); i
Ring morphism:
From: Number Field in beta with defining polynomial x^3 - 2
To: Real Field with 53 bits of precision
Defn: beta |--> 1.25992104989487
sage: i(beta)
1.25992104989487
sage: i(beta^3)
2.000000000000000
sage: i(beta^2 + 1)
2.58740105196820
```

An example from Jim Carlson:

```
sage: K = QQ # by the way :-)
sage: R.<a,b,c,d> = K[]; R
Multivariate Polynomial Ring in a, b, c, d over Rational Field
sage: S.<u> = K[]; S
Univariate Polynomial Ring in u over Rational Field
sage: f = R.hom([0,0,0,u], S); f
Ring morphism:
From: Multivariate Polynomial Ring in a, b, c, d over Rational Field
To: Univariate Polynomial Ring in u over Rational Field
```

(continues on next page)

(continued from previous page)

```

Defn: a |--> 0
      b |--> 0
      c |--> 0
      d |--> u
sage: f(a + b + c + d)
u
sage: f((a+b+c+d)^2)
u^2

```

class sage.rings.morphism.FrobeniusEndomorphism_generic

Bases: *RingHomomorphism*

A class implementing Frobenius endomorphisms on rings of prime characteristic.

power ()

Return an integer n such that this endomorphism is the n -th power of the absolute (arithmetic) Frobenius.

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: K.<u> = PowerSeriesRing(GF(5))
sage: Frob = K.frobenius_endomorphism()
sage: Frob.power()
1
sage: (Frob^9).power()
9

```

class sage.rings.morphism.RingHomomorphism

Bases: *RingMap*

Homomorphism of rings.

inverse ()

Return the inverse of this ring homomorphism if it exists.

Raises a `ZeroDivisionError` if the inverse does not exist.

ALGORITHM:

By default, this computes a Gröbner basis of the ideal corresponding to the graph of the ring homomorphism.

EXAMPLES:

```

sage: R.<t> = QQ[]
sage: f = R.hom([2*t - 1], R)
sage: f.inverse()
↳needs sage.libs.singular
Ring endomorphism of Univariate Polynomial Ring in t over Rational Field
Defn: t |--> 1/2*t + 1/2

```

The following non-linear homomorphism is not invertible, but it induces an isomorphism on a quotient ring:

```

sage: # needs sage.libs.singular
sage: R.<x,y,z> = QQ[]
sage: f = R.hom([y*z, x*z, x*y], R)
sage: f.inverse()
Traceback (most recent call last):
...

```

(continues on next page)

(continued from previous page)

```

ZeroDivisionError: ring homomorphism not surjective
sage: f.is_injective()
True
sage: Q.<x,y,z> = R.quotient(x*y*z - 1)
sage: g = Q.hom([y*z, x*z, x*y], Q)
sage: g.inverse()
Ring endomorphism of Quotient of Multivariate Polynomial Ring
in x, y, z over Rational Field by the ideal (x*y*z - 1)
  Defn: x |--> y*z
        y |--> x*z
        z |--> x*y
    
```

Homomorphisms over the integers are supported:

```

sage: S.<x,y> = ZZ[]
sage: f = S.hom([x + 2*y, x + 3*y], S)
sage: f.inverse() #_
↳needs sage.libs.singular
Ring endomorphism of Multivariate Polynomial Ring in x, y over Integer Ring
  Defn: x |--> 3*x - 2*y
        y |--> -x + y
sage: (f.inverse() * f).is_identity() #_
↳needs sage.libs.singular
True
    
```

The following homomorphism is invertible over the rationals, but not over the integers:

```

sage: g = S.hom([x + y, x - y - 2], S)
sage: g.inverse() #_
↳needs sage.libs.singular
Traceback (most recent call last):
...
ZeroDivisionError: ring homomorphism not surjective
sage: R.<x,y> = QQ[x,y]
sage: h = R.hom([x + y, x - y - 2], R)
sage: (h.inverse() * h).is_identity() #_
↳needs sage.libs.singular
True
    
```

This example by M. Nagata is a wild automorphism:

```

sage: R.<x,y,z> = QQ[]
sage: sigma = R.hom([x - 2*y*(z*x+y^2) - z*(z*x+y^2)^2,
...:                y + z*(z*x+y^2), z], R)
sage: tau = sigma.inverse(); tau #_
↳needs sage.libs.singular
Ring endomorphism of Multivariate Polynomial Ring in x, y, z over
Rational Field
  Defn: x |--> -y^4*z - 2*x*y^2*z^2 - x^2*z^3 + 2*y^3 + 2*x*y*z + x
        y |--> -y^2*z - x*z^2 + y
        z |--> z
sage: (tau * sigma).is_identity() #_
↳needs sage.libs.singular
True
    
```

We compute the triangular automorphism that converts moments to cumulants, as well as its inverse, using the moment generating function. The choice of a term ordering can have a great impact on the computation

time of a Gröbner basis, so here we choose a weighted ordering such that the images of the generators are homogeneous polynomials.

```
sage: d = 12
sage: T = TermOrder('wdegrevlex', [1..d])
sage: R = PolynomialRing(QQ, ['x%s' % j for j in (1..d)], order=T)
sage: S.<t> = PowerSeriesRing(R)
sage: egf = S([0] + list(R.gens())).ogf_to_egf().exp(prec=d+1)
sage: phi = R.hom(egf.egf_to_ogf().list()[1:], R)
sage: phi.im_gens()[5]
[x1,
 x1^2 + x2,
 x1^3 + 3*x1*x2 + x3,
 x1^4 + 6*x1^2*x2 + 3*x2^2 + 4*x1*x3 + x4,
 x1^5 + 10*x1^3*x2 + 15*x1*x2^2 + 10*x1^2*x3 + 10*x2*x3 + 5*x1*x4 + x5]
sage: all(p.is_homogeneous() for p in phi.im_gens()) #_
↳needs sage.libs.singular
True
sage: phi.inverse().im_gens()[5] #_
↳needs sage.libs.singular
[x1,
 -x1^2 + x2,
 2*x1^3 - 3*x1*x2 + x3,
 -6*x1^4 + 12*x1^2*x2 - 3*x2^2 - 4*x1*x3 + x4,
 24*x1^5 - 60*x1^3*x2 + 30*x1*x2^2 + 20*x1^2*x3 - 10*x2*x3 - 5*x1*x4 + x5]
sage: (phi.inverse() * phi).is_identity() #_
↳needs sage.libs.singular
True
```

Automorphisms of number fields as well as Galois fields are supported:

```
sage: K.<zeta7> = CyclotomicField(7) #_
↳needs sage.rings.number_field
sage: c = K.hom([1/zeta7]) #_
↳needs sage.rings.number_field
sage: (c.inverse() * c).is_identity() #_
↳needs sage.libs.singular sage.rings.number_field
True

sage: F.<t> = GF(7^3) #_
↳needs sage.rings.finite_rings
sage: f = F.hom(t^7, F) #_
↳needs sage.rings.finite_rings
sage: (f.inverse() * f).is_identity() #_
↳needs sage.libs.singular sage.rings.finite_rings
True
```

An isomorphism between the algebraic torus and the circle over a number field:

```
sage: # needs sage.libs.singular sage.rings.number_field
sage: K.<i> = QuadraticField(-1)
sage: A.<z,w> = K['z,w'].quotient('z*w - 1')
sage: B.<x,y> = K['x,y'].quotient('x^2 + y^2 - 1')
sage: f = A.hom([x + i*y, x - i*y], B)
sage: g = f.inverse()
sage: g.morphism_from_cover().im_gens()
[1/2*z + 1/2*w, (-1/2*i)*z + (1/2*i)*w]
sage: all(g(f(z)) == z for z in A.gens())
```

(continues on next page)

(continued from previous page)

```
True
```

inverse_image(I)

Return the inverse image of an ideal or an element in the codomain of this ring homomorphism.

INPUT:

- I – an ideal or element in the codomain

OUTPUT:

For an ideal I in the codomain, this returns the largest ideal in the domain whose image is contained in I .

Given an element b in the codomain, this returns an arbitrary element a in the domain such that $\text{self}(a) = b$ if one such exists. The element a is unique if this ring homomorphism is injective.

EXAMPLES:

```
sage: R.<x,y,z> = QQ[]
sage: S.<u,v> = QQ[]
sage: f = R.hom([u^2, u*v, v^2], S)
sage: I = S.ideal([u^6, u^5*v, u^4*v^2, u^3*v^3])
sage: J = f.inverse_image(I); J                                     #_
↳needs sage.libs.singular
Ideal (y^2 - x*z, x*y*z, x^2*z, x^2*y, x^3)
of Multivariate Polynomial Ring in x, y, z over Rational Field
sage: f(J) == I                                                  #_
↳needs sage.libs.singular
True
```

Under the above homomorphism, there exists an inverse image for every element that only involves monomials of even degree:

```
sage: [f.inverse_image(p) for p in [u^2, u^4, u*v + u^3*v^3]]     #_
↳needs sage.libs.singular
[x, x^2, x*y*z + y]
sage: f.inverse_image(u*v^2)                                     #_
↳needs sage.libs.singular
Traceback (most recent call last):
...
ValueError: element u*v^2 does not have preimage
```

The image of the inverse image ideal can be strictly smaller than the original ideal:

```
sage: # needs sage.libs.singular sage.rings.number_field
sage: S.<u,v> = QQ['u,v'].quotient('v^2 - 2')
sage: f = QuadraticField(2).hom([v], S)
sage: I = S.ideal(u + v)
sage: J = f.inverse_image(I)
sage: J.is_zero()
True
sage: f(J) < I
True
```

Fractional ideals are not yet fully supported:

```
sage: # needs sage.rings.number_field
sage: K.<a> = NumberField(QQ['x']('x^2+2'))
```

(continues on next page)

(continued from previous page)

```

sage: f = K.hom([-a], K)
sage: I = K.ideal([a + 1])
sage: f.inverse_image(I) #_
↳needs sage.libs.singular
Traceback (most recent call last):
...
NotImplementedError: inverse image not implemented...
sage: f.inverse_image(K.ideal(0)).is_zero() #_
↳needs sage.libs.singular
True
sage: f.inverse()(I) #_
↳needs sage.rings.padics
Fractional ideal (-a + 1)

```

ALGORITHM:

By default, this computes a Gröbner basis of an ideal related to the graph of the ring homomorphism.

REFERENCES:

- Proposition 2.5.12 [DS2009]

is_invertible()

Return whether this ring homomorphism is bijective.

EXAMPLES:

```

sage: R.<x,y,z> = QQ[]
sage: R.hom([y*z, x*z, x*y], R).is_invertible() #_
↳needs sage.libs.singular
False
sage: Q.<x,y,z> = R.quotient(x*y*z - 1) #_
↳needs sage.libs.singular
sage: Q.hom([y*z, x*z, x*y], Q).is_invertible() #_
↳needs sage.libs.singular
True

```

ALGORITHM:

By default, this requires the computation of a Gröbner basis.

is_surjective()

Return whether this ring homomorphism is surjective.

EXAMPLES:

```

sage: R.<x,y,z> = QQ[]
sage: R.hom([y*z, x*z, x*y], R).is_surjective() #_
↳needs sage.libs.singular
False
sage: Q.<x,y,z> = R.quotient(x*y*z - 1) #_
↳needs sage.libs.singular
sage: R.hom([y*z, x*z, x*y], Q).is_surjective() #_
↳needs sage.libs.singular
True

```

ALGORITHM:

By default, this requires the computation of a Gröbner basis.

kernel ()

Return the kernel ideal of this ring homomorphism.

EXAMPLES:

```
sage: A.<x,y> = QQ[]
sage: B.<t> = QQ[]
sage: f = A.hom([t^4, t^3 - t^2], B)
sage: f.kernel() #_
↳needs sage.libs.singular
Ideal (y^4 - x^3 + 4*x^2*y - 2*x*y^2 + x^2)
of Multivariate Polynomial Ring in x, y over Rational Field
```

We express a Veronese subring of a polynomial ring as a quotient ring:

```
sage: A.<a,b,c,d> = QQ[]
sage: B.<u,v> = QQ[]
sage: f = A.hom([u^3, u^2*v, u*v^2, v^3], B)
sage: f.kernel() == A.ideal(matrix.hankel([a, b, c], [d]).minors(2)) #_
↳needs sage.libs.singular
True
sage: Q = A.quotient(f.kernel()) #_
↳needs sage.libs.singular
sage: Q.hom(f.im_gens(), B).is_injective() #_
↳needs sage.libs.singular
True
```

The Steiner-Roman surface:

```
sage: R.<x,y,z> = QQ[]
sage: S = R.quotient(x^2 + y^2 + z^2 - 1)
sage: f = R.hom([x*y, x*z, y*z], S) #_
↳needs sage.libs.singular
sage: f.kernel() #_
↳needs sage.libs.singular
Ideal (x^2*y^2 + x^2*z^2 + y^2*z^2 - x*y*z)
of Multivariate Polynomial Ring in x, y, z over Rational Field
```

lift (x=None)

Return a lifting map associated to this homomorphism, if it has been defined.

If x is not `None`, return the value of the lift morphism on x .

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: f = R.hom([x, x])
sage: f(x+y)
2*x
sage: f.lift()
Traceback (most recent call last):
...
ValueError: no lift map defined
sage: g = R.hom(R)
sage: f._set_lift(g)
sage: f.lift() == g
True
sage: f.lift(x)
x
```

pushforward (I)

Returns the pushforward of the ideal I under this ring homomorphism.

EXAMPLES:

```
sage: R.<x,y> = QQ[]; S.<xx,yy> = R.quo([x^2, y^2]); f = S.cover() #_
↪needs sage.libs.singular
sage: f.pushforward(R.ideal([x, 3*x + x*y + y^2])) #_
↪needs sage.libs.singular
Ideal (xx, xx*yy + 3*xx) of Quotient of Multivariate Polynomial Ring
in x, y over Rational Field by the ideal (x^2, y^2)
```

class sage.rings.morphism.**RingHomomorphism_cover**

Bases: *RingHomomorphism*

A homomorphism induced by quotienting a ring out by an ideal.

EXAMPLES:

```
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S.<a,b> = R.quo(x^2 + y^2) #_
↪needs sage.libs.singular
sage: phi = S.cover(); phi #_
↪needs sage.libs.singular
Ring morphism:
  From: Multivariate Polynomial Ring in x, y over Rational Field
  To:   Quotient of Multivariate Polynomial Ring in x, y over Rational Field
        by the ideal (x^2 + y^2)
  Defn: Natural quotient map
sage: phi(x + y) #_
↪needs sage.libs.singular
a + b
```

kernel ()

Return the kernel of this covering morphism, which is the ideal that was quotiented out by.

EXAMPLES:

```
sage: f = Zmod(6).cover()
sage: f.kernel()
Principal ideal (6) of Integer Ring
```

class sage.rings.morphism.**RingHomomorphism_from_base**

Bases: *RingHomomorphism*

A ring homomorphism determined by a ring homomorphism of the base ring.

AUTHOR:

- Simon King (initial version, 2010-04-30)

EXAMPLES:

We define two polynomial rings and a ring homomorphism:

```
sage: R.<x,y> = QQ[]
sage: S.<z> = QQ[]
sage: f = R.hom([2*z, 3*z], S)
```

Now we construct polynomial rings based on R and S , and let f act on the coefficients:

```

sage: PR.<t> = R[]
sage: PS = S['t']
sage: Pf = PR.hom(f,PS)
sage: Pf
Ring morphism:
  From: Univariate Polynomial Ring in t
        over Multivariate Polynomial Ring in x, y over Rational Field
  To:   Univariate Polynomial Ring in t
        over Univariate Polynomial Ring in z over Rational Field
  Defn: Induced from base ring by
        Ring morphism:
          From: Multivariate Polynomial Ring in x, y over Rational Field
          To:   Univariate Polynomial Ring in z over Rational Field
          Defn: x |--> 2*z
                y |--> 3*z
sage: p = (x - 4*y + 1/13)*t^2 + (1/2*x^2 - 1/3*y^2)*t + 2*y^2 + x
sage: Pf(p)
(-10*z + 1/13)*t^2 - z^2*t + 18*z^2 + 2*z

```

Similarly, we can construct the induced homomorphism on a matrix ring over our polynomial rings:

```

sage: # needs sage.modules
sage: MR = MatrixSpace(R, 2, 2)
sage: MS = MatrixSpace(S, 2, 2)
sage: M = MR([x^2 + 1/7*x*y - y^2, -1/2*y^2 + 2*y + 1/6,
.....:      4*x^2 - 14*x, 1/2*y^2 + 13/4*x - 2/11*y])
sage: Mf = MR.hom(f, MS)
sage: Mf
Ring morphism:
  From: Full MatrixSpace of 2 by 2 dense matrices
        over Multivariate Polynomial Ring in x, y over Rational Field
  To:   Full MatrixSpace of 2 by 2 dense matrices
        over Univariate Polynomial Ring in z over Rational Field
  Defn: Induced from base ring by
        Ring morphism:
          From: Multivariate Polynomial Ring in x, y over Rational Field
          To:   Univariate Polynomial Ring in z over Rational Field
          Defn: x |--> 2*z
                y |--> 3*z
sage: Mf(M)
[      -29/7*z^2 -9/2*z^2 + 6*z + 1/6]
[      16*z^2 - 28*z   9/2*z^2 + 131/22*z]

```

The construction of induced homomorphisms is recursive, and so we have:

```

sage: # needs sage.modules
sage: MPR = MatrixSpace(PR, 2)
sage: MPS = MatrixSpace(PS, 2)
sage: M = MPR([(-x + y)*t^2 + 58*t - 3*x^2 + x*y,
.....:      (- 1/7*x*y - 1/40*x)*t^2 + (5*x^2 + y^2)*t + 2*y,
.....:      (- 1/3*y + 1)*t^2 + 1/3*x*y + y^2 + 5/2*y + 1/4,
.....:      (x + 6*y + 1)*t^2])
sage: MPf = MPR.hom(f, MPS); MPf
Ring morphism:
  From: Full MatrixSpace of 2 by 2 dense matrices over Univariate Polynomial
        Ring in t over Multivariate Polynomial Ring in x, y over Rational Field
  To:   Full MatrixSpace of 2 by 2 dense matrices over Univariate Polynomial

```

(continues on next page)

(continued from previous page)

```

Ring in t over Univariate Polynomial Ring in z over Rational Field
Defn: Induced from base ring by
Ring morphism:
  From: Univariate Polynomial Ring in t
         over Multivariate Polynomial Ring in x, y over Rational Field
  To:   Univariate Polynomial Ring in t
         over Univariate Polynomial Ring in z over Rational Field
Defn: Induced from base ring by
Ring morphism:
  From: Multivariate Polynomial Ring in x, y over Rational Field
  To:   Univariate Polynomial Ring in z over Rational Field
Defn: x |--> 2*z
      y |--> 3*z
sage: MPf(M)
[          z*t^2 + 58*t - 6*z^2 (-6/7*z^2 - 1/20*z)*t^2 + 29*z^2*t +
↪6*z]
[ (-z + 1)*t^2 + 11*z^2 + 15/2*z + 1/4          (20*z + 1)*t^
↪2]
    
```

inverse()

Return the inverse of this ring homomorphism if the underlying homomorphism of the base ring is invertible.

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: S.<a,b> = QQ[]
sage: f = R.hom([a + b, a - b], S)
sage: PR.<t> = R[]
sage: PS = S['t']
sage: Pf = PR.hom(f, PS)
sage: Pf.inverse() #_
↪needs sage.libs.singular
Ring morphism:
  From: Univariate Polynomial Ring in t over Multivariate
         Polynomial Ring in a, b over Rational Field
  To:   Univariate Polynomial Ring in t over Multivariate
         Polynomial Ring in x, y over Rational Field
Defn: Induced from base ring by
Ring morphism:
  From: Multivariate Polynomial Ring in a, b over Rational Field
  To:   Multivariate Polynomial Ring in x, y over Rational Field
Defn: a |--> 1/2*x + 1/2*y
      b |--> 1/2*x - 1/2*y
sage: Pf.inverse()(Pf(x*t^2 + y*t)) #_
↪needs sage.libs.singular
x*t^2 + y*t
    
```

underlying_map()

Return the underlying homomorphism of the base ring.

EXAMPLES:

```

sage: # needs sage.modules
sage: R.<x,y> = QQ[]
sage: S.<z> = QQ[]
sage: f = R.hom([2*z, 3*z], S)
sage: MR = MatrixSpace(R, 2)
    
```

(continues on next page)

(continued from previous page)

```
sage: MS = MatrixSpace(S, 2)
sage: g = MR.hom(f, MS)
sage: g.underlying_map() == f
True
```

class sage.rings.morphism.RingHomomorphism_from_fraction_field

Bases: *RingHomomorphism*

Morphisms between fraction fields.

inverse ()

Return the inverse of this ring homomorphism if it exists.

EXAMPLES:

```
sage: S.<x> = QQ[]
sage: f = S.hom([2*x - 1])
sage: g = f.extend_to_fraction_field() #_
↳needs sage.libs.singular
sage: g.inverse() #_
↳needs sage.libs.singular
Ring endomorphism of Fraction Field of Univariate Polynomial Ring
in x over Rational Field
Defn: x |--> 1/2*x + 1/2
```

class sage.rings.morphism.RingHomomorphism_from_quotient

Bases: *RingHomomorphism*

A ring homomorphism with domain a generic quotient ring.

INPUT:

- parent – a ring homset $\text{Hom}(R, S)$
- phi – a ring homomorphism $C \rightarrow S$, where C is the domain of R . `cover()`

OUTPUT: a ring homomorphism

The domain R is a quotient object $C \rightarrow R$, and R .`cover()` is the ring homomorphism $\varphi : C \rightarrow R$. The condition on the elements `im_gens` of S is that they define a homomorphism $C \rightarrow S$ such that each generator of the kernel of φ maps to 0.

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: R.<x, y, z> = PolynomialRing(QQ, 3)
sage: S.<a, b, c> = R.quo(x^3 + y^3 + z^3)
sage: phi = S.hom([b, c, a]); phi
Ring endomorphism of Quotient of Multivariate Polynomial Ring in x, y, z
over Rational Field by the ideal (x^3 + y^3 + z^3)
Defn: a |--> b
      b |--> c
      c |--> a
sage: phi(a + b + c)
a + b + c
sage: loads(dumps(phi)) == phi
True
```

Validity of the homomorphism is determined, when possible, and a `TypeError` is raised if there is no homomorphism sending the generators to the given images:

```

sage: S.hom([b^2, c^2, a^2]) #_
↳needs sage.libs.singular
Traceback (most recent call last):
...
ValueError: relations do not all (canonically) map to 0
under map determined by images of generators

```

morphism_from_cover()

Underlying morphism used to define this quotient map, i.e., the morphism from the cover of the domain.

EXAMPLES:

```

sage: R.<x,y> = QQ[]; S.<xx,yy> = R.quo([x^2, y^2]) #_
↳needs sage.libs.singular
sage: S.hom([yy,xx]).morphism_from_cover() #_
↳needs sage.libs.singular
Ring morphism:
  From: Multivariate Polynomial Ring in x, y over Rational Field
  To:   Quotient of Multivariate Polynomial Ring in x, y
        over Rational Field by the ideal (x^2, y^2)
  Defn: x |--> yy
        y |--> xx

```

class sage.rings.morphism.RingHomomorphism_im_gens

Bases: *RingHomomorphism*

A ring homomorphism determined by the images of generators.

base_map()

Return the map on the base ring that is part of the defining data for this morphism. May return None if a coercion is used.

EXAMPLES:

```

sage: # needs sage.rings.number_field
sage: R.<x> = ZZ[]
sage: K.<i> = NumberField(x^2 + 1)
sage: cc = K.hom([-i])
sage: S.<y> = K[]
sage: phi = S.hom([y^2], base_map=cc)
sage: phi
Ring endomorphism of Univariate Polynomial Ring in y
over Number Field in i with defining polynomial x^2 + 1
  Defn: y |--> y^2
        with map of base ring
sage: phi(y)
y^2
sage: phi(i*y)
-i*y^2
sage: phi.base_map()
Composite map:
  From: Number Field in i with defining polynomial x^2 + 1
  To:   Univariate Polynomial Ring in y over Number Field in i
        with defining polynomial x^2 + 1
  Defn: Ring endomorphism of Number Field in i with defining polynomial x^2
↳+ 1
        Defn: i |--> -i
        then

```

(continues on next page)

(continued from previous page)

```
Polynomial base injection morphism:
From: Number Field in i with defining polynomial x^2 + 1
To:   Univariate Polynomial Ring in y over Number Field in i
      with defining polynomial x^2 + 1
```

im_gens ()

Return the images of the generators of the domain.

OUTPUT:

- list – a copy of the list of gens (it is safe to change this)

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: f = R.hom([x, x + y])
sage: f.im_gens()
[x, x + y]
```

We verify that the returned list of images of gens is a copy, so changing it doesn't change f:

```
sage: f.im_gens()[0] = 5
sage: f.im_gens()
[x, x + y]
```

class sage.rings.morphism.RingMap

Bases: *Morphism*

Set-theoretic map between rings.

class sage.rings.morphism.RingMap_lift

Bases: *RingMap*

Given rings R and S such that for any $x \in R$ the function $x.lift()$ is an element that naturally coerces to S , this returns the set-theoretic ring map $R \rightarrow S$ sending x to $x.lift()$.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: S.<xbar,ybar> = R.quo( (x^2 + y^2, y) ) #_
↪needs sage.libs.singular
sage: S.lift() #_
↪needs sage.libs.singular
Set-theoretic ring morphism:
  From: Quotient of Multivariate Polynomial Ring in x, y
        over Rational Field by the ideal (x^2 + y^2, y)
  To:   Multivariate Polynomial Ring in x, y over Rational Field
  Defn: Choice of lifting map
sage: S.lift() == 0 #_
↪needs sage.libs.singular
False
```

Since [Issue #11068](#), it is possible to create quotient rings of non-commutative rings by two-sided ideals. It was needed to modify *RingMap_lift* so that rings can be accepted that are no instances of *sage.rings.ring.Ring*, as in the following example:


```

sage: # needs sage.modules sage.rings.finite_rings
sage: MS = MatrixSpace(GF(5), 2, 2)
sage: I = MS * [MS.0*MS.1, MS.2+MS.3] * MS
sage: Q = MS.quo(I)
sage: Q.0*Q.1 # indirect doctest
[0 1]
[0 0]

```

3.2 Space of homomorphisms between two rings

`sage.rings.homset.RingHomset` ($R, S, category=None$)

Construct a space of homomorphisms between the rings R and S .

For more on homsets, see `Hom()`.

EXAMPLES:

```

sage: Hom(ZZ, QQ) # indirect doctest
Set of Homomorphisms from Integer Ring to Rational Field

```

class `sage.rings.homset.RingHomset_generic` ($R, S, category=None$)

Bases: `HomsetWithBase`

A generic space of homomorphisms between two rings.

EXAMPLES:

```

sage: Hom(ZZ, QQ)
Set of Homomorphisms from Integer Ring to Rational Field
sage: QQ.Hom(ZZ)
Set of Homomorphisms from Rational Field to Integer Ring

```

Element

alias of `RingHomomorphism`

has_coerce_map_from (x)

The default for coercion maps between ring homomorphism spaces is very restrictive (until more implementation work is done).

Currently this checks if the domains and the codomains are equal.

EXAMPLES:

```

sage: H = Hom(ZZ, QQ)
sage: H2 = Hom(QQ, ZZ)
sage: H.has_coerce_map_from(H2)
False

```

natural_map ()

Returns the natural map from the domain to the codomain.

The natural map is the coercion map from the domain ring to the codomain ring.

EXAMPLES:

```
sage: H = Hom(ZZ, QQ)
sage: H.natural_map()
Natural morphism:
  From: Integer Ring
  To:   Rational Field
```

zero()

Return the zero element of this homset.

EXAMPLES:

Since a ring homomorphism maps 1 to 1, there can only be a zero morphism when mapping to the trivial ring:

```
sage: Hom(ZZ, Zmod(1)).zero()
Ring morphism:
  From: Integer Ring
  To:   Ring of integers modulo 1
  Defn: 1 |--> 0
sage: Hom(ZZ, Zmod(2)).zero()
Traceback (most recent call last):
...
ValueError: homset has no zero element
```

class sage.rings.homset.**RingHomset_quo_ring**(*R, S, category=None*)

Bases: *RingHomset_generic*

Space of ring homomorphisms where the domain is a (formal) quotient ring.

EXAMPLES:

```
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S.<a,b> = R.quotient(x^2 + y^2) #_
↪needs sage.libs.singular
sage: phi = S.hom([b,a]); phi #_
↪needs sage.libs.singular
Ring endomorphism of Quotient of Multivariate Polynomial Ring in x, y
over Rational Field by the ideal (x^2 + y^2)
  Defn: a |--> b
       b |--> a
sage: phi(a) #_
↪needs sage.libs.singular
b
sage: phi(b) #_
↪needs sage.libs.singular
a
```

Element

alias of *RingHomomorphism_from_quotient*

sage.rings.homset.**is_RingHomset**(*H*)

Return True if *H* is a space of homomorphisms between two rings.

EXAMPLES:

```
sage: from sage.rings.homset import is_RingHomset as is_RH
sage: is_RH(Hom(ZZ, QQ))
doctest:warning...
DeprecationWarning: the function is_RingHomset is deprecated;
```

(continues on next page)

(continued from previous page)

```
use 'isinstance(..., RingHomset_generic)' instead
See https://github.com/sagemath/sage/issues/37922 for details.
True
sage: is_RH(ZZ)
False
sage: is_RH(Hom(RR, CC)) #_
↳needs sage.rings.real_mpfr
True
sage: is_RH(Hom(FreeModule(ZZ,1), FreeModule(QQ,1))) #_
↳needs sage.modules
False
```


QUOTIENT RINGS

4.1 Quotient Rings

AUTHORS:

- William Stein
- Simon King (2011-04): Put it into the category framework, use the new coercion model.
- Simon King (2011-04): Quotients of non-commutative rings by twosided ideals.

Todo: The following skipped tests should be removed once [Issue #13999](#) is fixed:

```
sage: TestSuite(S).run(skip=['_test_nonzero_equal', '_test_elements', '_test_zero'])
```

In [Issue #11068](#), non-commutative quotient rings R/I were implemented. The only requirement is that the two-sided ideal I provides a reduce method so that $I.reduce(x)$ is the normal form of an element x with respect to I (i.e., we have $I.reduce(x) == I.reduce(y)$ if $x - y \in I$, and $x - I.reduce(x) \in I$). Here is a toy example:

```
sage: from sage.rings.noncommutative_ideals import Ideal_nc
sage: from itertools import product
sage: class PowerIdeal(Ideal_nc):
.....:     def __init__(self, R, n):
.....:         self._power = n
.....:         self._power = n
.....:         Ideal_nc.__init__(self, R, [R.prod(m) for m in product(R.gens(),
↳repeat=n)])
.....:     def reduce(self, x):
.....:         R = self.ring()
.....:         return add([c*R(m) for m,c in x if len(m)<self._power],R(0))
sage: F.<x,y,z> = FreeAlgebra(QQ, 3) #_
↳needs sage.combinat sage.modules
sage: I3 = PowerIdeal(F,3); I3 #_
↳needs sage.combinat sage.modules
Twosided Ideal (x^3, x^2*y, x^2*z, x*y*x, x*y^2, x*y*z, x*z*x, x*z*y,
x*z^2, y*x^2, y*x*y, y*x*z, y^2*x, y^3, y^2*z, y*z*x, y*z*y, y*z^2,
z*x^2, z*x*y, z*x*z, z*y*x, z*y^2, z*y*z, z^2*x, z^2*y, z^3) of
Free Algebra on 3 generators (x, y, z) over Rational Field
```

Free algebras have a custom quotient method that serves at creating finite dimensional quotients defined by multiplication matrices. We are bypassing it, so that we obtain the default quotient:

```
sage: # needs sage.combinat sage.modules
sage: Q3.<a,b,c> = F.quotient(I3)
sage: Q3
Quotient of Free Algebra on 3 generators (x, y, z) over Rational Field by
the ideal (x^3, x^2*y, x^2*z, x*y*x, x*y^2, x*y*z, x*z*x, x*z*y, x*z^2,
y*x^2, y*x*y, y*x*z, y^2*x, y^3, y^2*z, y*z*x, y*z*y, y*z^2, z*x^2, z*x*y,
z*x*z, z*y*x, z*y^2, z*y*z, z^2*x, z^2*y, z^3)
sage: (a+b+2)^4
16 + 32*a + 32*b + 24*a^2 + 24*a*b + 24*b*a + 24*b^2
sage: Q3.is_commutative()
False
```

Even though Q_3 is not commutative, there is commutativity for products of degree three:

```
sage: a*(b*c) - (b*c)*a == F.zero() #_
↪ needs sage.combinat sage.modules
True
```

If we quotient out all terms of degree two then of course the resulting quotient ring is commutative:

```
sage: # needs sage.combinat sage.modules
sage: I2 = PowerIdeal(F,2); I2
Twosided Ideal (x^2, x*y, x*z, y*x, y^2, y*z, z*x, z*y, z^2) of Free Algebra
on 3 generators (x, y, z) over Rational Field
sage: Q2.<a,b,c> = F.quotient(I2)
sage: Q2.is_commutative()
True
sage: (a+b+2)^4
16 + 32*a + 32*b
```

Since [Issue #7797](#), there is an implementation of free algebras based on Singular's implementation of the Letterplace Algebra. Our letterplace wrapper allows to provide the above toy example more easily:

```
sage: # needs sage.combinat sage.libs.singular sage.modules
sage: from itertools import product
sage: F.<x,y,z> = FreeAlgebra(QQ, implementation='letterplace')
sage: Q3 = F.quo(F*[F.prod(m) for m in product(F.gens(), repeat=3)]*F)
sage: Q3
Quotient of Free Associative Unital Algebra on 3 generators (x, y, z)
over Rational Field by the ideal (x*x*x, x*x*y, x*x*z, x*y*x, x*y*y, x*y*z,
x*z*x, x*z*y, x*z*z, y*x*x, y*x*y, y*x*z, y*y*x, y*y*y, y*y*z, y*z*x, y*z*y,
y*z*z, z*x*x, z*x*y, z*x*z, z*y*x, z*y*y, z*y*z, z*z*x, z*z*y, z*z*z)
sage: Q3.0*Q3.1 - Q3.1*Q3.0
xbar*ybar - ybar*xbar
sage: Q3.0*(Q3.1*Q3.2) - (Q3.1*Q3.2)*Q3.0
0
sage: Q2 = F.quo(F*[F.prod(m) for m in product(F.gens(), repeat=2)]*F)
sage: Q2.is_commutative()
True
```

`sage.rings.quotient_ring.QuotientRing(R, I, names=None, **kws)`

Creates a quotient ring of the ring R by the twosided ideal I .

Variables are labeled by names (if the quotient ring is a quotient of a polynomial ring). If names isn't given, 'bar' will be appended to the variable names in R .

INPUT:

- R – a ring.

- I – a twosided ideal of R .
- names – (optional) a list of strings to be used as names for the variables in the quotient ring R/I .
- further named arguments that will be passed to the constructor of the quotient ring instance.

OUTPUT: R/I - the quotient ring R mod the ideal I

ASSUMPTION:

I has a method $I.reduce(x)$ returning the normal form of elements $x \in R$. In other words, it is required that $I.reduce(x) == I.reduce(y) \iff x - y \in I$, and $x - I.reduce(x) \in I$, for all $x, y \in R$.

EXAMPLES:

Some simple quotient rings with the integers:

```
sage: R = QuotientRing(ZZ, 7*ZZ); R
Quotient of Integer Ring by the ideal (7)
sage: R.gens()
(1,)
sage: 1*R(3); 6*R(3); 7*R(3)
3
4
0
```

```
sage: S = QuotientRing(ZZ, ZZ.ideal(8)); S
Quotient of Integer Ring by the ideal (8)
sage: 2*S(4)
0
```

With polynomial rings (note that the variable name of the quotient ring can be specified as shown below):

```
sage: # needs sage.libs.pari
sage: P.<x> = QQ[]
sage: R.<xx> = QuotientRing(P, P.ideal(x^2 + 1))
sage: R
Univariate Quotient Polynomial Ring in xx over Rational Field
with modulus x^2 + 1
sage: R.gens(); R.gen()
(xx,)
xx
sage: for n in range(4): xx^n
1
xx
-1
-xx
```

```
sage: # needs sage.libs.pari
sage: P.<x> = QQ[]
sage: S = QuotientRing(P, P.ideal(x^2 - 2))
sage: S
Univariate Quotient Polynomial Ring in xbar over Rational Field
with modulus x^2 - 2
sage: xbar = S.gen(); S.gen()
xbar
sage: for n in range(3): xbar^n
1
xbar
2
```

Sage coerces objects into ideals when possible:

```
sage: P.<x> = QQ[]
sage: R = QuotientRing(P, x^2 + 1); R
↳needs sage.libs.pari
Univariate Quotient Polynomial Ring in xbar over Rational Field
with modulus x^2 + 1
```

By Noether's homomorphism theorems, the quotient of a quotient ring of R is just the quotient of R by the sum of the ideals. In this example, we end up modding out the ideal (x) from the ring $\mathbb{Q}[x, y]$:

```
sage: # needs sage.libs.pari sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S.<a,b> = QuotientRing(R, R.ideal(1 + y^2))
sage: T.<c,d> = QuotientRing(S, S.ideal(a))
sage: T
Quotient of Multivariate Polynomial Ring in x, y over Rational Field
by the ideal (x, y^2 + 1)
sage: R.gens(); S.gens(); T.gens()
(x, y)
(a, b)
(0, d)
sage: for n in range(4): d^n
1
d
-1
-d
```

class sage.rings.quotient_ring.**QuotientRingIdeal_generic** (*ring, gens, coerce=True, **kws*)

Bases: *Ideal_generic*

Specialized class for quotient-ring ideals.

EXAMPLES:

```
sage: Zmod(9).ideal([-6, 9])
Ideal (3, 0) of Ring of integers modulo 9
```

class sage.rings.quotient_ring.**QuotientRingIdeal_principal** (*ring, gens, coerce=True, **kws*)

Bases: *Ideal_principal, QuotientRingIdeal_generic*

Specialized class for principal quotient-ring ideals.

EXAMPLES:

```
sage: Zmod(9).ideal(-33)
Principal ideal (3) of Ring of integers modulo 9
```

class sage.rings.quotient_ring.**QuotientRing_generic** (*R, I, names, category=None*)

Bases: *QuotientRing_nc, CommutativeRing*

Creates a quotient ring of a *commutative* ring R by the ideal I .

EXAMPLES:


```

sage: R.<x> = PolynomialRing(ZZ)
sage: I = R.ideal([4 + 3*x + x^2, 1 + x^2])
sage: S = R.quotient_ring(I); S
Quotient of Univariate Polynomial Ring in x over Integer Ring
by the ideal (x^2 + 3*x + 4, x^2 + 1)

```

class sage.rings.quotient_ring.**QuotientRing_nc**(*R, I, names, category=None*)

Bases: *Ring, ParentWithGens*

The quotient ring of *R* by a twosided ideal *I*.

This class is for rings that do not inherit from *CommutativeRing*.

EXAMPLES:

Here is a quotient of a free algebra by a twosided homogeneous ideal:

```

sage: # needs sage.combinat sage.libs.singular sage.modules
sage: F.<x,y,z> = FreeAlgebra(QQ, implementation='letterplace')
sage: I = F * [x*y + y*z, x^2 + x*y - y*x - y^2]*F
sage: Q.<a,b,c> = F.quo(I); Q
Quotient of Free Associative Unital Algebra on 3 generators (x, y, z) over
↳Rational Field
by the ideal (x*y + y*z, x*x + x*y - y*x - y*y)
sage: a*b
-b*c
sage: a^3
-b*c*a - b*c*b - b*c*c

```

A quotient of a quotient is just the quotient of the original top ring by the sum of two ideals:

```

sage: # needs sage.combinat sage.libs.singular sage.modules
sage: J = Q * [a^3 - b^3] * Q
sage: R.<i,j,k> = Q.quo(J); R
Quotient of
Free Associative Unital Algebra on 3 generators (x, y, z) over Rational Field
by the ideal (-y*y*z - y*z*x - 2*y*z*z, x*y + y*z, x*x + x*y - y*x - y*y)
sage: i^3
-j*k*i - j*k*j - j*k*k
sage: j^3
-j*k*i - j*k*j - j*k*k

```

For rings that *do* inherit from *CommutativeRing*, we provide a subclass *QuotientRing_generic*, for backwards compatibility.

EXAMPLES:

```

sage: R.<x> = PolynomialRing(ZZ, 'x')
sage: I = R.ideal([4 + 3*x + x^2, 1 + x^2])
sage: S = R.quotient_ring(I); S
Quotient of Univariate Polynomial Ring in x over Integer Ring
by the ideal (x^2 + 3*x + 4, x^2 + 1)

```

```

sage: R.<x,y> = PolynomialRing(QQ)
sage: S.<a,b> = R.quo(x^2 + y^2)
↳needs sage.libs.singular
sage: a^2 + b^2 == 0
↳needs sage.libs.singular

```

(continues on next page)

(continued from previous page)

```
True
sage: S(0) == a^2 + b^2 #_
↪needs sage.libs.singular
True
```

Again, a quotient of a quotient is just the quotient of the original top ring by the sum of two ideals.

```
sage: # needs sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S.<a,b> = R.quo(1 + y^2)
sage: T.<c,d> = S.quo(a)
sage: T
Quotient of Multivariate Polynomial Ring in x, y over Rational Field
by the ideal (x, y^2 + 1)
sage: T.gens()
(0, d)
```

Element

alias of *QuotientRingElement*

ambient()

Returns the cover ring of the quotient ring: that is, the original ring *R* from which we modded out an ideal, *I*.

EXAMPLES:

```
sage: Q = QuotientRing(ZZ, 7 * ZZ)
sage: Q.cover_ring()
Integer Ring
```

```
sage: P.<x> = QQ[]
sage: Q = QuotientRing(P, x^2 + 1) #_
↪needs sage.libs.pari
sage: Q.cover_ring() #_
↪needs sage.libs.pari
Univariate Polynomial Ring in x over Rational Field
```

characteristic()

Return the characteristic of the quotient ring.

Todo: Not yet implemented!

EXAMPLES:

```
sage: Q = QuotientRing(ZZ, 7*ZZ)
sage: Q.characteristic()
Traceback (most recent call last):
...
NotImplementedError
```

construction()

Returns the functorial construction of *self*.

EXAMPLES:

```

sage: R.<x> = PolynomialRing(ZZ, 'x')
sage: I = R.ideal([4 + 3*x + x^2, 1 + x^2])
sage: R.quotient_ring(I).construction()
(QuotientFunctor, Univariate Polynomial Ring in x over Integer Ring)

sage: # needs sage.combinat sage.libs.singular sage.modules
sage: F.<x,y,z> = FreeAlgebra(QQ, implementation='letterplace')
sage: I = F * [x*y + y*z, x^2 + x*y - y*x - y^2] * F
sage: Q = F.quo(I)
sage: Q.construction()
(QuotientFunctor,
 Free Associative Unital Algebra on 3 generators (x, y, z) over Rational
 ↪Field)

```

cover()

The covering ring homomorphism $R \rightarrow R/I$, equipped with a section.

EXAMPLES:

```

sage: R = ZZ.quo(3 * ZZ)
sage: pi = R.cover()
sage: pi
Ring morphism:
  From: Integer Ring
  To:   Ring of integers modulo 3
  Defn: Natural quotient map
sage: pi(5)
2
sage: l = pi.lift()

```

```

sage: # needs sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ)
sage: Q = R.quo((x^2, y^2))
sage: pi = Q.cover()
sage: pi(x^3 + y)
ybar
sage: l = pi.lift(x + y^3)
sage: l
x
sage: l = pi.lift(); l
Set-theoretic ring morphism:
  From: Quotient of Multivariate Polynomial Ring in x, y over Rational Field
        by the ideal (x^2, y^2)
  To:   Multivariate Polynomial Ring in x, y over Rational Field
  Defn: Choice of lifting map
sage: l(x + y^3)
x

```

cover_ring()

Returns the cover ring of the quotient ring: that is, the original ring R from which we modded out an ideal, I .

EXAMPLES:

```

sage: Q = QuotientRing(ZZ, 7 * ZZ)
sage: Q.cover_ring()
Integer Ring

```

```
sage: P.<x> = QQ[]
sage: Q = QuotientRing(P, x^2 + 1) #_
↳needs sage.libs.pari
sage: Q.cover_ring() #_
↳needs sage.libs.pari
Univariate Polynomial Ring in x over Rational Field
```

defining_ideal()

Returns the ideal generating this quotient ring.

EXAMPLES:

In the integers:

```
sage: Q = QuotientRing(ZZ, 7*ZZ)
sage: Q.defining_ideal()
Principal ideal (7) of Integer Ring
```

An example involving a quotient of a quotient. By Noether's homomorphism theorems, this is actually a quotient by a sum of two ideals:

```
sage: # needs sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S.<a,b> = QuotientRing(R, R.ideal(1 + y^2))
sage: T.<c,d> = QuotientRing(S, S.ideal(a))
sage: S.defining_ideal()
Ideal (y^2 + 1) of Multivariate Polynomial Ring in x, y over Rational Field
sage: T.defining_ideal()
Ideal (x, y^2 + 1) of Multivariate Polynomial Ring in x, y over Rational Field
```

gen (i=0)

Returns the i -th generator for this quotient ring.

EXAMPLES:

```
sage: R = QuotientRing(ZZ, 7*ZZ)
sage: R.gen(0)
1
```

```
sage: # needs sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S.<a,b> = QuotientRing(R, R.ideal(1 + y^2))
sage: T.<c,d> = QuotientRing(S, S.ideal(a))
sage: T
Quotient of Multivariate Polynomial Ring in x, y over Rational Field
by the ideal (x, y^2 + 1)
sage: R.gen(0); R.gen(1)
x
y
sage: S.gen(0); S.gen(1)
a
b
sage: T.gen(0); T.gen(1)
0
d
```

ideal (*gens, **kws)

Return the ideal of `self` with the given generators.

EXAMPLES:

```

sage: R.<x,y> = PolynomialRing(QQ)
sage: S = R.quotient_ring(x^2 + y^2)
sage: S.ideal() #_
↪needs sage.libs.singular
Ideal (0) of Quotient of Multivariate Polynomial Ring in x, y
over Rational Field by the ideal (x^2 + y^2)
sage: S.ideal(x + y + 1) #_
↪needs sage.libs.singular
Ideal (xbar + ybar + 1) of Quotient of Multivariate Polynomial Ring in x, y
over Rational Field by the ideal (x^2 + y^2)

```

is_commutative()

Tell whether this quotient ring is commutative.

Note: This is certainly the case if the cover ring is commutative. Otherwise, if this ring has a finite number of generators, it is tested whether they commute. If the number of generators is infinite, a `NotImplementedError` is raised.

AUTHOR:

- Simon King (2011-03-23): See [Issue #7797](#).

EXAMPLES:

Any quotient of a commutative ring is commutative:

```

sage: P.<a,b,c> = QQ[]
sage: P.quo(P.random_element()).is_commutative()
True

```

The non-commutative case is more interesting:

```

sage: # needs sage.combinat sage.libs.singular sage.modules
sage: F.<x,y,z> = FreeAlgebra(QQ, implementation='letterplace')
sage: I = F * [x*y + y*z, x^2 + x*y - y*x - y^2] * F
sage: Q = F.quo(I)
sage: Q.is_commutative()
False
sage: Q.1*Q.2 == Q.2*Q.1
False

```

In the next example, the generators apparently commute:

```

sage: # needs sage.combinat sage.libs.singular sage.modules
sage: J = F * [x*y - y*x, x*z - z*x, y*z - z*y, x^3 - y^3] * F
sage: R = F.quo(J)
sage: R.is_commutative()
True

```

is_field(*proof=True*)

Returns `True` if the quotient ring is a field. Checks to see if the defining ideal is maximal.

is_integral_domain(*proof=True*)

With `proof` equal to `True` (the default), this function may raise a `NotImplementedError`.

When `proof` is `False`, if `True` is returned, then `self` is definitely an integral domain. If the function returns `False`, then either `self` is not an integral domain or it was unable to determine whether or not `self` is an integral domain.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: R.quo(x^2 - y).is_integral_domain() #_
↳needs sage.libs.singular
True
sage: R.quo(x^2 - y^2).is_integral_domain() #_
↳needs sage.libs.singular
False
sage: R.quo(x^2 - y^2).is_integral_domain(proof=False) #_
↳needs sage.libs.singular
False
sage: R.<a,b,c> = ZZ[]
sage: Q = R.quotient_ring([a, b])
sage: Q.is_integral_domain()
Traceback (most recent call last):
...
NotImplementedError
sage: Q.is_integral_domain(proof=False)
False
```

`is_noetherian()`

Return `True` if this ring is Noetherian.

EXAMPLES:

```
sage: R = QuotientRing(ZZ, 102 * ZZ)
sage: R.is_noetherian()
True

sage: P.<x> = QQ[]
sage: R = QuotientRing(P, x^2 + 1) #_
↳needs sage.libs.pari
sage: R.is_noetherian()
True
```

If the cover ring of `self` is not Noetherian, we currently have no way of testing whether `self` is Noetherian, so we raise an error:

```
sage: R.<x> = InfinitePolynomialRing(QQ)
sage: R.is_noetherian()
False
sage: I = R.ideal([x[1]^2, x[2]])
sage: S = R.quotient(I)
sage: S.is_noetherian()
Traceback (most recent call last):
...
NotImplementedError
```

`lift (x=None)`

Return the lifting map to the cover, or the image of an element under the lifting map.

Note: The category framework imposes that `Q.lift(x)` returns the image of an element `x` under the

lifting map. For backwards compatibility, we let `Q.lift()` return the lifting map.

EXAMPLES:

```
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S = R.quotient(x^2 + y^2)
sage: S.lift() #_
↪needs sage.libs.singular
Set-theoretic ring morphism:
  From: Quotient of Multivariate Polynomial Ring in x, y over Rational Field
        by the ideal (x^2 + y^2)
  To:   Multivariate Polynomial Ring in x, y over Rational Field
  Defn: Choice of lifting map
sage: S.lift(S.0) == x #_
↪needs sage.libs.singular
True
```

lifting_map()

Return the lifting map to the cover.

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S = R.quotient(x^2 + y^2)
sage: pi = S.cover(); pi
Ring morphism:
  From: Multivariate Polynomial Ring in x, y over Rational Field
  To:   Quotient of Multivariate Polynomial Ring in x, y over Rational Field
        by the ideal (x^2 + y^2)
  Defn: Natural quotient map
sage: L = S.lifting_map(); L
Set-theoretic ring morphism:
  From: Quotient of Multivariate Polynomial Ring in x, y over Rational Field
        by the ideal (x^2 + y^2)
  To:   Multivariate Polynomial Ring in x, y over Rational Field
  Defn: Choice of lifting map
sage: L(S.0)
x
sage: L(S.1)
y
```

Note that some reduction may be applied so that the lift of a reduction need not equal the original element:

```
sage: z = pi(x^3 + 2*y^2); z #_
↪needs sage.libs.singular
-xbar*ybar^2 + 2*ybar^2
sage: L(z) #_
↪needs sage.libs.singular
-x*y^2 + 2*y^2
sage: L(z) == x^3 + 2*y^2 #_
↪needs sage.libs.singular
False
```

Test that there also is a lift for rings that are no instances of *Ring* (see Issue #11068):

```

sage: # needs sage.modules
sage: MS = MatrixSpace(GF(5), 2, 2)
sage: I = MS * [MS.0*MS.1, MS.2 + MS.3] * MS
sage: Q = MS.quo(I)
sage: Q.lift()
Set-theoretic ring morphism:
  From: Quotient of Full MatrixSpace of 2 by 2 dense matrices
        over Finite Field of size 5 by the ideal
(
  [0 1]
  [0 0],

  [0 0]
  [1 1]
)
To: Full MatrixSpace of 2 by 2 dense matrices over Finite Field of size 5
Defn: Choice of lifting map

```

ngens ()

Returns the number of generators for this quotient ring.

Todo: Note that `ngens` counts 0 as a generator. Does this make sense? That is, since 0 only generates itself and the fact that this is true for all rings, is there a way to “knock it off” of the generators list if a generator of some original ring is modded out?

EXAMPLES:

```

sage: R = QuotientRing(ZZ, 7*ZZ)
sage: R.gens(); R.ngens()
(1,)
1

```

```

sage: # needs sage.libs.singular
sage: R.<x,y> = PolynomialRing(QQ,2)
sage: S.<a,b> = QuotientRing(R, R.ideal(1 + y^2))
sage: T.<c,d> = QuotientRing(S, S.ideal(a))
sage: T
Quotient of Multivariate Polynomial Ring in x, y over Rational Field
by the ideal (x, y^2 + 1)
sage: R.gens(); S.gens(); T.gens()
(x, y)
(a, b)
(0, d)
sage: R.ngens(); S.ngens(); T.ngens()
2
2
2

```

random_element ()

Return a random element of this quotient ring obtained by sampling a random element of the cover ring and reducing it modulo the defining ideal.

EXAMPLES:


```

sage: R.<x,y> = QQ[]
sage: S = R.quotient([x^3, y^2])
sage: S.random_element() # random
-8/5*xbar^2 + 3/2*xbar*ybar + 2*xbar - 4/23
    
```

retract (*x*)

The image of an element of the cover ring under the quotient map.

INPUT:

- *x* – An element of the cover ring

OUTPUT:

The image of the given element in *self*.

EXAMPLES:

```

sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S = R.quotient(x^2 + y^2)
sage: S.retract((x+y)^2)
↪needs sage.libs.singular
2*xbar*ybar
    
```

term_order ()

Return the term order of this ring.

EXAMPLES:

```

sage: P.<a,b,c> = PolynomialRing(QQ)
sage: I = Ideal([a^2 - a, b^2 - b, c^2 - c])
sage: Q = P.quotient(I)
sage: Q.term_order()
Degree reverse lexicographic term order
    
```

`sage.rings.quotient_ring.is_QuotientRing(x)`

Tests whether or not *x* inherits from *QuotientRing_nc*.

EXAMPLES:

```

sage: from sage.rings.quotient_ring import is_QuotientRing
sage: R.<x> = PolynomialRing(ZZ, 'x')
sage: I = R.ideal([4 + 3*x + x^2, 1 + x^2])
sage: S = R.quotient_ring(I)
sage: is_QuotientRing(S)
True
sage: is_QuotientRing(R)
False
    
```

```

sage: # needs sage.combinat sage.libs.singular sage.modules
sage: F.<x,y,z> = FreeAlgebra(QQ, implementation='letterplace')
sage: I = F * [x*y + y*z, x^2 + x*y - y*x - y^2] * F
sage: Q = F.quo(I)
sage: is_QuotientRing(Q)
True
sage: is_QuotientRing(F)
False
    
```

4.2 Quotient Ring Elements

AUTHORS:

- William Stein

class sage.rings.quotient_ring_element.**QuotientRingElement** (*parent, rep, reduce=True*)

Bases: `RingElement`

An element of a quotient ring R/I .

INPUT:

- *parent* – the ring R/I
- *rep* – a representative of the element in R ; this is used as the internal representation of the element
- *reduce* – bool (default: True) – if True, then the internal representation of the element is *rep* reduced modulo the ideal I

EXAMPLES:

```
sage: R.<x> = PolynomialRing(ZZ)
sage: S.<xbar> = R.quo((4 + 3*x + x^2, 1 + x^2)); S
Quotient of Univariate Polynomial Ring in x over Integer Ring
by the ideal (x^2 + 3*x + 4, x^2 + 1)
sage: v = S.gens(); v
(xbar,)
```

```
sage: loads(v[0].dumps()) == v[0]
True
```

```
sage: R.<x,y> = PolynomialRing(QQ, 2)
sage: S = R.quo(x^2 + y^2); S
Quotient of Multivariate Polynomial Ring in x, y over Rational Field
by the ideal (x^2 + y^2)
sage: S.gens()
↪needs sage.libs.singular #_
(xbar, ybar)
```

We name each of the generators.

```
sage: # needs sage.libs.singular
sage: S.<a,b> = R.quotient(x^2 + y^2)
sage: a
a
sage: b
b
sage: a^2 + b^2 == 0
True
sage: b.lift()
y
sage: (a^3 + b^2).lift()
-x*y^2 + y^2
```

is_unit ()

Return True if self is a unit in the quotient ring.

EXAMPLES:

```

sage: R.<x,y> = QQ[]; S.<a,b> = R.quo(1 - x*y); type(a) #_
↳needs sage.libs.singular
<class 'sage.rings.quotient_ring.QuotientRing_generic_with_category.element_
↳class'>
sage: a*b #_
↳needs sage.libs.singular
1
sage: S(2).is_unit() #_
↳needs sage.libs.singular
True
    
```

Check that [Issue #29469](#) is fixed:

```

sage: a.is_unit() #_
↳needs sage.libs.singular
True
sage: (a+b).is_unit() #_
↳needs sage.libs.singular
False
    
```

lc()

Return the leading coefficient of this quotient ring element.

EXAMPLES:

```

sage: # needs sage.libs.singular
sage: R.<x,y,z> = PolynomialRing(GF(7), 3, order='lex')
sage: I = sage.rings.ideal.FieldIdeal(R)
sage: Q = R.quo(I)
sage: f = Q(z*y + 2*x)
sage: f.lc()
2
    
```

lift()

If self is an element of R/I , then return self as an element of R .

EXAMPLES:

```

sage: R.<x,y> = QQ[]; S.<a,b> = R.quo(x^2 + y^2); type(a) #_
↳needs sage.libs.singular
<class 'sage.rings.quotient_ring.QuotientRing_generic_with_category.element_
↳class'>
sage: a.lift() #_
↳needs sage.libs.singular
x
sage: (3/5*(a + a^2 + b^2)).lift() #_
↳needs sage.libs.singular
3/5*x
    
```

lm()

Return the leading monomial of this quotient ring element.

EXAMPLES:

```

sage: # needs sage.libs.singular
sage: R.<x,y,z> = PolynomialRing(GF(7), 3, order='lex')
sage: I = sage.rings.ideal.FieldIdeal(R)
    
```

(continues on next page)

(continued from previous page)

```
sage: Q = R.quo(I)
sage: f = Q(z*y + 2*x)
sage: f.lm()
xbar
```

lt()

Return the leading term of this quotient ring element.

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: R.<x,y,z> = PolynomialRing(GF(7), 3, order='lex')
sage: I = sage.rings.ideal.FieldIdeal(R)
sage: Q = R.quo(I)
sage: f = Q(z*y + 2*x)
sage: f.lt()
2*xbar
```

monomials()

Return the monomials in self.

OUTPUT:

A list of monomials.

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: R.<x,y> = QQ[]; S.<a,b> = R.quo(x^2 + y^2); type(a)
<class 'sage.rings.quotient_ring.QuotientRing_generic_with_category.element_
↳class'>
sage: a.monomials()
[a]
sage: (a + a*b).monomials()
[a*b, a]
sage: R.zero().monomials()
[]
```

reduce(G)

Reduce this quotient ring element by a set of quotient ring elements G.

INPUT:

- G – a list of quotient ring elements

Warning: This method is not guaranteed to return unique minimal results. For quotients of polynomial rings, use `reduce()` on the ideal generated by G, instead.

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: P.<a,b,c,d,e> = PolynomialRing(GF(2), 5, order='lex')
sage: I1 = ideal([a*b + c*d + 1, a*c*e + d*e,
...:             a*b*e + c*e, b*c + c*d*e + 1])
sage: Q = P.quotient(sage.rings.ideal.FieldIdeal(P))
sage: I2 = ideal([Q(f) for f in I1.gens()])
```

(continues on next page)

(continued from previous page)

```
sage: f = Q((a*b + c*d + 1)^2 + e)
sage: f.reduce(I2.gens())
ebar
```

Notice that the result above is not minimal:

```
sage: I2.reduce(f) #_
↳needs sage.libs.singular
0
```

variables()

Return all variables occurring in `self`.

OUTPUT:

A tuple of linear monomials, one for each variable occurring in `self`.

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: R.<x,y> = QQ[]; S.<a,b> = R.quo(x^2 + y^2); type(a)
<class 'sage.rings.quotient_ring.QuotientRing_generic_with_category.element_
↳class'>
sage: a.variables()
(a,)
sage: b.variables()
(b,)
sage: s = a^2 + b^2 + 1; s
1
sage: s.variables()
()
sage: (a + b).variables()
(a, b)
```


FRACTION FIELDS

5.1 Fraction Field of Integral Domains

AUTHORS:

- William Stein (with input from David Joyner, David Kohel, and Joe Wetherell)
- Burcin Erocal
- Julian R uth (2017-06-27): embedding into the field of fractions and its section

EXAMPLES:

Quotienting is a constructor for an element of the fraction field:

```

sage: R.<x> = QQ[]
sage: (x^2-1)/(x+1)
x - 1
sage: parent((x^2-1)/(x+1))
Fraction Field of Univariate Polynomial Ring in x over Rational Field
```

The GCD is not taken (since it doesn't converge sometimes) in the inexact case:

```

sage: # needs sage.rings.real_mpr
sage: Z.<z> = CC[]
sage: I = CC.gen()
sage: (1+I+z)/(z+0.1*I)
(z + 1.000000000000000 + I)/(z + 0.100000000000000*I)
sage: (1+I*z)/(z+1.1)
(I*z + 1.000000000000000)/(z + 1.100000000000000)
```

`sage.rings.fraction_field.FractionField(R, names=None)`

Create the fraction field of the integral domain R.

INPUT:

- R – an integral domain
- names – ignored

EXAMPLES:

We create some example fraction fields:

```

sage: FractionField(IntegerRing())
Rational Field
sage: FractionField(PolynomialRing(RationalField()), 'x')
```

(continues on next page)

(continued from previous page)

```
Fraction Field of Univariate Polynomial Ring in x over Rational Field
sage: FractionField(PolynomialRing(IntegerRing(), 'x'))
Fraction Field of Univariate Polynomial Ring in x over Integer Ring
sage: FractionField(PolynomialRing(RationalField(), 2, 'x'))
Fraction Field of Multivariate Polynomial Ring in x0, x1 over Rational Field
```

Dividing elements often implicitly creates elements of the fraction field:

```
sage: x = PolynomialRing(RationalField(), 'x').gen()
sage: f = x/(x+1)
sage: g = x**3/(x+1)
sage: f/g
1/x^2
sage: g/f
x^2
```

The input must be an integral domain:

```
sage: Frac(Integers(4))
Traceback (most recent call last):
...
TypeError: R must be an integral domain
```

class sage.rings.fraction_field.FractionFieldEmbedding

Bases: DefaultConvertMap_unique

The embedding of an integral domain into its field of fractions.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: f = R.fraction_field().coerce_map_from(R); f
Coercion map:
  From: Univariate Polynomial Ring in x over Rational Field
  To:   Fraction Field of Univariate Polynomial Ring in x over Rational Field
```

is_injective()

Return whether this map is injective.

EXAMPLES:

The map from an integral domain to its fraction field is always injective:

```
sage: R.<x> = QQ[]
sage: R.fraction_field().coerce_map_from(R).is_injective()
True
```

is_surjective()

Return whether this map is surjective.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: R.fraction_field().coerce_map_from(R).is_surjective()
False
```


section()

Return a section of this map.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: R.fraction_field().coerce_map_from(R).section()
Section map:
  From: Fraction Field of Univariate Polynomial Ring in x over Rational Field
  To:   Univariate Polynomial Ring in x over Rational Field
```

class sage.rings.fraction_field.**FractionFieldEmbeddingSection**

Bases: [Section](#)

The section of the embedding of an integral domain into its field of fractions.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: f = R.fraction_field().coerce_map_from(R).section(); f
Section map:
  From: Fraction Field of Univariate Polynomial Ring in x over Rational Field
  To:   Univariate Polynomial Ring in x over Rational Field
```

class sage.rings.fraction_field.**FractionField_1poly_field**(*R*, *element_class*=<class 'sage.rings.fraction_field_element.FractionFieldElement_1poly_field'>)

Bases: [FractionField_generic](#)

The fraction field of a univariate polynomial ring over a field.

Many of the functions here are included for coherence with number fields.

class_number()

Here for compatibility with number fields and function fields.

EXAMPLES:

```
sage: R.<t> = GF(5)[]; K = R.fraction_field()
sage: K.class_number()
1
```

function_field()

Return the isomorphic function field.

EXAMPLES:

```
sage: R.<t> = GF(5)[]
sage: K = R.fraction_field()
sage: K.function_field()
Rational function field in t over Finite Field of size 5
```

See also:

[sage.rings.function_field.RationalFunctionField.field\(\)](#)

maximal_order()

Return the maximal order in this fraction field.

EXAMPLES:

```
sage: K = FractionField(GF(5) ['t'])
sage: K.maximal_order()
Univariate Polynomial Ring in t over Finite Field of size 5
```

ring_of_integers()

Return the ring of integers in this fraction field.

EXAMPLES:

```
sage: K = FractionField(GF(5) ['t'])
sage: K.ring_of_integers()
Univariate Polynomial Ring in t over Finite Field of size 5
```

```
class sage.rings.fraction_field.FractionField_generic (R, element_class=<class
'sage.rings.fraction_field_element.FractionFieldElement'>,
category=Category of quotient
fields)
```

Bases: *Field*

The fraction field of an integral domain.

base_ring()

Return the base ring of self.

This is the base ring of the ring which this fraction field is the fraction field of.

EXAMPLES:

```
sage: R = Frac(ZZ ['t'])
sage: R.base_ring()
Integer Ring
```

characteristic()

Return the characteristic of this fraction field.

EXAMPLES:

```
sage: R = Frac(ZZ ['t'])
sage: R.base_ring()
Integer Ring
sage: R = Frac(ZZ ['t']); R.characteristic()
0
sage: R = Frac(GF(5) ['w']); R.characteristic()
5
```

construction()

EXAMPLES:

```
sage: Frac(ZZ ['x']).construction()
(FractionField, Univariate Polynomial Ring in x over Integer Ring)
sage: K = Frac(GF(3) ['t'])
sage: f, R = K.construction()
sage: f(R)
Fraction Field of Univariate Polynomial Ring in t
over Finite Field of size 3
sage: f(R) == K
True
```

gen (*i=0*)Return the *i*-th generator of self.

EXAMPLES:

```

sage: R = Frac(PolynomialRing(QQ, 'z', 10)); R
Fraction Field of Multivariate Polynomial Ring
in z0, z1, z2, z3, z4, z5, z6, z7, z8, z9 over Rational Field
sage: R.0
z0
sage: R.gen(3)
z3
sage: R.3
z3

```

is_exact ()

Return if self is exact which is if the underlying ring is exact.

EXAMPLES:

```

sage: Frac(ZZ['x']).is_exact()
True
sage: Frac(CDF['x']).is_exact()
↪needs sage.rings.complex_double
False

```

is_field (*proof=True*)

Return True, since the fraction field is a field.

EXAMPLES:

```

sage: Frac(ZZ).is_field()
True

```

is_finite ()

Tells whether this fraction field is finite.

Note: A fraction field is finite if and only if the associated integral domain is finite.

EXAMPLES:

```

sage: Frac(QQ['a', 'b', 'c']).is_finite()
False

```

ngens ()

This is the same as for the parent object.

EXAMPLES:

```

sage: R = Frac(PolynomialRing(QQ, 'z', 10)); R
Fraction Field of Multivariate Polynomial Ring
in z0, z1, z2, z3, z4, z5, z6, z7, z8, z9 over Rational Field
sage: R.ngens()
10

```

random_element (*args, **kws)

Return a random element in this fraction field.

The arguments are passed to the random generator of the underlying ring.

EXAMPLES:

```
sage: F = ZZ['x'].fraction_field()
sage: F.random_element() # random
(2*x - 8)/(-x^2 + x)
```

```
sage: f = F.random_element(degree=5)
sage: f.numerator().degree() == f.denominator().degree()
True
sage: f.denominator().degree() <= 5
True
sage: while f.numerator().degree() != 5:
.....:     f = F.random_element(degree=5)
```

ring()

Return the ring that this is the fraction field of.

EXAMPLES:

```
sage: R = Frac(QQ['x,y'])
sage: R
Fraction Field of Multivariate Polynomial Ring in x, y over Rational Field
sage: R.ring()
Multivariate Polynomial Ring in x, y over Rational Field
```

some_elements()

Return some elements in this field.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: R.fraction_field().some_elements()
[0,
 1,
 x,
 2*x,
 x/(x^2 + 2*x + 1),
 1/x^2,
 ...
 (2*x^2 + 2)/(x^2 + 2*x + 1),
 (2*x^2 + 2)/x^3,
 (2*x^2 + 2)/(x^2 - 1),
 2]
```

`sage.rings.fraction_field.is_FractionField(x)`

Test whether or not *x* inherits from *FractionField_generic*.

EXAMPLES:

```
sage: from sage.rings.fraction_field import is_FractionField
sage: is_FractionField(Frac(ZZ['x']))
doctest:warning...
DeprecationWarning: The function is_FractionField is deprecated;
```

(continues on next page)

(continued from previous page)

```

use 'isinstance(..., FractionField_generic)' instead.
See https://github.com/sagemath/sage/issues/38128 for details.
True
sage: is_FractionField(QQ)
False

```

5.2 Fraction Field Elements

AUTHORS:

- William Stein (input from David Joyner, David Kohel, and Joe Wetherell)
- Sebastian Pancratz (2010-01-06): Rewrite of addition, multiplication and derivative to use Henrici's algorithms [Hor1972]

class sage.rings.fraction_field_element.**FractionFieldElement**

Bases: `FieldElement`

EXAMPLES:

```

sage: K = FractionField(PolynomialRing(QQ, 'x'))
sage: K
Fraction Field of Univariate Polynomial Ring in x over Rational Field
sage: loads(K.dumps()) == K
True
sage: x = K.gen()
sage: f = (x^3 + x)/(17 - x^19); f
(-x^3 - x)/(x^19 - 17)
sage: loads(f.dumps()) == f
True

```

denominator()

Return the denominator of self.

EXAMPLES:

```

sage: R.<x,y> = ZZ[]
sage: f = x/y + 1; f
(x + y)/y
sage: f.denominator()
y

```

is_one()

Return True if this element is equal to one.

EXAMPLES:

```

sage: F = ZZ['x,y'].fraction_field()
sage: x,y = F.gens()
sage: (x/x).is_one()
True
sage: (x/y).is_one()
False

```

is_square (*root=False*)

Return whether or not `self` is a perfect square.

If the optional argument `root` is `True`, then also returns a square root (or `None`, if the fraction field element is not square).

INPUT:

- `root` – whether or not to also return a square root (default: `False`)

OUTPUT:

- `bool` – whether or not a square
- `object` – (optional) an actual square root if found, and `None` otherwise.

EXAMPLES:

```
sage: R.<t> = QQ[]
sage: (1/t).is_square()
False
sage: (1/t^6).is_square()
True
sage: ((1+t)^4/t^6).is_square()
True
sage: (4*(1+t)^4/t^6).is_square()
True
sage: (2*(1+t)^4/t^6).is_square()
False
sage: ((1+t)/t^6).is_square()
False

sage: (4*(1+t)^4/t^6).is_square(root=True)
(True, (2*t^2 + 4*t + 2)/t^3)
sage: (2*(1+t)^4/t^6).is_square(root=True)
(False, None)

sage: R.<x> = QQ[]
sage: a = 2*(x+1)^2 / (2*(x-1)^2); a
(x^2 + 2*x + 1)/(x^2 - 2*x + 1)
sage: a.is_square()
True
sage: (0/x).is_square()
True
```

is_zero ()

Return `True` if this element is equal to zero.

EXAMPLES:

```
sage: F = ZZ['x,y'].fraction_field()
sage: x,y = F.gens()
sage: t = F(0)/x
sage: t.is_zero()
True
sage: u = 1/x - 1/x
sage: u.is_zero()
True
sage: u.parent() is F
True
```

nth_root (*n*)

Return a *n*-th root of this element.

EXAMPLES:

```
sage: R = QQ['t'].fraction_field()
sage: t = R.gen()
sage: p = (t+1)^3 / (t^2+t-1)^3
sage: p.nth_root(3)
(t + 1)/(t^2 + t - 1)

sage: p = (t+1) / (t-1)
sage: p.nth_root(2)
Traceback (most recent call last):
...
ValueError: not a 2nd power
```

numerator ()

Return the numerator of *self*.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: f = x/y + 1; f
(x + y)/y
sage: f.numerator()
x + y
```

reduce ()

Reduce this fraction.

Divides out the gcd of the numerator and denominator. If the denominator becomes a unit, it becomes 1. Additionally, depending on the base ring, the leading coefficients of the numerator and the denominator may be normalized to 1.

Automatically called for exact rings, but because it may be numerically unstable for inexact rings it must be called manually in that case.

EXAMPLES:

```
sage: R.<x> = RealField(10) [] #_
↪needs sage.rings.real_mpfr
sage: f = (x^2+2*x+1)/(x+1); f #_
↪needs sage.rings.real_mpfr
(x^2 + 2.0*x + 1.0)/(x + 1.0)
sage: f.reduce(); f #_
↪needs sage.rings.real_mpfr
x + 1.0
```

specialization (*D=None*, *phi=None*)

Returns the specialization of a fraction element of a polynomial ring

subs (*in_dict=None*, **args*, ***kwds*)

Substitute variables in the numerator and denominator of *self*.

If a dictionary is passed, the keys are mapped to generators of the parent ring. Otherwise, the arguments are transmitted unchanged to the method `subs` of the numerator and the denominator.

EXAMPLES:

```
sage: x, y = PolynomialRing(ZZ, 2, 'xy').gens()
sage: f = x^2 + y + x^2*y^2 + 5
sage: (1/f).subs(x=5)
1/(25*y^2 + y + 30)
```

valuation (*v=None*)

Return the valuation of `self`, assuming that the numerator and denominator have valuation functions defined on them.

EXAMPLES:

```
sage: x = PolynomialRing(RationalField(), 'x').gen()
sage: f = (x^3 + x)/(x^2 - 2*x^3)
sage: f
(-1/2*x^2 - 1/2)/(x^2 - 1/2*x)
sage: f.valuation()
-1
sage: f.valuation(x^2 + 1)
1
```

class `sage.rings.fraction_field_element.FractionFieldElement_1poly_field`

Bases: *FractionFieldElement*

A fraction field element where the parent is the fraction field of a univariate polynomial ring over a field.

Many of the functions here are included for coherence with number fields.

is_integral ()

Returns whether this element is actually a polynomial.

EXAMPLES:

```
sage: R.<t> = QQ[]
sage: elt = (t^2 + t - 2) / (t + 2); elt # == (t + 2)*(t - 1)/(t + 2)
t - 1
sage: elt.is_integral()
True
sage: elt = (t^2 - t) / (t+2); elt # == t*(t - 1)/(t + 2)
(t^2 - t)/(t + 2)
sage: elt.is_integral()
False
```

reduce ()

Pick a normalized representation of `self`.

In particular, for any `a == b`, after normalization they will have the same numerator and denominator.

EXAMPLES:

For univariate rational functions over a field, we have:

```
sage: R.<x> = QQ[]
sage: (2 + 2*x) / (4*x) # indirect doctest
(1/2*x + 1/2)/x
```

Compare with:


```
sage: R.<x> = ZZ[]
sage: (2 + 2*x) / (4*x)
(x + 1)/(2*x)
```

support ()

Returns a sorted list of primes dividing either the numerator or denominator of this element.

EXAMPLES:

```
sage: R.<t> = QQ[]
sage: h = (t^14 + 2*t^12 - 4*t^11 - 8*t^9 + 6*t^8 + 12*t^6 - 4*t^5
.....:      - 8*t^3 + t^2 + 2)/(t^6 + 6*t^5 + 9*t^4 - 2*t^2 - 12*t - 18)
sage: h.support()
↳needs sage.libs.pari
[t - 1, t + 3, t^2 + 2, t^2 + t + 1, t^4 - 2]
```

`sage.rings.fraction_field_element.is_FractionFieldElement(x)`

Return whether or not x is a *FractionFieldElement*.

EXAMPLES:

```
sage: from sage.rings.fraction_field_element import is_FractionFieldElement
sage: R.<x> = ZZ[]
sage: is_FractionFieldElement(x/2)
doctest:warning...
DeprecationWarning: The function is_FractionFieldElement is deprecated;
use 'isinstance(..., FractionFieldElement)' instead.
See https://github.com/sagemath/sage/issues/38128 for details.
False
sage: is_FractionFieldElement(2/x)
True
sage: is_FractionFieldElement(1/3)
False
```

`sage.rings.fraction_field_element.make_element(parent, numerator, denominator)`

Used for unpickling *FractionFieldElement* objects (and subclasses).

EXAMPLES:

```
sage: from sage.rings.fraction_field_element import make_element
sage: R = ZZ['x,y']
sage: x,y = R.gens()
sage: F = R.fraction_field()
sage: make_element(F, 1 + x, 1 + y)
(x + 1)/(y + 1)
```

`sage.rings.fraction_field_element.make_element_old(parent, cdict)`

Used for unpickling old *FractionFieldElement* pickles.

EXAMPLES:

```
sage: from sage.rings.fraction_field_element import make_element_old
sage: R.<x,y> = ZZ[]
sage: F = R.fraction_field()
sage: make_element_old(F, {'_FractionFieldElement__numerator': x + y,
.....:                    '_FractionFieldElement__denominator': x - y})
(x + y)/(x - y)
```


LOCALIZATION

6.1 Localization

Localization is an important ring construction tool. Whenever you have to extend a given integral domain such that it contains the inverses of a finite set of elements but should allow non injective homomorphic images this construction will be needed. See the example on Ariki-Koike algebras below for such an application.

EXAMPLES:

```
sage: # needs sage.modules
sage: LZ = Localization(ZZ, (5,11))
sage: m = matrix(LZ, [[5, 7], [0,11]])
sage: m.parent()
Full MatrixSpace of 2 by 2 dense matrices over Integer Ring localized at (5, 11)
sage: ~m      # parent of inverse is different: see documentation of m.__invert__
[ 1/5 -7/55]
[  0  1/11]
sage: ~m.parent()
Full MatrixSpace of 2 by 2 dense matrices over Rational Field
sage: mi = matrix(LZ, ~m)
sage: mi.parent()
Full MatrixSpace of 2 by 2 dense matrices over Integer Ring localized at (5, 11)
sage: mi == ~m
True
```

The next example defines the most general ring containing the coefficients of the irreducible representations of the Ariki-Koike algebra corresponding to the three colored permutations on three elements:

```
sage: R.<u0, u1, u2, q> = ZZ[]
sage: u = [u0, u1, u2]
sage: S = Set(u)
sage: I = S.cartesian_product(S)
sage: add_units = u + [q, q + 1] + [ui - uj for ui, uj in I if ui != uj]
sage: add_units += [q*ui - uj for ui, uj in I if ui != uj]
sage: L = R.localization(tuple(add_units)); L #_
↪needs sage.libs.pari
Multivariate Polynomial Ring in u0, u1, u2, q over Integer Ring localized at
(q, q + 1, u2, u1, u1 - u2, u0, u0 - u2, u0 - u1, u2*q - u1, u2*q - u0,
u1*q - u2, u1*q - u0, u0*q - u2, u0*q - u1)
```

Define the representation matrices (of one of the three dimensional irreducible representations):

```
sage: # needs sage.libs.pari sage.modules
sage: m1 = matrix(L, [[u1, 0, 0], [0, u0, 0], [0, 0, u0]])
```

(continues on next page)

(continued from previous page)

```
sage: m2 = matrix(L, [(u0*q - u0)/(u0 - u1), (u0*q - u1)/(u0 - u1), 0],
.....:               [(-u1*q + u0)/(u0 - u1), (-u1*q + u1)/(u0 - u1), 0],
.....:               [0, 0, -1]])
sage: m3 = matrix(L, [-1, 0, 0],
.....:               [0, u0*(1 - q)/(u1*q - u0), q*(u1 - u0)/(u1*q - u0)],
.....:               [0, (u1*q^2 - u0)/(u1*q - u0), (u1*q^2 - u1*q)/(u1*q - u0)])
sage: m1.base_ring() == L
True
```

Check relations of the Ariki-Koike algebra:

```
sage: # needs sage.libs.pari sage.modules
sage: m1*m2*m1*m2 == m2*m1*m2*m1
True
sage: m2*m3*m2 == m3*m2*m3
True
sage: m1*m3 == m3*m1
True
sage: m1**3 - (u0+u1+u2)*m1**2 + (u0*u1+u0*u2+u1*u2)*m1 - u0*u1*u2 == 0
True
sage: m2**2 - (q-1)*m2 - q == 0
True
sage: m3**2 - (q-1)*m3 - q == 0
True
sage: ~m1 in m1.parent()
True
sage: ~m2 in m2.parent()
True
sage: ~m3 in m3.parent()
True
```

Obtain specializations in positive characteristic:

```
sage: # needs sage.libs.pari sage.modules
sage: Fp = GF(17)
sage: f = L.hom((3,5,7,11), codomain=Fp); f
Ring morphism:
  From: Multivariate Polynomial Ring in u0, u1, u2, q over Integer Ring localized at
        (q, q + 1, u2, u1, u1 - u2, u0, u0 - u2, u0 - u1, u2*q - u1, u2*q - u0,
         u1*q - u2, u1*q - u0, u0*q - u2, u0*q - u1)
  To:   Finite Field of size 17
Defn:  u0 |--> 3
        u1 |--> 5
        u2 |--> 7
        q |--> 11
sage: mFp1 = matrix({k: f(v) for k, v in m1.dict().items()}); mFp1
[5 0 0]
[0 3 0]
[0 0 3]
sage: mFp1.base_ring()
Finite Field of size 17
sage: mFp2 = matrix({k: f(v) for k, v in m2.dict().items()}); mFp2
[ 2  3  0]
[ 9  8  0]
[ 0  0 16]
sage: mFp3 = matrix({k: f(v) for k, v in m3.dict().items()}); mFp3
[16 0 0]
```

(continues on next page)

(continued from previous page)

```
[ 0 4 5]
[ 0 7 6]
```

Obtain specializations in characteristic 0:

```
sage: # needs sage.libs.pari
sage: fQ = L.hom((3,5,7,11), codomain=QQ); fQ
Ring morphism:
  From: Multivariate Polynomial Ring in u0, u1, u2, q over Integer Ring
        localized at (q, q + 1, u2, u1, u1 - u2, u0, u0 - u2, u0 - u1,
        u2*q - u1, u2*q - u0, u1*q - u2, u1*q - u0, u0*q - u2, u0*q - u1)
  To:   Rational Field
  Defn: u0 |--> 3
        u1 |--> 5
        u2 |--> 7
        q |--> 11

sage: # needs sage.libs.pari sage.modules sage.rings.finite_rings
sage: mQ1 = matrix({k: fQ(v) for k, v in m1.dict().items()}); mQ1
[5 0 0]
[0 3 0]
[0 0 3]
sage: mQ1.base_ring()
Rational Field
sage: mQ2 = matrix({k: fQ(v) for k, v in m2.dict().items()}); mQ2
[-15 -14  0]
[ 26  25  0]
[  0  0 -1]
sage: mQ3 = matrix({k: fQ(v) for k, v in m3.dict().items()}); mQ3
[  -1  0  0]
[  0 -15/26  11/26]
[  0  301/26  275/26]

sage: # needs sage.libs.pari sage.libs.singular
sage: S.<x, y, z, t> = QQ[]
sage: T = S.quo(x + y + z)
sage: F = T.fraction_field()
sage: fF = L.hom((x, y, z, t), codomain=F); fF
Ring morphism:
  From: Multivariate Polynomial Ring in u0, u1, u2, q over Integer Ring
        localized at (q, q + 1, u2, u1, u1 - u2, u0, u0 - u2, u0 - u1,
        u2*q - u1, u2*q - u0, u1*q - u2, u1*q - u0, u0*q - u2, u0*q - u1)
  To:   Fraction Field of Quotient of Multivariate Polynomial Ring in x, y, z, t
        over Rational Field by the ideal (x + y + z)
  Defn: u0 |--> -ybar - zbar
        u1 |--> ybar
        u2 |--> zbar
        q |--> tbar
sage: mF1 = matrix({k: fF(v) for k, v in m1.dict().items()}); mF1 #_
↪needs sage.modules
[  ybar  0  0]
[  0 -ybar - zbar  0]
[  0  0 -ybar - zbar]
sage: mF1.base_ring() == F #_
↪needs sage.modules
True
```

AUTHORS:

- Sebastian Oehms 2019-12-09: initial version.
- Sebastian Oehms 2022-03-05: fix some corner cases and add `factor()` (Issue #33463)

class `sage.rings.localization.Localization` (*base_ring*, *extra_units*, *names=None*,
normalize=True, *category=None*, *warning=True*)

Bases: `IntegralDomain`, `UniqueRepresentation`

The localization generalizes the construction of the field of fractions of an integral domain to an arbitrary ring. Given a (not necessarily commutative) ring R and a subset S of R , there exists a ring $R[S^{-1}]$ together with the ring homomorphism $R \rightarrow R[S^{-1}]$ that “inverts” S ; that is, the homomorphism maps elements in S to unit elements in $R[S^{-1}]$ and, moreover, any ring homomorphism from R that “inverts” S uniquely factors through $R[S^{-1}]$.

The ring $R[S^{-1}]$ is called the *localization* of R with respect to S . For example, if R is a commutative ring and f an element in R , then the localization consists of elements of the form $r/f, r \in R, n \geq 0$ (to be precise, $R[f^{-1}] = R[t]/(ft - 1)$).

The above text is taken from *Wikipedia*. The construction here used for this class relies on the construction of the field of fraction and is therefore restricted to integral domains.

Accordingly, this class is inherited from `IntegralDomain` and can only be used in that context. Furthermore, the base ring should support `sage.structure.element.CommutativeRingElement.divides()` and the exact division operator `//` (`sage.structure.element.Element.__floordiv__()`) in order to guarantee a successful application.

INPUT:

- `base_ring` – an instance of `Ring` allowing the construction of `fraction_field()` (that is an integral domain)
- `extra_units` – tuple of elements of `base_ring` which should be turned into units
- `names` – passed to `IntegralDomain`
- `normalize` – (default: `True`) passed to `IntegralDomain`
- `category` – (default: `None`) passed to `IntegralDomain`
- `warning` – (default: `True`) to suppress a warning which is thrown if self cannot be represented uniquely

REFERENCES:

- [Wikipedia article Ring_\(mathematics\)#Localization](#)

EXAMPLES:

```
sage: L = Localization(ZZ, (3,5))
sage: 1/45 in L
True
sage: 1/43 in L
False

sage: Localization(L, (7,11))
Integer Ring localized at (3, 5, 7, 11)
sage: _.is_subring(QQ)
True

sage: L(~7)
Traceback (most recent call last):
...
```

(continues on next page)

(continued from previous page)

```

ValueError: factor 7 of denominator is not a unit

sage: Localization(Zp(7), (3, 5)) #_
↳needs sage.rings.padics
Traceback (most recent call last):
...
ValueError: all given elements are invertible in
7-adic Ring with capped relative precision 20

sage: # needs sage.libs.pari
sage: R.<x> = ZZ[]
sage: L = R.localization(x**2 + 1)
sage: s = (x+5)/(x**2+1)
sage: s in L
True
sage: t = (x+5)/(x**2+2)
sage: t in L
False
sage: L(t)
Traceback (most recent call last):
...
TypeError: fraction must have unit denominator
sage: L(s) in R
False
sage: y = L(x)
sage: g = L(s)
sage: g.parent()
Univariate Polynomial Ring in x over Integer Ring localized at (x^2 + 1,)
sage: f = (y+5)/(y**2+1); f
(x + 5)/(x^2 + 1)
sage: f == g
True
sage: (y+5)/(y**2+2)
Traceback (most recent call last):
...
ValueError: factor x^2 + 2 of denominator is not a unit

sage: Lau.<u, v> = LaurentPolynomialRing(ZZ) #_
↳needs sage.modules
sage: LauL = Lau.localization(u + 1) #_
↳needs sage.modules
sage: LauL(~u).parent() #_
↳needs sage.modules
Multivariate Polynomial Ring in u, v over Integer Ring localized at (v, u, u + 1)

```

More examples will be shown typing `sage.rings.localization?`

Element

alias of *LocalizationElement*

characteristic()

Return the characteristic of self.

EXAMPLES:

```

sage: # needs sage.libs.pari
sage: R.<a> = GF(5)[]

```

(continues on next page)

(continued from previous page)

```
sage: L = R.localization((a**2 - 3, a))
sage: L.characteristic()
5
```

fraction_field()

Return the fraction field of self.

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: R.<a> = GF(5)[]
sage: L = Localization(R, (a**2 - 3, a))
sage: L.fraction_field()
Fraction Field of Univariate Polynomial Ring in a over Finite Field of size 5
sage: L.is_subring(_)
True
```

gen(i)Return the i -th generator of self which is the i -th generator of the base ring.

EXAMPLES:

```
sage: R.<x, y> = ZZ[]
sage: R.localization((x**2 + 1, y - 1)).gen(0) #_
↪needs sage.libs.pari
x
sage: ZZ.localization(2).gen(0)
1
```

gens()

Return a tuple whose entries are the generators for this object, in order.

EXAMPLES:

```
sage: R.<x, y> = ZZ[]
sage: Localization(R, (x**2 + 1, y - 1)).gens() #_
↪needs sage.libs.pari
(x, y)
sage: Localization(ZZ, 2).gens()
(1,)
```

is_field(proof=True)

Return True if this ring is a field.

INPUT:

- `proof` – (default: True) Determines what to do in unknown cases

ALGORITHM:

If the parameter `proof` is set to `True`, the returned value is correct but the method might throw an error. Otherwise, if it is set to `False`, the method returns `True` if it can establish that self is a field and `False` otherwise.

EXAMPLES:


```
sage: R = ZZ.localization((2, 3))
sage: R.is_field()
False
```

krull_dimension()

Return the Krull dimension of this localization.

Since the current implementation just allows integral domains as base ring and localization at a finite set of elements the spectrum of `self` is open in the irreducible spectrum of its base ring. Therefore, by density we may take the dimension from there.

EXAMPLES:

```
sage: R = ZZ.localization((2, 3))
sage: R.krull_dimension()
1
```

ngens()

Return the number of generators of `self` according to the same method for the base ring.

EXAMPLES:

```
sage: R.<x, y> = ZZ[]
sage: Localization(R, (x**2 + 1, y - 1)).ngens() #_
↪needs sage.libs.pari
2

sage: Localization(ZZ, 2).ngens()
1
```

class `sage.rings.localization.LocalizationElement` (*parent, x*)

Bases: `IntegralDomainElement`

Element class for localizations of integral domains

INPUT:

- `parent` – instance of `Localization`
- `x` – instance of `FractionFieldElement` whose parent is the fraction field of the parent's base ring

EXAMPLES:

```
sage: # needs sage.libs.pari
sage: from sage.rings.localization import LocalizationElement
sage: P.<x, y, z> = GF(5)[]
sage: L = P.localization((x, y*z - x))
sage: LocalizationElement(L, 4/(y*z-x)**2)
(-1)/(y^2*z^2 - 2*x*y*z + x^2)
sage: _.parent()
Multivariate Polynomial Ring in x, y, z over Finite Field of size 5
localized at (x, y*z - x)
```

denominator()

Return the denominator of `self`.

EXAMPLES:

```
sage: L = Localization(ZZ, (3,5))
sage: L(7/15).denominator()
15
```

factor (*proof=None*)

Return the factorization of this polynomial.

INPUT:

- *proof* – (optional) if given it is passed to the corresponding method of the numerator of *self*

EXAMPLES:

```
sage: P.<X, Y> = QQ['x, y']
sage: L = P.localization(X - Y)
sage: x, y = L.gens()
sage: p = (x^2 - y^2)/(x-y)^2 #_
↪needs sage.libs.singular
sage: p.factor() #_
↪needs sage.libs.singular
(1/(x - y)) * (x + y)
```

inverse_of_unit ()

Return the inverse of *self*.

EXAMPLES:

```
sage: P.<x, y, z> = ZZ[]
sage: L = Localization(P, x*y*z)
sage: L(x*y*z).inverse_of_unit() #_
↪needs sage.libs.singular
1/(x*y*z)
sage: L(z).inverse_of_unit() #_
↪needs sage.libs.singular
1/z
```

is_unit ()

Return True if *self* is a unit.

EXAMPLES:

```
sage: # needs sage.libs.pari sage.singular
sage: P.<x, y, z> = QQ[]
sage: L = P.localization((x, y*z))
sage: L(y*z).is_unit()
True
sage: L(z).is_unit()
True
sage: L(x*y*z).is_unit()
True
```

numerator ()

Return the numerator of *self*.

EXAMPLES:

```
sage: L = ZZ.localization((3,5))
sage: L(7/15).numerator()
7
```

`sage.rings.localization.normalize_extra_units` (*base_ring*, *add_units*, *warning=True*)

Function to normalize input data.

The given list will be replaced by a list of the involved prime factors (if possible).

INPUT:

- `base_ring` – an instance of *IntegralDomain*
- `add_units` – list of elements from base ring
- `warning` – (default: `True`) to suppress a warning which is thrown if no normalization was possible

OUTPUT:

List of all prime factors of the elements of the given list.

EXAMPLES:

```
sage: from sage.rings.localization import normalize_extra_units
sage: normalize_extra_units(ZZ, [3, -15, 45, 9, 2, 50])
[2, 3, 5]
sage: P.<x,y,z> = ZZ[]
sage: normalize_extra_units(P, #_
↳needs sage.libs.pari
.....: [3*x, z*y**2, 2*z, 18*(x*y*z)**2, x*z, 6*x*z, 5])
[2, 3, 5, z, y, x]
sage: P.<x,y,z> = QQ[]
sage: normalize_extra_units(P, #_
↳needs sage.libs.pari
.....: [3*x, z*y**2, 2*z, 18*(x*y*z)**2, x*z, 6*x*z, 5])
[z, y, x]

sage: # needs sage.libs.singular
sage: R.<x, y> = ZZ[]
sage: Q.<a, b> = R.quo(x**2 - 5)
sage: p = b**2 - 5
sage: p == (b-a)*(b+a)
True
sage: normalize_extra_units(Q, [p]) #_
↳needs sage.libs.pari
doctest:...: UserWarning: Localization may not be represented uniquely
[b^2 - 5]
sage: normalize_extra_units(Q, [p], warning=False) #_
↳needs sage.libs.pari
[b^2 - 5]
```


RING EXTENSIONS

7.1 Extension of rings

Sage offers the possibility to work with ring extensions L/K as actual parents and perform meaningful operations on them and their elements.

The simplest way to build an extension is to use the method `sage.categories.commutative_rings.CommutativeRings.ParentMethods.over()` on the top ring, that is L . For example, the following line constructs the extension of finite fields $\mathbf{F}_{5^4}/\mathbf{F}_{5^2}$:

```
sage: GF(5^4).over(GF(5^2)) #_
↳needs sage.rings.finite_rings
Field in z4 with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its base
```

By default, Sage reuses the canonical generator of the top ring (here $z_4 \in \mathbf{F}_{5^4}$), together with its name. However, the user can customize them by passing in appropriate arguments:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5^2)
sage: k = GF(5^4)
sage: z4 = k.gen()
sage: K.<a> = k.over(F, gen=1-z4); K
Field in a with defining polynomial x^2 + z2*x + 4 over its base
```

The base of the extension is available via the method `base()` (or equivalently `base_ring()`):

```
sage: K.base() #_
↳needs sage.rings.finite_rings
Finite Field in z2 of size 5^2
```

It is also possible to build an extension on top of another extension, obtaining this way a tower of extensions:

```
sage: L.<b> = GF(5^8).over(K); L #_
↳needs sage.rings.finite_rings
Field in b with defining polynomial x^2 + (4*z2 + 3*a)*x + 1 - a over its base
sage: L.base() #_
↳needs sage.rings.finite_rings
Field in a with defining polynomial x^2 + z2*x + 4 over its base
sage: L.base().base() #_
↳needs sage.rings.finite_rings
Finite Field in z2 of size 5^2
```

The method `bases()` gives access to the complete list of rings in a tower:

```
sage: L.bases() #_
↪needs sage.rings.finite_rings
[Field in b with defining polynomial x^2 + (4*z2 + 3*a)*x + 1 - a over its base,
Field in a with defining polynomial x^2 + z2*x + 4 over its base,
Finite Field in z2 of size 5^2]
```

Once we have constructed an extension (or a tower of extensions), we have interesting methods attached to it. As a basic example, one can compute a basis of the top ring over any base in the tower:

```
sage: L.basis_over(K) #_
↪needs sage.rings.finite_rings
[1, b]
sage: L.basis_over(F) #_
↪needs sage.rings.finite_rings
[1, a, b, a*b]
```

When the base is omitted, the default is the natural base of the extension:

```
sage: L.basis_over() #_
↪needs sage.rings.finite_rings
[1, b]
```

The method `sage.rings.ring_extension_element.RingExtensionWithBasis.vector()` computes the coordinates of an element according to the above basis:

```
sage: u = a + 2*b + 3*a*b #_
↪needs sage.rings.finite_rings
sage: u.vector() # over K #_
↪needs sage.rings.finite_rings
(a, 2 + 3*a)
sage: u.vector(F) #_
↪needs sage.rings.finite_rings
(0, 1, 2, 3)
```

One can also compute traces and norms with respect to any base of the tower:

```
sage: # needs sage.rings.finite_rings
sage: u.trace() # over K
(2*z2 + 1) + (2*z2 + 1)*a
sage: u.trace(F)
z2 + 1
sage: u.trace().trace() # over K, then over F
z2 + 1
sage: u.norm() # over K
(z2 + 1) + (4*z2 + 2)*a
sage: u.norm(F)
2*z2 + 2
```

And minimal polynomials:

```
sage: u.minpoly() #_
↪needs sage.rings.finite_rings
x^2 + ((3*z2 + 4) + (3*z2 + 4)*a)*x + (z2 + 1) + (4*z2 + 2)*a
sage: u.minpoly(F) #_
↪needs sage.rings.finite_rings
x^4 + (4*z2 + 4)*x^3 + x^2 + (z2 + 1)*x + 2*z2 + 2
```

AUTHOR:

- Xavier Caruso (2019)

class sage.rings.ring_extension.**RingExtensionFactory**

Bases: *UniqueFactory*

Factory for ring extensions.

create_key_and_extra_args (*ring, defining_morphism=None, gens=None, names=None, constructors=None*)

Create a key and return it together with a list of constructors of the object.

INPUT:

- *ring* – a commutative ring
- *defining_morphism* – a ring homomorphism or a commutative ring or *None* (default: *None*); the defining morphism of this extension or its base (if it coerces to *ring*)
- *gens* – a list of generators of this extension (over its base) or *None* (default: *None*);
- *names* – a list or a tuple of variable names or *None* (default: *None*)
- *constructors* – a list of constructors; each constructor is a pair (*class, arguments*) where *class* is the class implementing the extension and *arguments* is the dictionary of arguments to pass in to init function

create_object (*version, key, **extra_args*)

Return the object associated to a given key.

class sage.rings.ring_extension.**RingExtensionFractionField**

Bases: *RingExtension_generic*

A class for ring extensions of the form $\text{extrm{Frac}}(A)/A$.

Element

alias of *RingExtensionFractionFieldElement*

ring()

Return the ring whose fraction field is this extension.

EXAMPLES:

```
sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: A.<a> = ZZ.extension(x^2 - 2)
sage: OK = A.over()
sage: K = OK.fraction_field(); K
Fraction Field of
Maximal Order generated by a in Number Field in a with defining polynomial x^
↪2 - 2 over its base
sage: K.ring()
Maximal Order generated by a in Number Field in a with defining polynomial x^
↪2 - 2 over its base
sage: K.ring() is OK
True
```

class sage.rings.ring_extension.**RingExtensionWithBasis**

Bases: *RingExtension_generic*

A class for finite free ring extensions equipped with a basis.

Element

alias of `RingExtensionWithBasisElement`

basis_over (*base=None*)

Return a basis of this extension over base.

INPUT:

- base – a commutative ring (which might be itself an extension)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F.<a> = GF(5^2).over() # over GF(5)
sage: K.<b> = GF(5^4).over(F)
sage: L.<c> = GF(5^12).over(K)
sage: L.basis_over(K)
[1, c, c^2]
sage: L.basis_over(F)
[1, b, c, b*c, c^2, b*c^2]
sage: L.basis_over(GF(5))
[1, a, b, a*b, c, a*c, b*c, a*b*c, c^2, a*c^2, b*c^2, a*b*c^2]
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: L.basis_over() #_
↪needs sage.rings.finite_rings
[1, c, c^2]

sage: K.basis_over() #_
↪needs sage.rings.finite_rings
[1, b]
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: L.degree_over(GF(5^6)) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z6 of size 5^6
```

fraction_field (*extend_base=False*)

Return the fraction field of this extension.

INPUT:

- extend_base – a boolean (default: False);

If `extend_base` is False, the fraction field of the extension L/K is defined as $\text{Frac}(L)/L/K$, except if L is already a field in which case the fraction field of L/K is L/K itself.

If `extend_base` is True, the fraction field of the extension L/K is defined as $\text{Frac}(L)/\text{Frac}(K)$ (provided that the defining morphism extends to the fraction fields, i.e. is injective).

EXAMPLES:

```
sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: A.<a> = ZZ.extension(x^2 - 5)
```

(continues on next page)

(continued from previous page)

```

sage: OK = A.over() # over ZZ
sage: OK
Order of conductor 2 generated by a in Number Field in a with defining_
↳polynomial x^2 - 5 over its base
sage: K1 = OK.fraction_field(); K1
Fraction Field of Order of conductor 2 generated by a in Number Field in a
with defining polynomial x^2 - 5 over its base
sage: K1.bases()
[Fraction Field of Order of conductor 2 generated by a in Number Field in a
with defining polynomial x^2 - 5 over its base,
Order of conductor 2 generated by a in Number Field in a
with defining polynomial x^2 - 5 over its base,
Integer Ring]
sage: K2 = OK.fraction_field(extend_base=True); K2
Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base
sage: K2.bases()
[Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base,
Rational Field]

```

Note that there is no coercion map between K_1 and K_2 :

```

sage: K1.has_coerce_map_from(K2) #_
↳needs sage.rings.number_field
False
sage: K2.has_coerce_map_from(K1) #_
↳needs sage.rings.number_field
False

```

We check that when the extension is a field, its fraction field does not change:

```

sage: K1.fraction_field() is K1 #_
↳needs sage.rings.number_field
True
sage: K2.fraction_field() is K2 #_
↳needs sage.rings.number_field
True

```

free_module (*base=None, map=True*)

Return a free module V over *base* which is isomorphic to this ring

INPUT:

- *base* – a commutative ring (which might be itself an extension) or `None` (default: `None`)
- *map* – boolean (default `True`); whether to return isomorphisms between this ring and V

OUTPUT:

- A finite-rank free module V over *base*
- The isomorphism from V to this ring corresponding to the basis output by the method `basis_over()` (only included if *map* is `True`)
- The reverse isomorphism of the isomorphism above (only included if *map* is `True`)

EXAMPLES:

```
sage: F = GF(11)
sage: K.<a> = GF(11^2).over() #_
↪needs sage.rings.finite_rings
sage: L.<b> = GF(11^6).over(K) #_
↪needs sage.rings.finite_rings
```

Forgetting a part of the multiplicative structure, the field L can be viewed as a vector space of dimension 3 over K , equipped with a distinguished basis, namely $(1, b, b^2)$:

```
sage: # needs sage.rings.finite_rings
sage: V, i, j = L.free_module(K)
sage: V
Vector space of dimension 3 over
Field in a with defining polynomial x^2 + 7*x + 2 over its base
sage: i
Generic map:
  From: Vector space of dimension 3 over
        Field in a with defining polynomial x^2 + 7*x + 2 over its base
  To:   Field in b with defining polynomial
        x^3 + (7 + 2*a)*x^2 + (2 - a)*x - a over its base
sage: j
Generic map:
  From: Field in b with defining polynomial
        x^3 + (7 + 2*a)*x^2 + (2 - a)*x - a over its base
  To:   Vector space of dimension 3 over
        Field in a with defining polynomial x^2 + 7*x + 2 over its base
sage: j(b)
(0, 1, 0)
sage: i((1, a, a+1))
1 + a*b + (1 + a)*b^2
```

Similarly, one can view L as a F -vector space of dimension 6:

```
sage: V, i, j, = L.free_module(F) #_
↪needs sage.rings.finite_rings
sage: V #_
↪needs sage.rings.finite_rings
Vector space of dimension 6 over Finite Field of size 11
```

In this case, the isomorphisms between V and L are given by the basis $(1, a, b, ab, b^2, ab^2)$:

```
sage: j(a*b) # needs sage.rings.finite_rings (0, 0, 0, 1, 0, 0)
sage: i((1,2,3,4,5,6)) # needs sage.rings.finite_rings
(1 + 2*a) + (3 + 4*a)*b + (5 + 6*a)*b^2
```

When base is omitted, the default is the base of this extension:

```
sage: L.free_module(map=False) #_
↪needs sage.rings.finite_rings
Vector space of dimension 3 over
Field in a with defining polynomial x^2 + 7*x + 2 over its base
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: L.degree(GF(11^3)) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: not (explicitly) defined over Finite Field in z3 of size 11^3
```

class sage.rings.ring_extension.**RingExtensionWithGen**

Bases: *RingExtensionWithBasis*

A class for finite free ring extensions generated by a single element

fraction_field (*extend_base=False*)

Return the fraction field of this extension.

INPUT:

- *extend_base* – a boolean (default: False);

If *extend_base* is False, the fraction field of the extension L/K is defined as $\text{Frac}(L)/L/K$, except if L is already a field in which base the fraction field of L/K is L/K itself.

If *extend_base* is True, the fraction field of the extension L/K is defined as $\text{Frac}(L)/\text{Frac}(K)$ (provided that the defining morphism extends to the fraction fields, i.e. is injective).

EXAMPLES:

```
sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: A.<a> = ZZ.extension(x^2 - 5)
sage: OK = A.over() # over ZZ
sage: OK
Order of conductor 2 generated by a in Number Field in a
with defining polynomial x^2 - 5 over its base
sage: K1 = OK.fraction_field(); K1
Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base
sage: K1.bases()
[Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base,
Order of conductor 2 generated by a in Number Field in a
with defining polynomial x^2 - 5 over its base,
Integer Ring]
sage: K2 = OK.fraction_field(extend_base=True); K2
Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base
sage: K2.bases()
[Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base,
Rational Field]
```

Note that there is no coercion map between K_1 and K_2 :

```
sage: K1.has_coerce_map_from(K2) #_
↪needs sage.rings.number_field
False
sage: K2.has_coerce_map_from(K1) #_
↪needs sage.rings.number_field
False
```

We check that when the extension is a field, its fraction field does not change:

```
sage: K1.fraction_field() is K1 #_
↪needs sage.rings.number_field
True
sage: K2.fraction_field() is K2 #_
↪needs sage.rings.number_field
True
```

gens (*base=None*)

Return the generators of this extension over base.

INPUT:

- base – a commutative ring (which might be itself an extension) or None (default: None)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K.<a> = GF(5^2).over() # over GF(5)
sage: K.gens()
(a,)
sage: L.<b> = GF(5^4).over(K)
sage: L.gens()
(b,)
sage: L.gens(GF(5))
(b, a)
```

modulus (*var='x'*)

Return the defining polynomial of this extension, that is the minimal polynomial of the given generator of this extension.

INPUT:

- var – a variable name (default: x)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K.<u> = GF(7^10).over(GF(7^2)); K
Field in u with defining polynomial x^5 + (6*z2 + 4)*x^4
+ (3*z2 + 5)*x^3 + (2*z2 + 2)*x^2 + 4*x + 6*z2 over its base
sage: P = K.modulus(); P
x^5 + (6*z2 + 4)*x^4 + (3*z2 + 5)*x^3 + (2*z2 + 2)*x^2 + 4*x + 6*z2
sage: P(u)
0
```

We can use a different variable name:

```
sage: K.modulus('y') #_
↪needs sage.rings.finite_rings
y^5 + (6*z2 + 4)*y^4 + (3*z2 + 5)*y^3 + (2*z2 + 2)*y^2 + 4*y + 6*z2
```

class sage.rings.ring_extension.**RingExtension_generic**

Bases: *CommutativeRing*

A generic class for all ring extensions.

Element

alias of *RingExtensionElement*

absolute_base()

Return the absolute base of this extension.

By definition, the absolute base of an iterated extension $K_n/\cdots K_2/K_1$ is the ring K_1 .

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5^2).over() # over GF(5)
sage: K = GF(5^4).over(F)
sage: L = GF(5^12).over(K)
sage: F.absolute_base()
Finite Field of size 5
sage: K.absolute_base()
Finite Field of size 5
sage: L.absolute_base()
Finite Field of size 5
```

See also:

base(), *bases()*, *is_defined_over()*

absolute_degree()

Return the degree of this extension over its absolute base

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: A = GF(5^4).over(GF(5^2))
sage: B = GF(5^12).over(A)
sage: A.absolute_degree()
2
sage: B.absolute_degree()
6
```

See also:

degree(), *relative_degree()*

backend(force=False)

Return the backend of this extension.

INPUT:

- *force* – a boolean (default: False); if False, raise an error if the backend is not exposed

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K = GF(5^3)
sage: E = K.over()
sage: E
Field in z3 with defining polynomial x^3 + 3*x + 3 over its base
sage: E.backend()
Finite Field in z3 of size 5^3
sage: E.backend() is K
True
```

base()

Return the base of this extension.

EXAMPLES:

```

sage: F = GF(5^2) #_
↪needs sage.rings.finite_rings
sage: K = GF(5^4).over(F) #_
↪needs sage.rings.finite_rings
sage: K.base() #_
↪needs sage.rings.finite_rings
Finite Field in z2 of size 5^2

```

In case of iterated extensions, the base is itself an extension:

```

sage: L = GF(5^8).over(K) #_
↪needs sage.rings.finite_rings
sage: L.base() #_
↪needs sage.rings.finite_rings
Field in z4 with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its base
sage: L.base() is K #_
↪needs sage.rings.finite_rings
True

```

See also:

bases(), *absolute_base()*, *is_defined_over()*

bases()

Return the list of successive bases of this extension (including itself).

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: F = GF(5^2).over() # over GF(5)
sage: K = GF(5^4).over(F)
sage: L = GF(5^12).over(K)
sage: F.bases()
[Field in z2 with defining polynomial x^2 + 4*x + 2 over its base,
 Finite Field of size 5]
sage: K.bases()
[Field in z4 with defining polynomial x^2 + (3 - z2)*x + z2 over its base,
 Field in z2 with defining polynomial x^2 + 4*x + 2 over its base,
 Finite Field of size 5]
sage: L.bases()
[Field in z12 with defining polynomial
 x^3 + (1 + (2 - z2)*z4)*x^2 + (2 + 2*z4)*x - z4 over its base,
 Field in z4 with defining polynomial x^2 + (3 - z2)*x + z2 over its base,
 Field in z2 with defining polynomial x^2 + 4*x + 2 over its base,
 Finite Field of size 5]

```

See also:

base(), *absolute_base()*, *is_defined_over()*

characteristic()

Return the characteristic of the extension as a ring.

OUTPUT:

A prime number or zero.

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: F = GF(5^2).over() # over GF(5)
sage: K = GF(5^4).over(F)
sage: L = GF(5^12).over(K)
sage: F.characteristic()
5
sage: K.characteristic()
5
sage: L.characteristic()
5

```

```

sage: F = RR.over(ZZ)
sage: F.characteristic()
0

```

```

sage: F = GF(11)
sage: A.<x> = F[]
sage: K = Frac(F).over(F)
sage: K.characteristic()
11

```

```

sage: E = GF(7).over(ZZ)
sage: E.characteristic()
7

```

construction()

Return the functorial construction of this extension, if defined.

EXAMPLES:

```

sage: E = GF(5^3).over() #_
↪needs sage.rings.finite_rings
sage: E.construction() #_
↪needs sage.rings.finite_rings

```

defining_morphism (*base=None*)

Return the defining morphism of this extension over base.

INPUT:

- *base* – a commutative ring (which might be itself an extension) or None (default: None)

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: F = GF(5^2)
sage: K = GF(5^4).over(F)
sage: L = GF(5^12).over(K)
sage: K.defining_morphism()
Ring morphism:
  From: Finite Field in z2 of size 5^2
  To:   Field in z4 with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its_
↪base
  Defn: z2 |--> z2
sage: L.defining_morphism()
Ring morphism:
  From: Field in z4 with defining polynomial x^2 + (4*z2 + 3)*x + z2 over its_

```

(continues on next page)

(continued from previous page)

```
↪base
To: Field in z12 with defining polynomial
    x^3 + (1 + (4*z2 + 2)*z4)*x^2 + (2 + 2*z4)*x - z4 over its base
Defn: z4 |--> z4
```

One can also pass in a base over which the extension is explicitly defined (see also `is_defined_over()`):

```
sage: L.defining_morphism(F) #_
↪needs sage.rings.finite_rings
Ring morphism:
  From: Finite Field in z2 of size 5^2
  To:   Field in z12 with defining polynomial
        x^3 + (1 + (4*z2 + 2)*z4)*x^2 + (2 + 2*z4)*x - z4 over its base
  Defn: z2 |--> z2
sage: L.defining_morphism(GF(5)) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field of size 5
```

degree (base)

Return the degree of this extension over base.

INPUT:

- base – a commutative ring (which might be itself an extension)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: A = GF(5^4).over(GF(5^2))
sage: B = GF(5^12).over(A)
sage: A.degree(GF(5^2))
2
sage: B.degree(A)
3
sage: B.degree(GF(5^2))
6
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: A.degree(GF(5)) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field of size 5
```

See also:

`relative_degree()`, `absolute_degree()`

degree_over (base=None)

Return the degree of this extension over base.

INPUT:

- base – a commutative ring (which might be itself an extension) or None (default: None)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5^2)
sage: K = GF(5^4).over(F)
sage: L = GF(5^12).over(K)
sage: K.degree_over(F)
2
sage: L.degree_over(K)
3
sage: L.degree_over(F)
6
```

If base is omitted, the degree is computed over the base of the extension:

```
sage: K.degree_over() #_
↪needs sage.rings.finite_rings
2
sage: L.degree_over() #_
↪needs sage.rings.finite_rings
3
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: K.degree_over(GF(5)) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field of size 5
```

`fraction_field` (*extend_base=False*)

Return the fraction field of this extension.

INPUT:

- `extend_base` – a boolean (default: `False`);

If `extend_base` is `False`, the fraction field of the extension L/K is defined as $\text{Frac}(L)/L/K$, except if L is already a field in which base the fraction field of L/K is L/K itself.

If `extend_base` is `True`, the fraction field of the extension L/K is defined as $\text{Frac}(L)/\text{Frac}(K)$ (provided that the defining morphism extends to the fraction fields, i.e. is injective).

EXAMPLES:

```
sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: A.<a> = ZZ.extension(x^2 - 5)
sage: OK = A.over() # over ZZ
sage: OK
Order of conductor 2 generated by a in Number Field in a
with defining polynomial x^2 - 5 over its base
sage: K1 = OK.fraction_field(); K1
Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base
sage: K1.bases()
[Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base,
```

(continues on next page)

(continued from previous page)

```

Order of conductor 2 generated by a in Number Field in a
with defining polynomial x^2 - 5 over its base,
Integer Ring]
sage: K2 = OK.fraction_field(extend_base=True); K2
Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base
sage: K2.bases()
[Fraction Field of Order of conductor 2 generated by a
in Number Field in a with defining polynomial x^2 - 5 over its base,
Rational Field]

```

Note that there is no coercion between K_1 and K_2 :

```

sage: K1.has_coerce_map_from(K2) #_
↪needs sage.rings.number_field
False
sage: K2.has_coerce_map_from(K1) #_
↪needs sage.rings.number_field
False

```

We check that when the extension is a field, its fraction field does not change:

```

sage: K1.fraction_field() is K1 #_
↪needs sage.rings.number_field
True
sage: K2.fraction_field() is K2 #_
↪needs sage.rings.number_field
True

```

from_base_ring(r)

Return the canonical embedding of r into this extension.

INPUT:

- r – an element of the base of the ring of this extension

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: k = GF(5)
sage: K.<u> = GF(5^2).over(k)
sage: L.<v> = GF(5^4).over(K)
sage: x = L.from_base_ring(k(2)); x
2
sage: x.parent()
Field in v with defining polynomial x^2 + (3 - u)*x + u over its base
sage: x = L.from_base_ring(u); x
u
sage: x.parent()
Field in v with defining polynomial x^2 + (3 - u)*x + u over its base

```

gen()

Return the first generator of this extension.

EXAMPLES:

```

sage: K = GF(5^2).over() # over GF(5) #_
↪needs sage.rings.finite_rings
sage: x = K.gen(); x #_
↪needs sage.rings.finite_rings
z2

```

Observe that the generator lives in the extension:

```

sage: x.parent() #_
↪needs sage.rings.finite_rings
Field in z2 with defining polynomial x^2 + 4*x + 2 over its base
sage: x.parent() is K #_
↪needs sage.rings.finite_rings
True

```

gens (*base=None*)

Return the generators of this extension over base.

INPUT:

- *base* – a commutative ring (which might be itself an extension) or *None* (default: *None*); if omitted, use the base of this extension

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: K.<a> = GF(5^2).over() # over GF(5)
sage: K.gens()
(a,)
sage: L.<b> = GF(5^4).over(K)
sage: L.gens()
(b,)
sage: L.gens(GF(5))
(b, a)

sage: S.<x> = QQ[]
sage: T.<y> = S[]
sage: T.over(S).gens()
(y,)
sage: T.over(QQ).gens()
(y, x)

```

hom (*im_gens*, *codomain=None*, *base_map=None*, *category=None*, *check=True*)

Return the unique homomorphism from this extension to *codomain* that sends `self.gens()` to the entries of *im_gens* and induces the map *base_map* on the base ring.

INPUT:

- *im_gens* – the images of the generators of this extension
- *codomain* – the codomain of the homomorphism; if omitted, it is set to the smallest parent containing all the entries of *im_gens*
- *base_map* – a map from one of the bases of this extension into something that coerces into the codomain; if omitted, coercion maps are used
- *category* – the category of the resulting morphism
- *check* – a boolean (default: *True*); whether to verify that the images of generators extend to define a map (using only canonical coercions)

EXAMPLES:

```
sage: K.<a> = GF(5^2).over() # over GF(5) #_
↪needs sage.rings.finite_rings
sage: L.<b> = GF(5^6).over(K) #_
↪needs sage.rings.finite_rings
```

We define (by hand) the relative Frobenius endomorphism of the extension L/K :

```
sage: L.hom([b^25]) #_
↪needs sage.rings.finite_rings
Ring endomorphism of
Field in b with defining polynomial x^3 + (2 + 2*a)*x - a over its base
Defn: b |--> 2 + 2*a*b + (2 - a)*b^2
```

Defining the absolute Frobenius of L is a bit more complicated because it is not a homomorphism of K -algebras. For this reason, the construction `L.hom([b^5])` fails:

```
sage: L.hom([b^5]) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: images do not define a valid homomorphism
```

What we need is to specify a base map:

```
sage: FrobK = K.hom([a^5]) #_
↪needs sage.rings.finite_rings
sage: FrobL = L.hom([b^5], base_map=FrobK); FrobL #_
↪needs sage.rings.finite_rings
Ring endomorphism of
Field in b with defining polynomial x^3 + (2 + 2*a)*x - a over its base
Defn: b |--> (-1 + a) + (1 + 2*a)*b + a*b^2
with map on base ring:
a |--> 1 - a
```

As a shortcut, we may use the following construction:

```
sage: phi = L.hom([b^5, a^5]); phi #_
↪needs sage.rings.finite_rings
Ring endomorphism of
Field in b with defining polynomial x^3 + (2 + 2*a)*x - a over its base
Defn: b |--> (-1 + a) + (1 + 2*a)*b + a*b^2
with map on base ring:
a |--> 1 - a
sage: phi == FrobL #_
↪needs sage.rings.finite_rings
True
```

is_defined_over (*base*)

Return whether or not *base* is one of the bases of this extension.

INPUT:

- *base* – a commutative ring, which might be itself an extension

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: A = GF(5^4).over(GF(5^2))
sage: B = GF(5^12).over(A)
sage: A.is_defined_over(GF(5^2))
True
sage: A.is_defined_over(GF(5))
False

sage: # needs sage.rings.finite_rings
sage: B.is_defined_over(A)
True
sage: B.is_defined_over(GF(5^4))
True
sage: B.is_defined_over(GF(5^2))
True
sage: B.is_defined_over(GF(5))
False

```

Note that an extension is defined over itself:

```

sage: A.is_defined_over(A) #_
↪needs sage.rings.finite_rings
True
sage: A.is_defined_over(GF(5^4)) #_
↪needs sage.rings.finite_rings
True

```

See also:

`base()`, `bases()`, `absolute_base()`

is_field (*proof=True*)

Return whether or not this extension is a field.

INPUT:

- `proof` – a boolean (default: `False`)

EXAMPLES:

```

sage: K = GF(5^5).over() # over GF(5) #_
↪needs sage.rings.finite_rings
sage: K.is_field() #_
↪needs sage.rings.finite_rings
True

sage: S.<x> = QQ[]
sage: A = S.over(QQ)
sage: A.is_field()
False

sage: B = A.fraction_field()
sage: B.is_field()
True

```

is_finite_over (*base=None*)

Return whether or not this extension is finite over `base` (as a module).

INPUT:

- base – a commutative ring (which might be itself an extension) or None (default: None)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K = GF(5^2).over() # over GF(5)
sage: L = GF(5^4).over(K)
sage: L.is_finite_over(K)
True
sage: L.is_finite_over(GF(5))
True
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: L.is_finite_over() #_
↪needs sage.rings.finite_rings
True
```

is_free_over (*base=None*)

Return True if this extension is free (as a module) over base

INPUT:

- base – a commutative ring (which might be itself an extension) or None (default: None)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K = GF(5^2).over() # over GF(5)
sage: L = GF(5^4).over(K)
sage: L.is_free_over(K)
True
sage: L.is_free_over(GF(5))
True
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: L.is_free_over() #_
↪needs sage.rings.finite_rings
True
```

ngens (*base=None*)

Return the number of generators of this extension over base.

INPUT:

- base – a commutative ring (which might be itself an extension) or None (default: None)

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K = GF(5^2).over() # over GF(5)
sage: K.gens()
(z2,)
sage: K.ngens()
1
sage: L = GF(5^4).over(K)
sage: L.gens(GF(5))
(z4, z2)
```

(continues on next page)

(continued from previous page)

```
sage: L.ngens(GF(5))
2
```

print_options (**options)

Update the printing options of this extension.

INPUT:

- `over` – an integer or Infinity (default: 0); the maximum number of bases included in the printing of this extension
- `base` – a base over which this extension is finite free; elements in this extension will be printed as a linear combination of a basis of this extension over the given base

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: A.<a> = GF(5^2).over() # over GF(5)
sage: B.<b> = GF(5^4).over(A)
sage: C.<c> = GF(5^12).over(B)
sage: D.<d> = GF(5^24).over(C)
```

Observe what happens when we modify the option `over`:

```
sage: # needs sage.rings.finite_rings
sage: D
Field in d with defining polynomial
x^2 + ((1 - a) + ((1 + 2*a) - b)*c + ((2 + a) + (1 - a)*b)*c^2)*x + c over
↳ its base
sage: D.print_options(over=2)
sage: D
Field in d with defining polynomial x^2 + ((1 - a) + ((1 + 2*a) - b)*c + ((2
↳ + a) + (1 - a)*b)*c^2)*x + c over
Field in c with defining polynomial x^3 + (1 + (2 - a)*b)*x^2 + (2 + 2*b)*x
↳ b over
Field in b with defining polynomial x^2 + (3 - a)*x + a over its base
sage: D.print_options(over=Infinity)
sage: D
Field in d with defining polynomial x^2 + ((1 - a) + ((1 + 2*a) - b)*c + ((2
↳ + a) + (1 - a)*b)*c^2)*x + c over
Field in c with defining polynomial x^3 + (1 + (2 - a)*b)*x^2 + (2 + 2*b)*x
↳ b over
Field in b with defining polynomial x^2 + (3 - a)*x + a over
Field in a with defining polynomial x^2 + 4*x + 2 over
Finite Field of size 5
```

Now the option `base`:

```
sage: # needs sage.rings.finite_rings
sage: d^2
-c + ((-1 + a) + ((-1 + 3*a) + b)*c + ((3 - a) + (-1 + a)*b)*c^2)*d
sage: D.basis_over(B)
[1, c, c^2, d, c*d, c^2*d]
sage: D.print_options(base=B)
sage: d^2
-c + (-1 + a)*d + ((-1 + 3*a) + b)*c*d + ((3 - a) + (-1 + a)*b)*c^2*d
sage: D.basis_over(A)
```

(continues on next page)

(continued from previous page)

```
[1, b, c, b*c, c^2, b*c^2, d, b*d, c*d, b*c*d, c^2*d, b*c^2*d]
sage: D.print_options(base=A)
sage: d^2
-c + (-1 + a)*d + (-1 + 3*a)*c*d + b*c*d + (3 - a)*c^2*d + (-1 + a)*b*c^2*d
```

random_element()

Return a random element in this extension.

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K = GF(5^2).over() # over GF(5)
sage: x = K.random_element(); x # random
3 + z2
sage: x.parent()
Field in z2 with defining polynomial x^2 + 4*x + 2 over its base
sage: x.parent() is K
True
```

relative_degree()

Return the degree of this extension over its base

EXAMPLES:

```
sage: A = GF(5^4).over(GF(5^2)) #_
↪needs sage.rings.finite_rings
sage: A.relative_degree() #_
↪needs sage.rings.finite_rings
2
```

See also:

degree(), *absolute_degree()*

sage.rings.ring_extension.**common_base**(*K*, *L*, *degree*)

Return a common base on which *K* and *L* are defined.

INPUT:

- *K* – a commutative ring
- *L* – a commutative ring
- *degree* – a boolean; if true, return the degree of *K* and *L* over their common base

EXAMPLES:

```
sage: from sage.rings.ring_extension import common_base

sage: common_base(GF(5^3), GF(5^7), False) #_
↪needs sage.rings.finite_rings
Finite Field of size 5
sage: common_base(GF(5^3), GF(5^7), True) #_
↪needs sage.rings.finite_rings
(Finite Field of size 5, 3, 7)

sage: common_base(GF(5^3), GF(7^5), False) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
NotImplementedError: unable to find a common base
```

When degree is set to True, we only look up for bases on which both K and L are finite:

```
sage: S.<x> = QQ[]
sage: common_base(S, QQ, False)
Rational Field
sage: common_base(S, QQ, True)
Traceback (most recent call last):
...
NotImplementedError: unable to find a common base
```

`sage.rings.ring_extension.generators` (*ring*, *base*)

Return the generators of *ring* over *base*.

INPUT:

- *ring* – a commutative ring
- *base* – a commutative ring

EXAMPLES:

```
sage: from sage.rings.ring_extension import generators
sage: S.<x> = QQ[]
sage: T.<y> = S[]

sage: generators(T, S)
(y,)
sage: generators(T, QQ)
(y, x)
```

`sage.rings.ring_extension.tower_bases` (*ring*, *degree*)

Return the list of bases of *ring* (including itself); if *degree* is True, restrict to finite extensions and return in addition the degree of *ring* over each base.

INPUT:

- *ring* – a commutative ring
- *degree* – a boolean

EXAMPLES:

```
sage: from sage.rings.ring_extension import tower_bases
sage: S.<x> = QQ[]
sage: T.<y> = S[]
sage: tower_bases(T, False)
([Univariate Polynomial Ring in y over
  Univariate Polynomial Ring in x over Rational Field,
  Univariate Polynomial Ring in x over Rational Field,
  Rational Field],
 [])
sage: tower_bases(T, True)
([Univariate Polynomial Ring in y over
  Univariate Polynomial Ring in x over Rational Field],
 [1])
```

(continues on next page)

(continued from previous page)

```
sage: K.<a> = Qq(5^2) #_
↳needs sage.rings.padics
sage: L.<w> = K.extension(x^3 - 5) #_
↳needs sage.rings.padics
sage: tower_bases(L, True) #_
↳needs sage.rings.padics
([5-adic Eisenstein Extension Field in w defined by x^3 - 5 over its base field,
 5-adic Unramified Extension Field in a defined by x^2 + 4*x + 2,
 5-adic Field with capped relative precision 20],
 [1, 3, 6])
```

`sage.rings.ring_extension.variable_names` (*ring*, *base*)

Return the variable names of the generators of ring over base.

INPUT:

- ring – a commutative ring
- base – a commutative ring

EXAMPLES:

```
sage: from sage.rings.ring_extension import variable_names
sage: S.<x> = QQ[]
sage: T.<y> = S[]

sage: variable_names(T, S)
('y',)
sage: variable_names(T, QQ)
('y', 'x')
```

7.2 Elements lying in extension of rings

AUTHOR:

- Xavier Caruso (2019)

class `sage.rings.ring_extension_element.RingExtensionElement`

Bases: `CommutativeAlgebraElement`

Generic class for elements lying in ring extensions.

additive_order ()

Return the additive order of this element.

EXAMPLES:

```
sage: K.<a> = GF(5^4).over(GF(5^2)) #_
↳needs sage.rings.finite_rings
sage: a.additive_order() #_
↳needs sage.rings.finite_rings
5
```

backend (*force=False*)

Return the backend of this element.

INPUT:

- `force` – a boolean (default: `False`); if `False`, raise an error if the backend is not exposed

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5^2)
sage: K.<z> = GF(5^4).over(F)
sage: x = z^10
sage: x
(z^2 + 2) + (3*z^2 + 1)*z
sage: y = x.backend()
sage: y
4*z^4^3 + 2*z^4^2 + 4*z^4 + 4
sage: y.parent()
Finite Field in z4 of size 5^4
```

`in_base()`

Return this element as an element of the base.

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5^2)
sage: K.<z> = GF(5^4).over(F)
sage: x = z^3 + z^2 + z + 4
sage: y = x.in_base()
sage: y
z^2 + 1
sage: y.parent()
Finite Field in z2 of size 5^2
```

When the element is not in the base, an error is raised:

```
sage: z.in_base()
↳needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: z is not in the base
```

```
sage: # needs sage.rings.finite_rings
sage: S.<X> = F[]
sage: E = S.over(F)
sage: f = E(1)
sage: g = f.in_base(); g
1
sage: g.parent()
Finite Field in z2 of size 5^2
```

`is_nilpotent()`

Return whether if this element is nilpotent in this ring.

EXAMPLES:

```
sage: A.<x> = PolynomialRing(QQ)
sage: E = A.over(QQ)
sage: E(0).is_nilpotent()
True
sage: E(x).is_nilpotent()
False
```

is_prime()

Return whether this element is a prime element in this ring.

EXAMPLES:

```
sage: A.<x> = PolynomialRing(QQ)
sage: E = A.over(QQ)
sage: E(x^2 + 1).is_prime() #_
↳needs sage.libs.pari
True
sage: E(x^2 - 1).is_prime() #_
↳needs sage.libs.pari
False
```

is_square (root=False)

Return whether this element is a square in this ring.

INPUT:

- root – a boolean (default: False); if True, return also a square root

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K.<a> = GF(5^3).over()
sage: a.is_square()
False
sage: a.is_square(root=True)
(False, None)
sage: b = a + 1
sage: b.is_square()
True
sage: b.is_square(root=True)
(True, 2 + 3*a + a^2)
```

is_unit()

Return whether if this element is a unit in this ring.

EXAMPLES:

```
sage: A.<x> = PolynomialRing(QQ)
sage: E = A.over(QQ)
sage: E(4).is_unit()
True
sage: E(x).is_unit()
False
```

multiplicative_order()

Return the multiplicity order of this element.

EXAMPLES:

```
sage: K.<a> = GF(5^4).over(GF(5^2)) #_
↳needs sage.rings.finite_rings
sage: a.multiplicative_order() #_
↳needs sage.rings.finite_rings
624
```

sqrt (*extend=True, all=False, name=None*)

Return a square root or all square roots of this element.

INPUT:

- *extend* – a boolean (default: `True`); if “True”, return a square root in an extension ring, if necessary. Otherwise, raise a `ValueError` if the root is not in the ring
- *all* – a boolean (default: `False`); if `True`, return all square roots of this element, instead of just one.
- *name* – Required when *extend=True* and *self* is not a square. This will be the name of the generator extension.

Note: The option `extend=True` is often not implemented.

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K.<a> = GF(5^3).over()
sage: b = a + 1
sage: b.sqrt()
2 + 3*a + a^2
sage: b.sqrt(all=True)
[2 + 3*a + a^2, 3 + 2*a - a^2]
```

class `sage.rings.ring_extension_element.RingExtensionFractionFieldElement`

Bases: `RingExtensionElement`

A class for elements lying in fraction fields of ring extensions.

denominator ()

Return the denominator of this element.

EXAMPLES:

```
sage: # needs sage.rings.number_field
sage: R.<x> = ZZ[]
sage: A.<a> = ZZ.extension(x^2 - 2)
sage: OK = A.over() # over ZZ
sage: K = OK.fraction_field(); K
Fraction Field of
Maximal Order generated by a in Number Field in a
with defining polynomial x^2 - 2 over its base
sage: x = K(1/a); x
a/2
sage: denom = x.denominator(); denom
2
```

The denominator is an element of the ring which was used to construct the fraction field:

```
sage: denom.parent() #_
↪needs sage.rings.number_field
Maximal Order generated by a in Number Field in a with defining polynomial x^
↪2 - 2 over its base
sage: denom.parent() is OK #_
↪needs sage.rings.number_field
True
```

numerator()

Return the numerator of this element.

EXAMPLES:

```
sage: # needs sage.rings.number_field
sage: x = polygen(ZZ, 'x')
sage: A.<a> = ZZ.extension(x^2 - 2)
sage: OK = A.over() # over ZZ
sage: K = OK.fraction_field(); K
Fraction Field of Maximal Order generated by a in Number Field in a
with defining polynomial x^2 - 2 over its base
sage: x = K(1/a); x
a/2
sage: num = x.numerator(); num
a
```

The numerator is an element of the ring which was used to construct the fraction field:

```
sage: num.parent() #_
↪needs sage.rings.number_field
Maximal Order generated by a in Number Field in a
with defining polynomial x^2 - 2 over its base
sage: num.parent() is OK #_
↪needs sage.rings.number_field
True
```

class sage.rings.ring_extension_element.**RingExtensionWithBasisElement**

Bases: *RingExtensionElement*

A class for elements lying in finite free extensions.

charpoly (*base=None, var='x'*)

Return the characteristic polynomial of this element over base.

INPUT:

- base – a commutative ring (which might be itself an extension) or None

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5)
sage: K.<a> = GF(5^3).over(F)
sage: L.<b> = GF(5^6).over(K)
sage: u = a/(1+b)
sage: chi = u.charpoly(K); chi
x^2 + (1 + 2*a + 3*a^2)*x + 3 + 2*a^2
```

We check that the charpoly has coefficients in the base ring:

```
sage: chi.base_ring() #_
↪needs sage.rings.finite_rings
Field in a with defining polynomial x^3 + 3*x + 3 over its base
sage: chi.base_ring() is K #_
↪needs sage.rings.finite_rings
True
```

and that it annihilates u:

```
sage: chi(u)
↪needs sage.rings.finite_rings
0
```

Similarly, one can compute the characteristic polynomial over F :

```
sage: u.charpoly(F)
↪needs sage.rings.finite_rings
x^6 + x^4 + 2*x^3 + 3*x + 4
```

A different variable name can be specified:

```
sage: u.charpoly(F, var='t')
↪needs sage.rings.finite_rings
t^6 + t^4 + 2*t^3 + 3*t + 4
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: u.charpoly()
↪needs sage.rings.finite_rings
x^2 + (1 + 2*a + 3*a^2)*x + 3 + 2*a^2
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: u.charpoly(GF(5^2))
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z2 of size 5^2
```

matrix (*base=None*)

Return the matrix of the multiplication by this element (in the basis output by `basis_over()`).

INPUT:

- `base` – a commutative ring (which might be itself an extension) or `None`

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K.<a> = GF(5^3).over() # over GF(5)
sage: L.<b> = GF(5^6).over(K)
sage: u = a/(1+b)
sage: u
(2 + a + 3*a^2) + (3 + 3*a + a^2)*b
sage: b*u
(3 + 2*a^2) + (2 + 2*a - a^2)*b
sage: u.matrix(K)
[2 + a + 3*a^2 3 + 3*a + a^2]
[ 3 + 2*a^2 2 + 2*a - a^2]
sage: u.matrix(GF(5))
[2 1 3 3 3 1]
[1 3 1 2 0 3]
[2 3 3 1 3 0]
[3 0 2 2 2 4]
[4 2 0 3 0 2]
[0 4 2 4 2 0]
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: u.matrix() #_
↪needs sage.rings.finite_rings
[2 + a + 3*a^2 3 + 3*a + a^2]
[ 3 + 2*a^2 2 + 2*a - a^2]
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method bases()):

```
sage: u.matrix(GF(5^2)) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z2 of size 5^2
```

minpoly (base=None, var='x')

Return the minimal polynomial of this element over base.

INPUT:

- base – a commutative ring (which might be itself an extension) or None

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5)
sage: K.<a> = GF(5^3).over(F)
sage: L.<b> = GF(5^6).over(K)
sage: u = 1 / (a+b)
sage: chi = u.minpoly(K); chi
x^2 + (2*a + a^2)*x - 1 + a
```

We check that the minimal polynomial has coefficients in the base ring:

```
sage: chi.base_ring() #_
↪needs sage.rings.finite_rings
Field in a with defining polynomial x^3 + 3*x + 3 over its base
sage: chi.base_ring() is K #_
↪needs sage.rings.finite_rings
True
```

and that it annihilates u:

```
sage: chi(u) #_
↪needs sage.rings.finite_rings
0
```

Similarly, one can compute the minimal polynomial over F:

```
sage: u.minpoly(F) #_
↪needs sage.rings.finite_rings
x^6 + 4*x^5 + x^4 + 2*x^2 + 3
```

A different variable name can be specified:

```
sage: u.minpoly(F, var='t') #_
↪needs sage.rings.finite_rings
t^6 + 4*t^5 + t^4 + 2*t^2 + 3
```


If base is omitted, it is set to its default which is the base of the extension:

```
sage: u.minpoly()
↪needs sage.rings.finite_rings
x^2 + (2*a + a^2)*x - 1 + a
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: u.minpoly(GF(5^2))
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z2 of size 5^2
```

norm (*base=None*)

Return the norm of this element over base.

INPUT:

- base – a commutative ring (which might be itself an extension) or None

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5)
sage: K.<a> = GF(5^3).over(F)
sage: L.<b> = GF(5^6).over(K)
sage: u = a/(1+b)
sage: nr = u.norm(K); nr
3 + 2*a^2
```

We check that the norm lives in the base ring:

```
sage: nr.parent()
↪needs sage.rings.finite_rings
Field in a with defining polynomial x^3 + 3*x + 3 over its base
sage: nr.parent() is K
↪needs sage.rings.finite_rings
True
```

Similarly, one can compute the norm over F:

```
sage: u.norm(F)
↪needs sage.rings.finite_rings
4
```

We check the transitivity of the norm:

```
sage: u.norm(F) == nr.norm(F)
↪needs sage.rings.finite_rings
True
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: u.norm()
↪needs sage.rings.finite_rings
3 + 2*a^2
```

Note that `base` must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: u.norm(GF(5^2)) #_
↳needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z2 of size 5^2
```

polynomial (*base=None, var='x'*)

Return a polynomial (in one or more variables) over `base` whose evaluation at the generators of the parent equals this element.

INPUT:

- `base` – a commutative ring (which might be itself an extension) or `None`

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F.<a> = GF(5^2).over() # over GF(5)
sage: K.<b> = GF(5^4).over(F)
sage: L.<c> = GF(5^12).over(K)
sage: u = 1/(a + b + c); u
(2 + (-1 - a)*b) + ((2 + 3*a) + (1 - a)*b)*c + ((-1 - a) - a*b)*c^2
sage: P = u.polynomial(K); P
((-1 - a) - a*b)*x^2 + ((2 + 3*a) + (1 - a)*b)*x + 2 + (-1 - a)*b
sage: P.base_ring() is K
True
sage: P(c) == u
True
```

When the base is F , we obtain a bivariate polynomial:

```
sage: P = u.polynomial(F); P #_
↳needs sage.rings.finite_rings
(-a)*x0^2*x1 + (-1 - a)*x0^2 + (1 - a)*x0*x1 + (2 + 3*a)*x0 + (-1 - a)*x1 + 2
```

We check that its value at the generators is the element we started with:

```
sage: L.gens(F) #_
↳needs sage.rings.finite_rings
(c, b)
sage: P(c, b) == u #_
↳needs sage.rings.finite_rings
True
```

Similarly, when the base is $GF(5)$, we get a trivariate polynomial:

```
sage: P = u.polynomial(GF(5)); P # needs sage.rings.finite_rings -x0^2*x1*x2 - x0^2*x2 -
x0*x1*x2 - x0^2 + x0*x1 - 2*x0*x2 - x1*x2 + 2*x0 - x1 + 2 sage: P(c, b, a) == u # needs
sage.rings.finite_rings True
```

Different variable names can be specified:

```
sage: u.polynomial(GF(5), var='y') #_
↳needs sage.rings.finite_rings
-y0^2*y1*y2 - y0^2*y2 - y0*y1*y2 - y0^2 + y0*y1 - 2*y0*y2 - y1*y2 + 2*y0 - y1_
↳+ 2
```

(continues on next page)

(continued from previous page)

```

sage: u.polynomial(GF(5), var=['x','y','z']) #_
↪needs sage.rings.finite_rings
-x^2*y*z - x^2*z - x*y*z - x^2 + x*y - 2*x*z - y*z + 2*x - y + 2
    
```

If base is omitted, it is set to its default which is the base of the extension:

```

sage: u.polynomial() #_
↪needs sage.rings.finite_rings
((-1 - a) - a*b)*x^2 + ((2 + 3*a) + (1 - a)*b)*x + 2 + (-1 - a)*b
    
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```

sage: u.polynomial(GF(5^3)) #_
↪needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z3 of size 5^3
    
```

trace (*base=None*)

Return the trace of this element over base.

INPUT:

- base – a commutative ring (which might be itself an extension) or None

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: F = GF(5)
sage: K.<a> = GF(5^3).over(F)
sage: L.<b> = GF(5^6).over(K)
sage: u = a/(1+b)
sage: tr = u.trace(K); tr
-1 + 3*a + 2*a^2
    
```

We check that the trace lives in the base ring:

```

sage: tr.parent() #_
↪needs sage.rings.finite_rings
Field in a with defining polynomial x^3 + 3*x + 3 over its base
sage: tr.parent() is K #_
↪needs sage.rings.finite_rings
True
    
```

Similarly, one can compute the trace over F:

```

sage: u.trace(F) #_
↪needs sage.rings.finite_rings
0
    
```

We check the transitivity of the trace:

```

sage: u.trace(F) == tr.trace(F) #_
↪needs sage.rings.finite_rings
True
    
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: u.trace()
↳needs sage.rings.finite_rings
-1 + 3*a + 2*a^2
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: u.trace(GF(5^2))
↳needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z2 of size 5^2
```

vector (*base=None*)

Return the vector of coordinates of this element over base (in the basis output by the method `basis_over()`).

INPUT:

- base – a commutative ring (which might be itself an extension) or None

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: F = GF(5)
sage: K.<a> = GF(5^2).over() # over F
sage: L.<b> = GF(5^6).over(K)
sage: x = (a+b)^4; x
(-1 + a) + (3 + a)*b + (1 - a)*b^2
sage: x.vector(K) # basis is (1, b, b^2)
(-1 + a, 3 + a, 1 - a)
sage: x.vector(F) # basis is (1, a, b, a*b, b^2, a*b^2)
(4, 1, 3, 1, 1, 4)
```

If base is omitted, it is set to its default which is the base of the extension:

```
sage: x.vector()
↳needs sage.rings.finite_rings
(-1 + a, 3 + a, 1 - a)
```

Note that base must be an explicit base over which the extension has been defined (as listed by the method `bases()`):

```
sage: x.vector(GF(5^3))
↳needs sage.rings.finite_rings
Traceback (most recent call last):
...
ValueError: not (explicitly) defined over Finite Field in z3 of size 5^3
```

7.3 Morphisms between extension of rings

AUTHOR:

- Xavier Caruso (2019)

class sage.rings.ring_extension_morphism.**MapFreeModuleToRelativeRing**

Bases: `Map`

Base class of the module isomorphism between a ring extension and a free module over one of its bases.

is_injective ()

Return whether this morphism is injective.

EXAMPLES:

```
sage: K = GF(11^6).over(GF(11^3)) #_
↪needs sage.rings.finite_rings
sage: V, i, j = K.free_module() #_
↪needs sage.rings.finite_rings
sage: i.is_injective() #_
↪needs sage.rings.finite_rings
True
```

is_surjective ()

Return whether this morphism is surjective.

EXAMPLES:

```
sage: K = GF(11^6).over(GF(11^3)) #_
↪needs sage.rings.finite_rings
sage: V, i, j = K.free_module() #_
↪needs sage.rings.finite_rings
sage: i.is_surjective() #_
↪needs sage.rings.finite_rings
True
```

class sage.rings.ring_extension_morphism.**MapRelativeRingToFreeModule**

Bases: `Map`

Base class of the module isomorphism between a ring extension and a free module over one of its bases.

is_injective ()

Return whether this morphism is injective.

EXAMPLES:

```
sage: K = GF(11^6).over(GF(11^3)) #_
↪needs sage.rings.finite_rings
sage: V, i, j = K.free_module() #_
↪needs sage.rings.finite_rings
sage: j.is_injective() #_
↪needs sage.rings.finite_rings
True
```

is_surjective ()

Return whether this morphism is injective.

EXAMPLES:

```

sage: K = GF(11^6).over(GF(11^3)) #_
↪needs sage.rings.finite_rings
sage: V, i, j = K.free_module() #_
↪needs sage.rings.finite_rings
sage: j.is_surjective() #_
↪needs sage.rings.finite_rings
True

```

class sage.rings.ring_extension_morphism.**RingExtensionBackendIsomorphism**

Bases: *RingExtensionHomomorphism*

A class for implementating isomorphisms taking an element of the backend to its ring extension.

class

sage.rings.ring_extension_morphism.**RingExtensionBackendReverseIsomorphism**

Bases: *RingExtensionHomomorphism*

A class for implementating isomorphisms from a ring extension to its backend.

class sage.rings.ring_extension_morphism.**RingExtensionHomomorphism**

Bases: *RingMap*

A class for ring homomorphisms between extensions.

base_map()

Return the base map of this morphism or just None if the base map is a coercion map.

EXAMPLES:

```

sage: F = GF(5)
sage: K.<a> = GF(5^2).over(F) #_
↪needs sage.rings.finite_rings
sage: L.<b> = GF(5^6).over(K) #_
↪needs sage.rings.finite_rings

```

We define the absolute Frobenius of L:

```

sage: FrobL = L.hom([b^5, a^5]); FrobL #_
↪needs sage.rings.finite_rings
Ring endomorphism of
Field in b with defining polynomial x^3 + (2 + 2*a)*x - a over its base
Defn: b |--> (-1 + a) + (1 + 2*a)*b + a*b^2
      with map on base ring:
      a |--> 1 - a
sage: FrobL.base_map() #_
↪needs sage.rings.finite_rings
Ring morphism:
From: Field in a with defining polynomial x^2 + 4*x + 2 over its base
To: Field in b with defining polynomial x^3 + (2 + 2*a)*x - a over its_
↪base
Defn: a |--> 1 - a

```

The square of FrobL acts trivially on K; in other words, it has a trivial base map:

```

sage: phi = FrobL^2; phi #_
↪needs sage.rings.finite_rings
Ring endomorphism of
Field in b with defining polynomial x^3 + (2 + 2*a)*x - a over its base

```

(continues on next page)

(continued from previous page)

```

Defn: b |--> 2 + 2*a*b + (2 - a)*b^2
sage: phi.base_map()
↪needs sage.rings.finite_rings

```

is_identity()

Return whether this morphism is the identity.

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: K.<a> = GF(5^2).over() # over GF(5)
sage: FrobK = K.hom([a^5])
sage: FrobK.is_identity()
False
sage: (FrobK^2).is_identity()
True

```

Coercion maps are not considered as identity morphisms:

```

sage: # needs sage.rings.finite_rings
sage: L.<b> = GF(5^6).over(K)
sage: iota = L.defining_morphism(); iota
Ring morphism:
  From: Field in a with defining polynomial x^2 + 4*x + 2 over its base
  To:   Field in b with defining polynomial x^3 + (2 + 2*a)*x - a over its_
↪base
  Defn: a |--> a
sage: iota.is_identity()
False

```

is_injective()

Return whether this morphism is injective.

EXAMPLES:

```

sage: # needs sage.rings.finite_rings
sage: K = GF(5^10).over(GF(5^5))
sage: iota = K.defining_morphism(); iota
Ring morphism:
  From: Finite Field in z5 of size 5^5
  To:   Field in z10 with defining polynomial
        x^2 + (2*z5^3 + 2*z5^2 + 4*z5 + 4)*x + z5 over its base
  Defn: z5 |--> z5
sage: iota.is_injective()
True

sage: K = GF(7).over(ZZ)
sage: iota = K.defining_morphism(); iota
Ring morphism:
  From: Integer Ring
  To:   Finite Field of size 7 over its base
  Defn: 1 |--> 1
sage: iota.is_injective()
False

```

is_surjective()

Return whether this morphism is surjective.

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: K = GF(5^10).over(GF(5^5))
sage: iota = K.defined_morphism(); iota
Ring morphism:
  From: Finite Field in z5 of size 5^5
  To:   Field in z10 with defining polynomial
        x^2 + (2*z5^3 + 2*z5^2 + 4*z5 + 4)*x + z5 over its base
  Defn: z5 |--> z5
sage: iota.is_surjective()
False

sage: K = GF(7).over(ZZ)
sage: iota = K.defined_morphism(); iota
Ring morphism:
  From: Integer Ring
  To:   Finite Field of size 7 over its base
  Defn: 1 |--> 1
sage: iota.is_surjective()
True
```


GENERIC DATA STRUCTURES AND ALGORITHMS FOR RINGS

8.1 Generic data structures and algorithms for rings

AUTHORS:

- Lorenz Panny (2022): `ProductTree`, `prod_with_derivative()`

class `sage.rings.generic.ProductTree` (*leaves*)

Bases: `object`

A simple binary product tree, i.e., a tree of ring elements in which every node equals the product of its children. (In particular, the *root* equals the product of all *leaves*.)

Product trees are a very useful building block for fast computer algebra. For example, a quasilinear-time Discrete Fourier Transform (the famous *Fast* Fourier Transform) can be implemented as follows using the `remainders()` method of this class:

```
sage: # needs sage.rings.finite_rings
sage: from sage.rings.generic import ProductTree
sage: F = GF(65537)
sage: a = F(1111)
sage: assert a.multiplicative_order() == 1024
sage: R.<x> = F[]
sage: ms = [x - a^i for i in range(1024)] # roots of unity
sage: ys = [F.random_element() for _ in range(1024)] # input vector
sage: tree = ProductTree(ms)
sage: zs = tree.remainders(R(ys)) # compute FFT!
sage: zs == [R(ys) % m for m in ms]
True
```

Similarly, the `interpolation()` method can be used to implement the inverse Fast Fourier Transform:

```
sage: tree.interpolation(zs).padded_list(len(ys)) == ys #_
↳needs sage.rings.finite_rings
True
```

This class encodes the tree as *layers*: Layer 0 is just a tuple of the leaves. Layer $i + 1$ is obtained from layer i by replacing each pair of two adjacent elements by their product, starting from the left. (If the length is odd, the unpaired element at the end is simply copied as is.) This iteration stops as soon as it yields a layer containing only a single element (the root).

Note: Use this class if you need the `remainders()` method. To compute just the product, `prod()` is likely faster.

INPUT:

- leaves – an iterable of elements in a common ring

EXAMPLES:

```
sage: from sage.rings.generic import ProductTree
sage: R.<x> = GF(101)[ ]
sage: vs = [x - i for i in range(1,10)]
sage: tree = ProductTree(vs)
sage: tree.root()
x^9 + 56*x^8 + 62*x^7 + 44*x^6 + 47*x^5 + 42*x^4 + 15*x^3 + 11*x^2 + 12*x + 13
sage: tree.reminders(x^7 + x + 1)
[3, 30, 70, 27, 58, 72, 98, 98, 23]
sage: tree.reminders(x^100)
[1, 1, 1, 1, 1, 1, 1, 1, 1]
```

```
sage: # needs sage.libs.pari
sage: vs = prime_range(100)
sage: tree = ProductTree(vs)
sage: tree.root().factor()
2 * 3 * 5 * 7 * 11 * 13 * 17 * 19 * 23 * 29 * 31 * 37 * 41 * 43 * 47 * 53 * 59 *
↳ 61 * 67 * 71 * 73 * 79 * 83 * 89 * 97
sage: tree.reminders(3599)
[1, 2, 4, 1, 2, 11, 12, 8, 11, 3, 3, 10, 32, 30, 27, 48, 0, 0, 48, 49, 22, 44, 30,
↳ 39, 10]
```

We can access the individual layers of the tree:

```
sage: tree.layers #_
↳ needs sage.libs.pari
[(2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73,
↳ 79, 83, 89, 97),
(6, 35, 143, 323, 667, 1147, 1763, 2491, 3599, 4757, 5767, 7387, 97),
(210, 46189, 765049, 4391633, 17120443, 42600829, 97),
(9699690, 3359814435017, 729345064647247, 97),
(32589158477190044730, 70746471270782959),
(2305567963945518424753102147331756070,)]
```

interpolation(*xs*)

Given a sequence *xs* of values, one per leaf, return a single element *x* which is congruent to the *i*th value in *xs* modulo the *i*th leaf, for all *i*.

This is an explicit version of the Chinese remainder theorem; see also `CRT()`. Using this product tree is faster for repeated calls since the required CRT bases are cached after the first run.

The base ring must support the `xgcd()` function for this method to work.

EXAMPLES:

```
sage: from sage.rings.generic import ProductTree
sage: vs = prime_range(100)
sage: tree = ProductTree(vs)
sage: tree.interpolation([1, 1, 2, 1, 9, 1, 7, 15, 8, 20, 15, 6, 27, 11, 2, 6,
↳ 0, 25, 49, 5, 51, 4, 19, 74, 13])
1085749272377676749812331719267
```

This method is faster than `CRT()` for repeated calls with the same moduli:

```

sage: vs = prime_range(1000,2000)
sage: rs = lambda: [randrange(1,100) for _ in vs]
sage: tree = ProductTree(vs)
sage: %timeit CRT(rs(), vs)           # not tested
372 µs ± 3.34 µs per loop (mean ± std. dev. of 7 runs, 1,000 loops each)
sage: %timeit tree.interpolation(rs()) # not tested
146 µs ± 479 ns per loop (mean ± std. dev. of 7 runs, 10,000 loops each)

```

leaves ()

Return a tuple containing the leaves of this product tree.

EXAMPLES:

```

sage: from sage.rings.generic import ProductTree
sage: R.<x> = GF(101)[]
sage: vs = [x - i for i in range(1,10)]
sage: tree = ProductTree(vs)
sage: tree.leaves()
(x + 100, x + 99, x + 98, ..., x + 93, x + 92)
sage: tree.leaves() == tuple(vs)
True

```

remainders (x)

Given a value x , return a list of all remainders of x modulo the leaves of this product tree.

The base ring must support the `%` operator for this method to work.

INPUT:

- x – an element of the base ring of this product tree

EXAMPLES:

```

sage: # needs sage.libs.pari
sage: from sage.rings.generic import ProductTree
sage: vs = prime_range(100)
sage: tree = ProductTree(vs)
sage: n = 1085749272377676749812331719267
sage: tree.remainders(n)
[1, 1, 2, 1, 9, 1, 7, 15, 8, 20, 15, 6, 27, 11, 2, 6, 0, 25, 49, 5, 51, 4, 19,
 ↪ 74, 13]
sage: [n % v for v in vs]
[1, 1, 2, 1, 9, 1, 7, 15, 8, 20, 15, 6, 27, 11, 2, 6, 0, 25, 49, 5, 51, 4, 19,
 ↪ 74, 13]

```

root ()

Return the value at the root of this product tree (i.e., the product of all leaves).

EXAMPLES:

```

sage: from sage.rings.generic import ProductTree
sage: R.<x> = GF(101)[]
sage: vs = [x - i for i in range(1,10)]
sage: tree = ProductTree(vs)
sage: tree.root()
x^9 + 56*x^8 + 62*x^7 + 44*x^6 + 47*x^5 + 42*x^4 + 15*x^3 + 11*x^2 + 12*x + 13
sage: tree.root() == prod(vs)
True

```

`sage.rings.generic.prod_with_derivative` (*pairs*)

Given an iterable of pairs $(f, \partial f)$ of ring elements, return the pair $(\prod f, \partial \prod f)$, assuming ∂ is an operator obeying the standard product rule.

This function is entirely algebraic, hence still works when the elements f and ∂f are all passed through some ring homomorphism first. One particularly useful instance of this is evaluating the derivative of a product of polynomials at a point without fully expanding the product; see the second example below.

INPUT:

- *pairs* – an iterable of tuples $(f, \partial f)$ of elements of a common ring

ALGORITHM: Repeated application of the product rule.

EXAMPLES:

```
sage: from sage.rings.generic import prod_with_derivative
sage: R.<x> = ZZ[]
sage: fs = [x^2 + 2*x + 3, 4*x + 5, 6*x^7 + 8*x + 9]
sage: prod(fs)
24*x^10 + 78*x^9 + 132*x^8 + 90*x^7 + 32*x^4 + 140*x^3 + 293*x^2 + 318*x + 135
sage: prod(fs).derivative()
240*x^9 + 702*x^8 + 1056*x^7 + 630*x^6 + 128*x^3 + 420*x^2 + 586*x + 318
sage: F, dF = prod_with_derivative((f, f.derivative()) for f in fs)
sage: F
24*x^10 + 78*x^9 + 132*x^8 + 90*x^7 + 32*x^4 + 140*x^3 + 293*x^2 + 318*x + 135
sage: dF
240*x^9 + 702*x^8 + 1056*x^7 + 630*x^6 + 128*x^3 + 420*x^2 + 586*x + 318
```

The main reason for this function to exist is that it allows us to *evaluate* the derivative of a product of polynomials at a point α without ever fully expanding the product *as a polynomial*:

```
sage: alpha = 42
sage: F(alpha)
442943981574522759
sage: dF(alpha)
104645261461514994
sage: us = [f(alpha) for f in fs]
sage: vs = [f.derivative()(alpha) for f in fs]
sage: prod_with_derivative(zip(us, vs))
(442943981574522759, 104645261461514994)
```

9.1 Big O for various types (power series, p-adics, etc.)

See also:

- asymptotic expansions
- p-adic numbers
- power series
- polynomials

`sage.rings.big_oh.O(*x, **kws)`

Big O constructor for various types.

EXAMPLES:

This is useful for writing power series elements:

```
sage: R.<t> = ZZ[['t']]
sage: (1+t)^10 + O(t^5)
1 + 10*t + 45*t^2 + 120*t^3 + 210*t^4 + O(t^5)
```

A power series ring is created implicitly if a polynomial element is passed:

```
sage: R.<x> = QQ['x']
sage: O(x^100)
O(x^100)
sage: 1/(1+x+O(x^5))
1 - x + x^2 - x^3 + x^4 + O(x^5)
sage: R.<u,v> = QQ[['u','v']]
sage: 1 + u + v^2 + O(u, v)^5
1 + u + v^2 + O(u, v)^5
```

This is also useful to create p -adic numbers:

```
sage: O(7^6) #_
↪needs sage.rings.padics
O(7^6)
sage: 1/3 + O(7^6) #_
↪needs sage.rings.padics
5 + 4*7 + 4*7^2 + 4*7^3 + 4*7^4 + 4*7^5 + O(7^6)
```

It behaves well with respect to adding negative powers of p :

```
sage: a = O(11^-32); a #_
↪needs sage.rings.padics
O(11^-32)
sage: a.parent() #_
↪needs sage.rings.padics
11-adic Field with capped relative precision 20
```

There are problems if you add a rational with very negative valuation to an O -Term:

```
sage: 11^-12 + O(11^15) #_
↪needs sage.rings.padics
11^-12 + O(11^8)
```

The reason that this fails is that the constructor doesn't know the right precision cap to use. If you cast explicitly or use other means of element creation, you can get around this issue:

```
sage: # needs sage.rings.padics
sage: K = Qp(11, 30)
sage: K(11^-12) + O(11^15)
11^-12 + O(11^15)
sage: 11^-12 + K(O(11^15))
11^-12 + O(11^15)
sage: K(11^-12, absprec=15)
11^-12 + O(11^15)
sage: K(11^-12, 15)
11^-12 + O(11^15)
```

We can also work with asymptotic expansions:

```
sage: A.<n> = AsymptoticRing(growth_group='QQ^n * n^QQ * log(n)^QQ', #_
↪needs sage.symbolic
.....: coefficient_ring=QQ); A
Asymptotic Ring <QQ^n * n^QQ * log(n)^QQ * Signs^n> over Rational Field
sage: O(n) #_
↪needs sage.symbolic
O(n)
```

Application with Puiseux series:

```
sage: P.<y> = PuiseuxSeriesRing(ZZ)
sage: y^(1/5) + O(y^(1/3))
y^(1/5) + O(y^(1/3))
sage: y^(1/3) + O(y^(1/5))
O(y^(1/5))
```

9.2 Signed and Unsigned Infinities

The unsigned infinity “ring” is the set of two elements

1. infinity
2. A number less than infinity

The rules for arithmetic are that the unsigned infinity ring does not canonically coerce to any other ring, and all other rings canonically coerce to the unsigned infinity ring, sending all elements to the single element “a number less than infinity” of

the unsigned infinity ring. Arithmetic and comparisons then take place in the unsigned infinity ring, where all arithmetic operations that are well-defined are defined.

The infinity “ring” is the set of five elements

1. plus infinity
2. a positive finite element
3. zero
4. a negative finite element
5. negative infinity

The infinity ring coerces to the unsigned infinity ring, sending the infinite elements to infinity and the non-infinite elements to “a number less than infinity.” Any ordered ring coerces to the infinity ring in the obvious way.

Note: The shorthand `oo` is predefined in Sage to be the same as `+Infinity` in the infinity ring. It is considered equal to, but not the same as `Infinity` in the *UnsignedInfinityRing*.

EXAMPLES:

We fetch the unsigned infinity ring and create some elements:

```
sage: P = UnsignedInfinityRing; P
The Unsigned Infinity Ring
sage: P(5)
A number less than infinity
sage: P.ngens()
1
sage: unsigned_oo = P.0; unsigned_oo
Infinity
```

We compare finite numbers with infinity:

```
sage: 5 < unsigned_oo
True
sage: 5 > unsigned_oo
False
sage: unsigned_oo < 5
False
sage: unsigned_oo > 5
True
```

Demonstrating the shorthand `oo` versus `Infinity`:

```
sage: oo
+Infinity
sage: oo is InfinityRing.0
True
sage: oo is UnsignedInfinityRing.0
False
sage: oo == UnsignedInfinityRing.0
True
```

We do arithmetic:

```
sage: unsigned_oo + 5
Infinity
```

We make `1 / unsigned_oo` return the integer 0 so that arithmetic of the following type works:

```
sage: (1/unsigned_oo) + 2
2
sage: 32/5 - (2.439/unsigned_oo)
32/5
```

Note that many operations are not defined, since the result is not well-defined:

```
sage: unsigned_oo/0
Traceback (most recent call last):
...
ValueError: quotient of number < oo by number < oo not defined
```

What happened above is that 0 is canonically coerced to “A number less than infinity” in the unsigned infinity ring. Next, Sage tries to divide by multiplying with its inverse. Finally, this inverse is not well-defined.

```
sage: 0/unsigned_oo
0
sage: unsigned_oo * 0
Traceback (most recent call last):
...
ValueError: unsigned oo times smaller number not defined
sage: unsigned_oo/unsigned_oo
Traceback (most recent call last):
...
ValueError: unsigned oo times smaller number not defined
```

In the infinity ring, we can negate infinity, multiply positive numbers by infinity, etc.

```
sage: P = InfinityRing; P
The Infinity Ring
sage: P(5)
A positive finite number
```

The symbol `oo` is predefined as a shorthand for `+Infinity`:

```
sage: oo
+Infinity
```

We compare finite and infinite elements:

```
sage: 5 < oo
True
sage: P(-5) < P(5)
True
sage: P(2) < P(3)
False
sage: -oo < oo
True
```

We can do more arithmetic than in the unsigned infinity ring:

```
sage: 2 * oo
+Infinity
sage: -2 * oo
-Infinity
sage: 1 - oo
```

(continues on next page)

(continued from previous page)

```
-Infinity
sage: 1 / oo
0
sage: -1 / oo
0
```

We make $1 / \infty$ and $1 / -\infty$ return the integer 0 instead of the infinity ring `Zero` so that arithmetic of the following type works:

```
sage: (1/oo) + 2
2
sage: 32/5 - (2.439/-oo)
32/5
```

If we try to subtract infinities or multiply infinity by zero we still get an error:

```
sage: oo - oo
Traceback (most recent call last):
...
SignError: cannot add infinity to minus infinity
sage: 0 * oo
Traceback (most recent call last):
...
SignError: cannot multiply infinity by zero
sage: P(2) + P(-3)
Traceback (most recent call last):
...
SignError: cannot add positive finite value to negative finite value
```

Signed infinity can also be represented by RR / RDF elements. But unsigned infinity cannot:

```
sage: oo in RR, oo in RDF
(True, True)
sage: unsigned_infinity in RR, unsigned_infinity in RDF
(False, False)
```

class sage.rings.infinity.**AnInfinity**

Bases: object

lcm(*x*)

Return the least common multiple of ∞ and *x*, which is by definition ∞ unless *x* is 0.

EXAMPLES:

```
sage: oo.lcm(0)
0
sage: oo.lcm(oo)
+Infinity
sage: oo.lcm(-oo)
+Infinity
sage: oo.lcm(10)
+Infinity
sage: (-oo).lcm(10)
+Infinity
```

class sage.rings.infinity.**FiniteNumber**(*parent*, *x*)

Bases: RingElement

Initialize self.

sign()

Return the sign of self.

EXAMPLES:

```
sage: sign(InfinityRing(2))
1
sage: sign(InfinityRing(0))
0
sage: sign(InfinityRing(-2))
-1
```

sqrt()

EXAMPLES:

```
sage: InfinityRing(7).sqrt()
A positive finite number
sage: InfinityRing(0).sqrt()
Zero
sage: InfinityRing(-.001).sqrt()
Traceback (most recent call last):
...
SignError: cannot take square root of a negative number
```

class sage.rings.infinity.InfinityRing_class

Bases: Singleton, CommutativeRing

Initialize self.

fraction_field()

This isn't really a ring, let alone an integral domain.

gen ($n=0$)

The two generators are plus and minus infinity.

EXAMPLES:

```
sage: InfinityRing.gen(0)
+Infinity
sage: InfinityRing.gen(1)
-Infinity
sage: InfinityRing.gen(2)
Traceback (most recent call last):
...
IndexError: n must be 0 or 1
```

gens()

The two generators are plus and minus infinity.

EXAMPLES:

```
sage: InfinityRing.gens()
(+Infinity, -Infinity)
```

is_commutative()

The Infinity Ring is commutative

EXAMPLES:

```
sage: InfinityRing.is_commutative()
True
```

is_zero()

The Infinity Ring is not zero

EXAMPLES:

```
sage: InfinityRing.is_zero()
False
```

ngens()

The two generators are plus and minus infinity.

EXAMPLES:

```
sage: InfinityRing.ngens()
2
sage: len(InfinityRing.gens())
2
```

class sage.rings.infinity.**LessThanInfinity**(*args)

Bases: `_uniq`, `RingElement`

Initialize self.

EXAMPLES:

```
sage: sage.rings.infinity.LessThanInfinity() is UnsignedInfinityRing(5)
True
```

sign()

Raise an error because the sign of `self` is not well defined.

EXAMPLES:

```
sage: sign(UnsignedInfinityRing(2))
Traceback (most recent call last):
...
NotImplementedError: sign of number < oo is not well defined
sage: sign(UnsignedInfinityRing(0))
Traceback (most recent call last):
...
NotImplementedError: sign of number < oo is not well defined
sage: sign(UnsignedInfinityRing(-2))
Traceback (most recent call last):
...
NotImplementedError: sign of number < oo is not well defined
```

class sage.rings.infinity.**MinusInfinity**(*args)

Bases: `_uniq`, `AnInfinity`, `InfinityElement`

Initialize self.

sqrt()

EXAMPLES:

```
sage: (-oo).sqrt()
Traceback (most recent call last):
...
SignError: cannot take square root of negative infinity
```

class sage.rings.infinity.PlusInfinity(*args)

Bases: `_uniq`, `AnInfinity`, `InfinityElement`

Initialize self.

sqrt ()

The square root of self.

The square root of infinity is infinity.

EXAMPLES:

```
sage: oo.sqrt()
+Infinity
```

exception sage.rings.infinity.SignError

Bases: `ArithmeticError`

Sign error exception.

class sage.rings.infinity.UnsignedInfinity(*args)

Bases: `_uniq`, `AnInfinity`, `InfinityElement`

Initialize self.

class sage.rings.infinity.UnsignedInfinityRing_class

Bases: `Singleton`, `Parent`

Initialize self.

gen (n=0)

The “generator” of self is the infinity object.

EXAMPLES:

```
sage: UnsignedInfinityRing.gen()
Infinity
sage: UnsignedInfinityRing.gen(1)
Traceback (most recent call last):
...
IndexError: UnsignedInfinityRing only has one generator
```

gens ()

The “generator” of self is the infinity object.

EXAMPLES:

```
sage: UnsignedInfinityRing.gens()
(Infinity,)
```

less_than_infinity ()

This is the element that represents a finite value.

EXAMPLES:

```
sage: UnsignedInfinityRing.less_than_infinity()
A number less than infinity
sage: UnsignedInfinityRing(5) is UnsignedInfinityRing.less_than_infinity()
True
```

ngens ()

The unsigned infinity ring has one “generator.”

EXAMPLES:

```
sage: UnsignedInfinityRing.ngens()
1
sage: len(UnsignedInfinityRing.gens())
1
```

`sage.rings.infinity.is_Infinite(x)`

This is a type check for infinity elements.

EXAMPLES:

```
sage: sage.rings.infinity.is_Infinite(oo)
True
sage: sage.rings.infinity.is_Infinite(-oo)
True
sage: sage.rings.infinity.is_Infinite(unsigned_infinity)
True
sage: sage.rings.infinity.is_Infinite(3)
False
sage: sage.rings.infinity.is_Infinite(RR(infinity))
False
sage: sage.rings.infinity.is_Infinite(ZZ)
False
```

`sage.rings.infinity.test_comparison(ring)`

Check comparison with infinity

INPUT:

- `ring` – a sub-ring of the real numbers

OUTPUT:

Various attempts are made to generate elements of `ring`. An assertion is triggered if one of these elements does not compare correctly with plus/minus infinity.

EXAMPLES:

```
sage: from sage.rings.infinity import test_comparison
sage: rings = [ZZ, QQ, RDF]
sage: rings += [RR, RealField(200)] #_
↳needs sage.rings.real_mprfr
sage: rings += [RLF, RIF] #_
↳needs sage.rings.real_interval_field
sage: for R in rings:
.....:     print('testing {}'.format(R))
.....:     test_comparison(R)
testing Integer Ring
testing Rational Field
testing Real Double Field...
```

(continues on next page)

(continued from previous page)

```
sage: test_comparison(AA) #_
↳needs sage.rings.number_field
```

Comparison with number fields does not work:

```
sage: x = polygen(ZZ, 'x')
sage: K.<sqrt3> = NumberField(x^2 - 3) #_
↳needs sage.rings.number_field
sage: (-oo < 1 + sqrt3) and (1 + sqrt3 < oo) # known bug #_
↳needs sage.rings.number_field
False
```

The symbolic ring handles its own infinities, but answers `False` (meaning: cannot decide) already for some very elementary comparisons:

```
sage: test_comparison(SR) # known bug #_
↳needs sage.symbolic
Traceback (most recent call last):
...
AssertionError: testing -1000.0 in Symbolic Ring: id = ...
```

`sage.rings.infinity.test_signed_infinity(pos_inf)`

Test consistency of infinity representations.

There are different possible representations of infinity in Sage. These are all consistent with the infinity ring, that is, compare with infinity in the expected way. See also [Issue #14045](#)

INPUT:

- `pos_inf` – a representation of positive infinity.

OUTPUT:

An assertion error is raised if the representation is not consistent with the infinity ring.

Check that [Issue #14045](#) is fixed:

```
sage: InfinityRing(float('+inf'))
+Infinity
sage: InfinityRing(float('-inf'))
-Infinity
sage: oo > float('+inf')
False
sage: oo == float('+inf')
True
```

EXAMPLES:

```
sage: from sage.rings.infinity import test_signed_infinity
sage: test_signed_infinity(oo)
sage: test_signed_infinity(float('+inf'))
sage: test_signed_infinity(RIF(oo)) #_
↳needs sage.rings.real_interval_field
sage: test_signed_infinity(RIF(oo)) #_
↳needs sage.rings.real_interval_field
sage: test_signed_infinity(SR(oo)) #_
↳needs sage.symbolic
```

9.3 Support Python's numbers abstract base class

See also:

[PEP 3141](#) for more information about `numbers`.

DERIVATION

10.1 Derivations

Let A be a ring and B be a bimodule over A . A derivation $d : A \rightarrow B$ is an additive map that satisfies the Leibniz rule

$$d(xy) = xd(y) + d(x)y.$$

If B is an algebra over A and if we are given in addition a ring homomorphism $\theta : A \rightarrow B$, a twisted derivation with respect to θ (or a θ -derivation) is an additive map $d : A \rightarrow B$ such that

$$d(xy) = \theta(x)d(y) + d(x)y.$$

When θ is the morphism defining the structure of A -algebra on B , a θ -derivation is nothing but a derivation. In general, if $\iota : A \rightarrow B$ denotes the defining morphism above, one easily checks that $\theta - \iota$ is a θ -derivation.

This file provides support for derivations and twisted derivations over commutative rings with values in algebras (i.e. we require that B is a commutative A -algebra). In this case, the set of derivations (resp. θ -derivations) is a module over B .

Given a ring A , the module of derivations over A can be created as follows:

```
sage: A.<x, y, z> = QQ[]
sage: M = A.derivation_module()
sage: M
Module of derivations over
Multivariate Polynomial Ring in x, y, z over Rational Field
```

The method `gens()` returns the generators of this module:

```
sage: A.<x, y, z> = QQ[]
sage: M = A.derivation_module()
sage: M.gens()
(d/dx, d/dy, d/dz)
```

We can combine them in order to create all derivations:

```
sage: d = 2*M.gen(0) + z*M.gen(1) + (x^2 + y^2)*M.gen(2)
sage: d
2*d/dx + z*d/dy + (x^2 + y^2)*d/dz
```

and now play with them:

```
sage: d(x + y + z)
x^2 + y^2 + z + 2
sage: P = A.random_element()
```

(continues on next page)

(continued from previous page)

```
sage: Q = A.random_element()
sage: d(P*Q) == P*d(Q) + d(P)*Q
True
```

Alternatively we can use the method `derivation()` of the ring A to create derivations:

```
sage: Dx = A.derivation(x); Dx
d/dx
sage: Dy = A.derivation(y); Dy
d/dy
sage: Dz = A.derivation(z); Dz
d/dz
sage: A.derivation([2, z, x^2+y^2])
2*d/dx + z*d/dy + (x^2 + y^2)*d/dz
```

Sage knows moreover that M is a Lie algebra:

```
sage: M.category()
Join of
Category of Lie algebras with basis over Rational Field and
Category of modules with basis over
Multivariate Polynomial Ring in x, y, z over Rational Field
```

Computations of Lie brackets are implemented as well:

```
sage: Dx.bracket(Dy)
0
sage: d.bracket(Dx)
-2*x*d/dz
```

At the creation of a module of derivations, a codomain can be specified:

```
sage: B = A.fraction_field()
sage: A.derivation_module(B)
Module of derivations from Multivariate Polynomial Ring in x, y, z over Rational Field
to Fraction Field of Multivariate Polynomial Ring in x, y, z over Rational Field
```

Alternatively, one can specify a morphism f with domain A . In this case, the codomain of the derivations is the codomain of f but the latter is viewed as an algebra over A through the homomorphism f . This construction is useful, for example, if we want to work with derivations on A at a certain point, e.g. $(0, 1, 2)$. Indeed, in order to achieve this, we first define the evaluation map at this point:

```
sage: ev = A.hom([QQ(0), QQ(1), QQ(2)])
sage: ev
Ring morphism:
From: Multivariate Polynomial Ring in x, y, z over Rational Field
To: Rational Field
Defn: x |--> 0
      y |--> 1
      z |--> 2
```

Now we use this ring homomorphism to define a structure of A -algebra on \mathbf{Q} and then build the following module of derivations:

```
sage: M = A.derivation_module(ev)
sage: M
```

(continues on next page)

(continued from previous page)

```

Module of derivations
  from Multivariate Polynomial Ring in x, y, z over Rational Field
  to Rational Field
sage: M.gens()
(d/dx, d/dy, d/dz)

```

Elements in M then acts as derivations at $(0, 1, 2)$:

```

sage: Dx = M.gen(0)
sage: Dy = M.gen(1)
sage: Dz = M.gen(2)
sage: f = x^2 + y^2 + z^2
sage: Dx(f) # = 2*x evaluated at (0,1,2)
0
sage: Dy(f) # = 2*y evaluated at (0,1,2)
2
sage: Dz(f) # = 2*z evaluated at (0,1,2)
4

```

Twisted derivations are handled similarly:

```

sage: theta = B.hom([B(y), B(z), B(x)])
sage: theta
Ring endomorphism of Fraction Field of
Multivariate Polynomial Ring in x, y, z over Rational Field
Defn: x |--> y
      y |--> z
      z |--> x
sage: M = B.derivation_module(twist=theta)
sage: M
Module of twisted derivations over Fraction Field of Multivariate Polynomial Ring
in x, y, z over Rational Field (twisting morphism: x |--> y, y |--> z, z |--> x)

```

Over a field, one proves that every θ -derivation is a multiple of $\theta - id$, so that:

```

sage: d = M.gen(); d
[x |--> y, y |--> z, z |--> x] - id

```

and then:

```

sage: d(x)
-x + y
sage: d(y)
-y + z
sage: d(z)
x - z
sage: d(x + y + z)
0

```

AUTHOR:

- Xavier Caruso (2018-09)

```
class sage.rings.derivation.RingDerivation
```

```
  Bases: ModuleElement
```

An abstract class for twisted and untwisted derivations over commutative rings.

codomain()

Return the codomain of this derivation.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: f = R.derivation(); f
d/dx
sage: f.codomain()
Univariate Polynomial Ring in x over Rational Field
sage: f.codomain() is R
True
```

```
sage: S.<y> = R[]
sage: M = R.derivation_module(S)
sage: M.random_element().codomain()
Univariate Polynomial Ring in y over
Univariate Polynomial Ring in x over Rational Field
sage: M.random_element().codomain() is S
True
```

domain()

Return the domain of this derivation.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: f = R.derivation(y); f
d/dy
sage: f.domain()
Multivariate Polynomial Ring in x, y over Rational Field
sage: f.domain() is R
True
```

class sage.rings.derivation.**RingDerivationModule** (*domain, codomain, twist=None*)

Bases: Module, UniqueRepresentation

A class for modules of derivations over a commutative ring.

basis()

Return a basis of this module of derivations.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: M = R.derivation_module()
sage: M.basis()
Family (d/dx, d/dy)
```

codomain()

Return the codomain of the derivations in this module.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: M = R.derivation_module(); M
Module of derivations over Multivariate Polynomial Ring in x, y over Integer
↪ Ring
```

(continues on next page)

(continued from previous page)

```
sage: M.codomain()
Multivariate Polynomial Ring in x, y over Integer Ring
```

defining_morphism()

Return the morphism defining the structure of algebra of the codomain over the domain.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: M = R.derivation_module()
sage: M.defining_morphism()
Identity endomorphism of Univariate Polynomial Ring in x over Rational Field

sage: S.<y> = R[]
sage: M = R.derivation_module(S)
sage: M.defining_morphism()
Polynomial base injection morphism:
  From: Univariate Polynomial Ring in x over Rational Field
  To:   Univariate Polynomial Ring in y over
        Univariate Polynomial Ring in x over Rational Field

sage: ev = R.hom([QQ(0)])
sage: M = R.derivation_module(ev)
sage: M.defining_morphism()
Ring morphism:
  From: Univariate Polynomial Ring in x over Rational Field
  To:   Rational Field
  Defn: x |--> 0
```

domain()

Return the domain of the derivations in this module.

EXAMPLES:

```
sage: R.<x, y> = ZZ[]
sage: M = R.derivation_module(); M
Module of derivations over Multivariate Polynomial Ring in x, y over Integer
↪Ring
sage: M.domain()
Multivariate Polynomial Ring in x, y over Integer Ring
```

dual_basis()

Return the dual basis of the canonical basis of this module of derivations (which is that returned by the method *basis()*).

Note: The dual basis of (d_1, \dots, d_n) is a family (x_1, \dots, x_n) of elements in the domain such that $d_i(x_i) = 1$ and $d_i(x_j) = 0$ if $i \neq j$.

EXAMPLES:

```
sage: R.<x, y> = ZZ[]
sage: M = R.derivation_module()
sage: M.basis()
Family (d/dx, d/dy)
```

(continues on next page)

(continued from previous page)

```
sage: M.dual_basis()
Family (x, y)
```

gen ($n=0$)

Return the n -th generator of this module of derivations.

INPUT:

- n – an integer (default: 0)

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: M = R.derivation_module(); M
Module of derivations over Multivariate Polynomial Ring in x, y over Integer_
↪Ring
sage: M.gen()
d/dx
sage: M.gen(1)
d/dy
```

gens ()

Return the generators of this module of derivations.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: M = R.derivation_module(); M
Module of derivations over Multivariate Polynomial Ring in x, y over Integer_
↪Ring
sage: M.gens()
(d/dx, d/dy)
```

We check that, for a nontrivial twist over a field, the module of twisted derivation is a vector space of dimension 1 generated by `twist - id`:

```
sage: K = R.fraction_field()
sage: theta = K.hom([K(y), K(x)])
sage: M = K.derivation_module(twist=theta); M
Module of twisted derivations over Fraction Field of Multivariate Polynomial
Ring in x, y over Integer Ring (twisting morphism: x |--> y, y |--> x)
sage: M.gens()
([x |--> y, y |--> x] - id,)
```

ngens ()

Return the number of generators of this module of derivations.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: M = R.derivation_module(); M
Module of derivations over Multivariate Polynomial Ring in x, y over Integer_
↪Ring
sage: M.ngens()
2
```

Indeed, generators are:

```
sage: M.gens()
(d/dx, d/dy)
```

We check that, for a nontrivial twist over a field, the module of twisted derivation is a vector space of dimension 1 generated by `twist - id`:

```
sage: K = R.fraction_field()
sage: theta = K.hom([K(y), K(x)])
sage: M = K.derivation_module(twist=theta); M
Module of twisted derivations over Fraction Field of Multivariate Polynomial
Ring in x, y over Integer Ring (twisting morphism: x |--> y, y |--> x)
sage: M.ngens()
1
sage: M.gen()
[x |--> y, y |--> x] - id
```

random_element (*args, **kws)

Return a random derivation in this module.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: M = R.derivation_module()
sage: M.random_element() # random
(x^2 + x*y - 3*y^2 + x + 1)*d/dx + (-2*x^2 + 3*x*y + 10*y^2 + 2*x + 8)*d/dy
```

ring_of_constants ()

Return the subring of the domain consisting of elements x such that $d(x) = 0$ for all derivation d in this module.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: M = R.derivation_module()
sage: M.basis()
Family (d/dx, d/dy)
sage: M.ring_of_constants()
Rational Field
```

some_elements ()

Return a list of elements of this module.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: M = R.derivation_module()
sage: M.some_elements()
[d/dx, d/dy, x*d/dx, x*d/dy, y*d/dx, y*d/dy]
```

twisting_morphism ()

Return the twisting homomorphism of the derivations in this module.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: theta = R.hom([y, x])
sage: M = R.derivation_module(twist=theta); M
```

(continues on next page)

(continued from previous page)

```
Module of twisted derivations over Multivariate Polynomial Ring in x, y
over Integer Ring (twisting morphism: x |--> y, y |--> x)
sage: M.twisting_morphism()
Ring endomorphism of Multivariate Polynomial Ring in x, y over Integer Ring
Defn: x |--> y
      y |--> x
```

When the derivations are untwisted, this method returns nothing:

```
sage: M = R.derivation_module()
sage: M.twisting_morphism()
```

class `sage.rings.derivation.RingDerivationWithTwist_generic` (*parent*, *scalar=0*)

Bases: *RingDerivation*

The class handles θ -derivations of the form $\lambda(\theta - \iota)$ (where ι is the defining morphism of the codomain over the domain) for a scalar λ varying in the codomain.

extend_to_fraction_field()

Return the extension of this derivation to fraction fields of the domain and the codomain.

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: theta = R.hom([y,x])
sage: d = R.derivation(x, twist=theta)
sage: d
x*([x |--> y, y |--> x] - id)

sage: D = d.extend_to_fraction_field(); D #_
↪needs sage.libs.singular
x*([x |--> y, y |--> x] - id)
sage: D.domain() #_
↪needs sage.libs.singular
Fraction Field of Multivariate Polynomial Ring in x, y over Integer Ring

sage: D(1/x) #_
↪needs sage.libs.singular
(x - y)/y
```

list()

Return the list of coefficient of this twisted derivation on the canonical basis.

EXAMPLES:

```
sage: R.<x,y> = QQ[]
sage: K = R.fraction_field()
sage: theta = K.hom([y,x])
sage: M = K.derivation_module(twist=theta)
sage: M.basis()
Family (twisting_morphism - id,)
sage: f = (x+y) * M.gen()
sage: f
(x + y)*(twisting_morphism - id)
sage: f.list()
[x + y]
```


postcompose (*morphism*)

Return the twisted derivation obtained by applying first this twisted derivation and then `morphism`.

INPUT:

- `morphism` – a homomorphism of rings whose domain is the codomain of this derivation or a ring into which the codomain of this derivation

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: theta = R.hom([y,x])
sage: D = R.derivation(x, twist=theta); D
x*([x |--> y, y |--> x] - id)

sage: f = R.hom([x^2, y^3])
sage: g = D.precompose(f); g
x*([x |--> y^2, y |--> x^3] - [x |--> x^2, y |--> y^3])
```

Observe that the g is no longer a θ -derivation but a $(\theta \circ f)$ -derivation:

```
sage: g.parent().twisting_morphism()
Ring endomorphism of Multivariate Polynomial Ring in x, y over Integer Ring
Defn: x |--> y^2
      y |--> x^3
```

precompose (*morphism*)

Return the twisted derivation obtained by applying first `morphism` and then this twisted derivation.

INPUT:

- `morphism` – a homomorphism of rings whose codomain is the domain of this derivation or a ring that coerces to the domain of this derivation

EXAMPLES:

```
sage: R.<x,y> = ZZ[]
sage: theta = R.hom([y,x])
sage: D = R.derivation(x, twist=theta); D
x*([x |--> y, y |--> x] - id)

sage: f = R.hom([x^2, y^3])
sage: g = D.postcompose(f); g
x^2*([x |--> y^3, y |--> x^2] - [x |--> x^2, y |--> y^3])
```

Observe that the g is no longer a θ -derivation but a $(f \circ \theta)$ -derivation:

```
sage: g.parent().twisting_morphism()
Ring endomorphism of Multivariate Polynomial Ring in x, y over Integer Ring
Defn: x |--> y^3
      y |--> x^2
```

class `sage.rings.derivation.RingDerivationWithoutTwist`

Bases: `RingDerivation`

An abstract class for untwisted derivations.

extend_to_fraction_field()

Return the extension of this derivation to fraction fields of the domain and the codomain.

EXAMPLES:

```

sage: S.<x> = QQ[]
sage: d = S.derivation()
sage: d
d/dx

sage: D = d.extend_to_fraction_field()
sage: D
d/dx
sage: D.domain()
Fraction Field of Univariate Polynomial Ring in x over Rational Field

sage: D(1/x)
-1/x^2

```

is_zero()

Return True if this derivation is zero.

EXAMPLES:

```

sage: R.<x,y> = ZZ[]
sage: f = R.derivation(); f
d/dx
sage: f.is_zero()
False

sage: (f-f).is_zero()
True

```

list()

Return the list of coefficient of this derivation on the canonical basis.

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: M = R.derivation_module()
sage: M.basis()
Family (d/dx, d/dy)

sage: R.derivation(x).list()
[1, 0]
sage: R.derivation(y).list()
[0, 1]

sage: f = x*R.derivation(x) + y*R.derivation(y); f
x*d/dx + y*d/dy
sage: f.list()
[x, y]

```

monomial_coefficients()

Return dictionary of nonzero coordinates (on the canonical basis) of this derivation.

More precisely, this returns a dictionary whose keys are indices of basis elements and whose values are the corresponding coefficients.

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: M = R.derivation_module()

```

(continues on next page)

(continued from previous page)

```

sage: M.basis()
Family (d/dx, d/dy)

sage: R.derivation(x).monomial_coefficients()
{0: 1}
sage: R.derivation(y).monomial_coefficients()
{1: 1}

sage: f = x*R.derivation(x) + y*R.derivation(y); f
x*d/dx + y*d/dy
sage: f.monomial_coefficients()
{0: x, 1: y}

```

postcompose (*morphism*)

Return the derivation obtained by applying first this derivation and then `morphism`.

INPUT:

- `morphism` – a homomorphism of rings whose domain is the codomain of this derivation or a ring into which the codomain of this derivation coerces

EXAMPLES:

```

sage: A.<x,y>= QQ[]
sage: ev = A.hom([QQ(0), QQ(1)])
sage: Dx = A.derivation(x)
sage: Dy = A.derivation(y)

```

We can define the derivation at $(0, 1)$ just by postcomposing with `ev`:

```

sage: dx = Dx.postcompose(ev)
sage: dy = Dy.postcompose(ev)
sage: f = x^2 + y^2
sage: dx(f)
0
sage: dy(f)
2

```

Note that we cannot avoid the creation of the evaluation morphism: if we pass in `QQ` instead, an error is raised since there is no coercion morphism from `A` to `QQ`:

```

sage: Dx.postcompose(QQ)
Traceback (most recent call last):
...
TypeError: the codomain of the derivation does not coerce to the given ring

```

Note that this method cannot be used to compose derivations:

```

sage: Dx.precompose(Dy)
Traceback (most recent call last):
...
TypeError: you must give a homomorphism of rings

```

precompose (*morphism*)

Return the derivation obtained by applying first `morphism` and then this derivation.

INPUT:

- morphism – a homomorphism of rings whose codomain is the domain of this derivation or a ring that coerces to the domain of this derivation

EXAMPLES:

```
sage: A.<x> = QQ[]
sage: B.<x,y> = QQ[]
sage: D = B.derivation(x) - 2*x*B.derivation(y); D
d/dx - 2*x*d/dy
```

When restricting to A, the term d/dy disappears (since it vanishes on A):

```
sage: D.precompose(A)
d/dx
```

If we restrict to another well chosen subring, the derivation vanishes:

```
sage: C.<t> = QQ[]
sage: f = C.hom([x^2 + y]); f
Ring morphism:
  From: Univariate Polynomial Ring in t over Rational Field
  To:   Multivariate Polynomial Ring in x, y over Rational Field
  Defn: t |--> x^2 + y
sage: D.precompose(f)
0
```

Note that this method cannot be used to compose derivations:

```
sage: D.precompose(D)
Traceback (most recent call last):
...
TypeError: you must give a homomorphism of rings
```

pth_power()

Return the p -th power of this derivation where p is the characteristic of the domain.

Note: Leibniz rule implies that this is again a derivation.

EXAMPLES:

```
sage: # needs sage.rings.finite_rings
sage: R.<x,y> = GF(5)[]
sage: Dx = R.derivation(x)
sage: Dx.pth_power()
0
sage: (x*Dx).pth_power()
x*d/dx
sage: (x^6*Dx).pth_power()
x^26*d/dx

sage: Dy = R.derivation(y) #_
↪needs sage.rings.finite_rings
sage: (x*Dx + y*Dy).pth_power() #_
↪needs sage.rings.finite_rings
x*d/dx + y*d/dy
```

An error is raised if the domain has characteristic zero:

```

sage: R.<x,y> = QQ[]
sage: Dx = R.derivation(x)
sage: Dx.pth_power()
Traceback (most recent call last):
...
TypeError: the domain of the derivation must have positive and prime_
↳characteristic

```

or if the characteristic is not a prime number:

```

sage: R.<x,y> = Integers(10)[]
sage: Dx = R.derivation(x)
sage: Dx.pth_power()
Traceback (most recent call last):
...
TypeError: the domain of the derivation must have positive and prime_
↳characteristic

```

class `sage.rings.derivation.RingDerivationWithoutTwist_fraction_field`(*parent*,
arg=None)

Bases: `RingDerivationWithoutTwist_wrapper`

This class handles derivations over fraction fields.

class `sage.rings.derivation.RingDerivationWithoutTwist_function`(*parent*, *arg=None*)

Bases: `RingDerivationWithoutTwist`

A class for untwisted derivations over rings whose elements are either polynomials, rational fractions, power series or Laurent series.

is_zero()

Return True if this derivation is zero.

EXAMPLES:

```

sage: R.<x,y> = ZZ[]
sage: f = R.derivation(); f
d/dx
sage: f.is_zero()
False

sage: (f-f).is_zero()
True

```

list()

Return the list of coefficient of this derivation on the canonical basis.

EXAMPLES:

```

sage: R.<x,y> = GF(5)[][]
sage: M = R.derivation_module()
sage: M.basis()
Family (d/dx, d/dy)

sage: R.derivation(x).list()
[1, 0]
sage: R.derivation(y).list()
[0, 1]

```

(continues on next page)

(continued from previous page)

```
sage: f = x*R.derivation(x) + y*R.derivation(y); f
x*d/dx + y*d/dy
sage: f.list()
[x, y]
```

class `sage.rings.derivation.RingDerivationWithoutTwist_quotient` (*parent, arg=None*)
 Bases: `RingDerivationWithoutTwist_wrapper`

This class handles derivations over quotient rings.

class `sage.rings.derivation.RingDerivationWithoutTwist_wrapper` (*parent, arg=None*)
 Bases: `RingDerivationWithoutTwist`

This class is a wrapper for derivation.

It is useful for changing the parent without changing the computation rules for derivations. It is used for derivations over fraction fields and quotient rings.

list ()

Return the list of coefficient of this derivation on the canonical basis.

EXAMPLES:

```
sage: # needs sage.libs.singular
sage: R.<X,Y> = GF(5) []
sage: S.<x,y> = R.quo([X^5, Y^5])
sage: M = S.derivation_module()
sage: M.basis()
Family (d/dx, d/dy)
sage: S.derivation(x).list()
[1, 0]
sage: S.derivation(y).list()
[0, 1]
sage: f = x*S.derivation(x) + y*S.derivation(y); f
x*d/dx + y*d/dy
sage: f.list()
[x, y]
```

class `sage.rings.derivation.RingDerivationWithoutTwist_zero` (*parent, arg=None*)
 Bases: `RingDerivationWithoutTwist`

This class can only represent the zero derivation.

It is used when the parent is the zero derivation module (e.g., when its domain is $\mathbb{Z}\mathbb{Z}$, $\mathbb{Q}\mathbb{Q}$, a finite field, etc.)

is_zero ()

Return True if this derivation vanishes.

EXAMPLES:

```
sage: M = QQ.derivation_module()
sage: M().is_zero()
True
```

list ()

Return the list of coefficient of this derivation on the canonical basis.

EXAMPLES:

```
sage: M = QQ.derivation_module()  
sage: M().list()  
[]
```


INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

r

- sage.rings.abc, 14
- sage.rings.big_oh, 145
- sage.rings.derivation, 157
- sage.rings.fraction_field, 83
- sage.rings.fraction_field_element, 89
- sage.rings.generic, 141
- sage.rings.homset, 61
- sage.rings.ideal, 23
- sage.rings.ideal_monoid, 38
- sage.rings.infinity, 146
- sage.rings.localization, 95
- sage.rings.morphism, 43
- sage.rings.noncommutative_ideals, 39
- sage.rings.numbers_abc, 155
- sage.rings.quotient_ring, 65
- sage.rings.quotient_ring_element, 78
- sage.rings.ring, 1
- sage.rings.ring_extension, 105
- sage.rings.ring_extension_element, 126
- sage.rings.ring_extension_morphism, 137

A

absolute_base() (*sage.rings.ring_extension.RingExtension_generic method*), 112
 absolute_degree() (*sage.rings.ring_extension.RingExtension_generic method*), 113
 absolute_norm() (*sage.rings.ideal.Ideal_generic method*), 26
 additive_order() (*sage.rings.ring_extension_element.RingExtensionElement method*), 126
 Algebra (*class in sage.rings.ring*), 2
 algebraic_closure() (*sage.rings.ring.Field method*), 3
 AlgebraicField (*class in sage.rings.abc*), 14
 AlgebraicField_common (*class in sage.rings.abc*), 14
 AlgebraicRealField (*class in sage.rings.abc*), 14
 ambient() (*sage.rings.quotient_ring.QuotientRing_nc method*), 70
 AnInfinity (*class in sage.rings.infinity*), 149
 apply_morphism() (*sage.rings.ideal.Ideal_generic method*), 26
 associated_primes() (*sage.rings.ideal.Ideal_generic method*), 27

B

backend() (*sage.rings.ring_extension_element.RingExtensionElement method*), 126
 backend() (*sage.rings.ring_extension.RingExtension_generic method*), 113
 base() (*sage.rings.ring_extension.RingExtension_generic method*), 113
 base_extend() (*sage.rings.ring.Ring method*), 6
 base_map() (*sage.rings.morphism.RingHomomorphism_im_gens method*), 59
 base_map() (*sage.rings.ring_extension_morphism.RingExtensionHomomorphism method*), 138
 base_ring() (*sage.rings.fraction_field.FractionField_generic method*), 86
 base_ring() (*sage.rings.ideal.Ideal_generic method*), 27

bases() (*sage.rings.ring_extension.RingExtension_generic method*), 114
 basis() (*sage.rings.derivation.RingDerivationModule method*), 160
 basis_over() (*sage.rings.ring_extension.RingExtensionWithBasis method*), 108

C

CallableSymbolicExpressionRing (*class in sage.rings.abc*), 15
 category() (*sage.rings.ideal.Ideal_generic method*), 27
 category() (*sage.rings.ring.Ring method*), 7
 characteristic() (*sage.rings.fraction_field.FractionField_generic method*), 86
 characteristic() (*sage.rings.localization.Localization method*), 99
 characteristic() (*sage.rings.quotient_ring.QuotientRing_nc method*), 70
 characteristic() (*sage.rings.ring_extension.RingExtension_generic method*), 114
 charpoly() (*sage.rings.ring_extension_element.RingExtensionWithBasisElement method*), 130
 class_number() (*sage.rings.fraction_field.FractionField_1poly_field method*), 85
 codomain() (*sage.rings.derivation.RingDerivation method*), 159
 codomain() (*sage.rings.derivation.RingDerivationModule method*), 160
 common_base() (*in module sage.rings.ring_extension*), 124
 CommutativeAlgebra (*class in sage.rings.ring*), 2
 CommutativeRing (*class in sage.rings.ring*), 2
 ComplexBallField (*class in sage.rings.abc*), 15
 ComplexDoubleField (*class in sage.rings.abc*), 16
 ComplexField (*class in sage.rings.abc*), 16
 ComplexIntervalField (*class in sage.rings.abc*), 16
 construction() (*sage.rings.fraction_field.FractionField_generic method*), 86
 construction() (*sage.rings.quotient_ring.QuotientRing_nc method*), 70
 construction() (*sage.rings.ring_extension.RingExtension_generic method*), 115

cover() (*sage.rings.quotient_ring.QuotientRing_nc method*), 71
 cover_ring() (*sage.rings.quotient_ring.QuotientRing_nc method*), 71
 create_key_and_extra_args() (*sage.rings.ring_extension.RingExtensionFactory method*), 107
 create_object() (*sage.rings.ring_extension.RingExtensionFactory method*), 107
 Cyclic() (*in module sage.rings.ideal*), 23

D

DedekindDomain (*class in sage.rings.ring*), 3
 defining_ideal() (*sage.rings.quotient_ring.QuotientRing_nc method*), 72
 defining_morphism() (*sage.rings.derivation.RingDerivationModule method*), 161
 defining_morphism() (*sage.rings.ring_extension.RingExtension_generic method*), 115
 degree() (*sage.rings.ring_extension.RingExtension_generic method*), 116
 degree_over() (*sage.rings.ring_extension.RingExtension_generic method*), 116
 denominator() (*sage.rings.fraction_field_element.FractionFieldElement method*), 89
 denominator() (*sage.rings.localization.LocalizationElement method*), 101
 denominator() (*sage.rings.ring_extension_element.RingExtensionFractionFieldElement method*), 129
 divides() (*sage.rings.ideal.Ideal_principal method*), 36
 divides() (*sage.rings.ring.Field method*), 4
 domain() (*sage.rings.derivation.RingDerivation method*), 160
 domain() (*sage.rings.derivation.RingDerivationModule method*), 161
 dual_basis() (*sage.rings.derivation.RingDerivationModule method*), 161

E

Element (*sage.rings.homset.RingHomset_generic attribute*), 61
 Element (*sage.rings.homset.RingHomset_quo_ring attribute*), 62
 Element (*sage.rings.ideal_monoid.IdealMonoid_c attribute*), 39
 Element (*sage.rings.localization.Localization attribute*), 99
 Element (*sage.rings.quotient_ring.QuotientRing_nc attribute*), 70
 Element (*sage.rings.ring_extension.RingExtension_generic attribute*), 112
 Element (*sage.rings.ring_extension.RingExtensionFractionField attribute*), 107

Element (*sage.rings.ring_extension.RingExtensionWithBasis attribute*), 107
 embedded_primes() (*sage.rings.ideal.Ideal_generic method*), 28
 epsilon() (*sage.rings.ring.Ring method*), 7
 extend_to_fraction_field() (*sage.rings.derivation.RingDerivationWithoutTwist method*), 165
 extend_to_fraction_field() (*sage.rings.derivation.RingDerivationWithTwist_generic method*), 164
 extension() (*sage.rings.ring.CommutativeRing method*), 2

F

factor() (*sage.rings.localization.LocalizationElement method*), 102
 Field (*class in sage.rings.ring*), 3
 FieldIdeal() (*in module sage.rings.ideal*), 24
 FiniteNumber (*class in sage.rings.infinity*), 149
 fraction_field() (*sage.rings.infinity.InfinityRing_class method*), 150
 fraction_field() (*sage.rings.localization.Localization method*), 100
 fraction_field() (*sage.rings.ring_extension.RingExtension_generic method*), 117
 fraction_field() (*sage.rings.ring_extension.RingExtensionWithBasis method*), 108
 fraction_field() (*sage.rings.ring_extension.RingExtensionWithGen method*), 111
 fraction_field() (*sage.rings.ring.CommutativeRing method*), 2
 fraction_field() (*sage.rings.ring.Field method*), 4
 FractionField() (*in module sage.rings.fraction_field*), 83
 FractionField_1poly_field (*class in sage.rings.fraction_field*), 85
 FractionField_generic (*class in sage.rings.fraction_field*), 86
 FractionFieldElement (*class in sage.rings.fraction_field_element*), 89
 FractionFieldElement_1poly_field (*class in sage.rings.fraction_field_element*), 92
 FractionFieldEmbedding (*class in sage.rings.fraction_field*), 84
 FractionFieldEmbeddingSection (*class in sage.rings.fraction_field*), 85
 free_module() (*sage.rings.ring_extension.RingExtensionWithBasis method*), 109
 free_resolution() (*sage.rings.ideal.Ideal_generic method*), 28
 FrobeniusEndomorphism_generic (*class in sage.rings.morphism*), 49
 from_base_ring() (*sage.rings.ring_extension.RingExtension_generic method*), 118

- function_field() (*sage.rings.fraction_field.FractionField_1poly_field* method), 85
- ## G
- gcd() (*sage.rings.ideal.Ideal_pid* method), 34
 gen() (*sage.rings.derivation.RingDerivationModule* method), 162
 gen() (*sage.rings.fraction_field.FractionField_generic* method), 86
 gen() (*sage.rings.ideal.Ideal_generic* method), 28
 gen() (*sage.rings.ideal.Ideal_principal* method), 36
 gen() (*sage.rings.infinity.InfinityRing_class* method), 150
 gen() (*sage.rings.infinity.UnsignedInfinityRing_class* method), 152
 gen() (*sage.rings.localization.Localization* method), 100
 gen() (*sage.rings.quotient_ring.QuotientRing_nc* method), 72
 gen() (*sage.rings.ring_extension.RingExtension_generic* method), 118
 generators() (*in module sage.rings.ring_extension*), 125
 gens() (*sage.rings.derivation.RingDerivationModule* method), 162
 gens() (*sage.rings.ideal.Ideal_generic* method), 28
 gens() (*sage.rings.infinity.InfinityRing_class* method), 150
 gens() (*sage.rings.infinity.UnsignedInfinityRing_class* method), 152
 gens() (*sage.rings.localization.Localization* method), 100
 gens() (*sage.rings.ring_extension.RingExtension_generic* method), 119
 gens() (*sage.rings.ring_extension.RingExtensionWithGen* method), 112
 gens_reduced() (*sage.rings.ideal.Ideal_generic* method), 29
 graded_free_resolution() (*sage.rings.ideal.Ideal_generic* method), 29
- ## H
- has_coerce_map_from() (*sage.rings.homset.RingHomset_generic* method), 61
 hom() (*sage.rings.ring_extension.RingExtension_generic* method), 119
- ## I
- Ideal() (*in module sage.rings.ideal*), 24
 ideal() (*sage.rings.quotient_ring.QuotientRing_nc* method), 72
 ideal() (*sage.rings.ring.Field* method), 4
 ideal() (*sage.rings.ring.Ring* method), 8
 Ideal_fractional (*class in sage.rings.ideal*), 26
 Ideal_generic (*class in sage.rings.ideal*), 26
 ideal_monoid() (*sage.rings.ring.CommutativeRing* method), 2
 ideal_monoid() (*sage.rings.ring.Ring* method), 8
 Ideal_nc (*class in sage.rings.noncommutative_ideals*), 40
 Ideal_pid (*class in sage.rings.ideal*), 34
 Ideal_principal (*class in sage.rings.ideal*), 36
 IdealMonoid() (*in module sage.rings.ideal_monoid*), 38
 IdealMonoid_c (*class in sage.rings.ideal_monoid*), 39
 IdealMonoid_nc (*class in sage.rings.noncommutative_ideals*), 40
 im_gens() (*sage.rings.morphism.RingHomomorphism_im_gens* method), 60
 in_base() (*sage.rings.ring_extension_element.RingExtensionElement* method), 127
 InfinityRing_class (*class in sage.rings.infinity*), 150
 IntegerModRing (*class in sage.rings.abc*), 17
 integral_closure() (*sage.rings.ring.Field* method), 4
 IntegralDomain (*class in sage.rings.ring*), 5
 interpolation() (*sage.rings.generic.ProductTree* method), 142
 inverse() (*sage.rings.morphism.RingHomomorphism* method), 49
 inverse() (*sage.rings.morphism.RingHomomorphism_from_base* method), 57
 inverse() (*sage.rings.morphism.RingHomomorphism_from_fraction_field* method), 58
 inverse_image() (*sage.rings.morphism.RingHomomorphism* method), 52
 inverse_of_unit() (*sage.rings.localization.LocalizationElement* method), 102
 is_commutative() (*sage.rings.infinity.InfinityRing_class* method), 150
 is_commutative() (*sage.rings.quotient_ring.QuotientRing_nc* method), 73
 is_commutative() (*sage.rings.ring.CommutativeRing* method), 3
 is_defined_over() (*sage.rings.ring_extension.RingExtension_generic* method), 120
 is_exact() (*sage.rings.fraction_field.FractionField_generic* method), 87
 is_exact() (*sage.rings.ring.Ring* method), 9
 is_field() (*sage.rings.fraction_field.FractionField_generic* method), 87
 is_field() (*sage.rings.localization.Localization* method), 100
 is_field() (*sage.rings.quotient_ring.QuotientRing_nc* method), 73
 is_field() (*sage.rings.ring_extension.RingExtension_generic* method), 121
 is_field() (*sage.rings.ring.Field* method), 5
 is_field() (*sage.rings.ring.IntegralDomain* method), 5
 is_field() (*sage.rings.ring.Ring* method), 9

- `is_finite()` (*sage.rings.fraction_field.FractionField_generic method*), 87
`is_finite_over()` (*sage.rings.ring_extension.RingExtension_generic method*), 121
`is_FractionField()` (*in module sage.rings.fraction_field*), 88
`is_FractionFieldElement()` (*in module sage.rings.fraction_field_element*), 93
`is_free_over()` (*sage.rings.ring_extension.RingExtension_generic method*), 122
`is_Ideal()` (*in module sage.rings.ideal*), 38
`is_identity()` (*sage.rings.ring_extension_morphism.RingExtensionHomomorphism method*), 139
`is_Infinite()` (*in module sage.rings.infinity*), 153
`is_injective()` (*sage.rings.fraction_field.FractionFieldEmbedding method*), 84
`is_injective()` (*sage.rings.ring_extension_morphism.MapFreeModuleToRelativeRing method*), 137
`is_injective()` (*sage.rings.ring_extension_morphism.MapRelativeRingToFreeModule method*), 137
`is_injective()` (*sage.rings.ring_extension_morphism.RingExtensionHomomorphism method*), 139
`is_integral()` (*sage.rings.fraction_field_element.FractionFieldElement_1poly_field method*), 92
`is_integral_domain()` (*sage.rings.quotient_ring.QuotientRing_nc method*), 73
`is_integrally_closed()` (*sage.rings.ring.Field method*), 5
`is_integrally_closed()` (*sage.rings.ring.IntegralDomain method*), 6
`is_invertible()` (*sage.rings.morphism.RingHomomorphism method*), 53
`is_maximal()` (*sage.rings.ideal.Ideal_generic method*), 29
`is_maximal()` (*sage.rings.ideal.Ideal_pid method*), 34
`is_nilpotent()` (*sage.rings.ring_extension_element.RingExtensionElement method*), 127
`is_noetherian()` (*sage.rings.quotient_ring.QuotientRing_nc method*), 74
`is_noetherian()` (*sage.rings.ring.Field method*), 5
`is_one()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 89
`is_primary()` (*sage.rings.ideal.Ideal_generic method*), 30
`is_prime()` (*sage.rings.ideal.Ideal_generic method*), 30
`is_prime()` (*sage.rings.ideal.Ideal_pid method*), 35
`is_prime()` (*sage.rings.ring_extension_element.RingExtensionElement method*), 127
`is_prime_field()` (*sage.rings.ring.Ring method*), 10
`is_principal()` (*sage.rings.ideal.Ideal_generic method*), 31
`is_principal()` (*sage.rings.ideal.Ideal_principal method*), 37
`is_QuotientRing()` (*in module sage.rings.quotient_ring*), 77
`is_Ring()` (*in module sage.rings.ring*), 13
`is_RingHomset()` (*in module sage.rings.homset*), 62
`is_square()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 89
`is_square()` (*sage.rings.ring_extension_element.RingExtensionElement method*), 128
`is_subring()` (*sage.rings.ring.Ring method*), 10
`is_surjective()` (*sage.rings.fraction_field.FractionFieldEmbedding method*), 84
`is_surjective()` (*sage.rings.morphism.RingHomomorphism method*), 53
`is_surjective()` (*sage.rings.ring_extension_morphism.MapFreeModuleToRelativeRing method*), 137
`is_surjective()` (*sage.rings.ring_extension_morphism.MapRelativeRingToFreeModule method*), 137
`is_surjective()` (*sage.rings.ring_extension_morphism.RingExtensionHomomorphism method*), 139
`is_trivial()` (*sage.rings.ideal.Ideal_generic method*), 31
`is_unit()` (*sage.rings.localization.LocalizationElement method*), 102
`is_unit()` (*sage.rings.quotient_ring_element.QuotientRingElement method*), 78
`is_unit()` (*sage.rings.ring_extension_element.RingExtensionElement method*), 128
`is_zero()` (*sage.rings.derivation.RingDerivation WithoutTwist method*), 166
`is_zero()` (*sage.rings.derivation.RingDerivation WithoutTwist_function method*), 169
`is_zero()` (*sage.rings.derivation.RingDerivation WithoutTwist_zero method*), 170
`is_zero()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 90
`is_zero()` (*sage.rings.infinity.InfinityRing_class method*), 151

K

- `Katsura()` (*in module sage.rings.ideal*), 37
`kernel()` (*sage.rings.morphism.RingHomomorphism method*), 53
`kernel()` (*sage.rings.morphism.RingHomomorphism_cover method*), 55
`krull_dimension()` (*sage.rings.localization.Localization method*), 101

- krull_dimension() (*sage.rings.ring.CommutativeRing method*), 3
 krull_dimension() (*sage.rings.ring.Field method*), 5
- ## L
- lc() (*sage.rings.quotient_ring_element.QuotientRingElement method*), 79
 lcm() (*sage.rings.infinity.AnInfinity method*), 149
 leaves() (*sage.rings.generic.ProductTree method*), 143
 less_than_infinity() (*sage.rings.infinity.UnsignedInfinityRing_class method*), 152
 LessThanInfinity (*class in sage.rings.infinity*), 151
 lift() (*sage.rings.morphism.RingHomomorphism method*), 54
 lift() (*sage.rings.quotient_ring_element.QuotientRingElement method*), 79
 lift() (*sage.rings.quotient_ring.QuotientRing_nc method*), 74
 lifting_map() (*sage.rings.quotient_ring.QuotientRing_nc method*), 75
 list() (*sage.rings.derivation.RingDerivation WithoutTwist method*), 166
 list() (*sage.rings.derivation.RingDerivation WithoutTwist_function method*), 169
 list() (*sage.rings.derivation.RingDerivation WithoutTwist_wrapper method*), 170
 list() (*sage.rings.derivation.RingDerivation WithoutTwist_zero method*), 170
 list() (*sage.rings.derivation.RingDerivation WithTwist_generic method*), 164
 lm() (*sage.rings.quotient_ring_element.QuotientRingElement method*), 79
 Localization (*class in sage.rings.localization*), 98
 localization() (*sage.rings.ring.CommutativeRing method*), 3
 LocalizationElement (*class in sage.rings.localization*), 101
 lt() (*sage.rings.quotient_ring_element.QuotientRingElement method*), 80
- ## M
- make_element() (*in module sage.rings.fraction_field_element*), 93
 make_element_old() (*in module sage.rings.fraction_field_element*), 93
 MapFreeModuleToRelativeRing (*class in sage.rings.ring_extension_morphism*), 137
 MapRelativeRingToFreeModule (*class in sage.rings.ring_extension_morphism*), 137
 matrix() (*sage.rings.ring_extension_element.RingExtensionWithBasisElement method*), 131
 maximal_order() (*sage.rings.fraction_field.FractionField_Ipoly_field method*), 85
 minimal_associated_primes() (*sage.rings.ideal.Ideal_generic method*), 32
 minpoly() (*sage.rings.ring_extension_element.RingExtensionWithBasisElement method*), 132
 MinusInfinity (*class in sage.rings.infinity*), 151
 module
 sage.rings.abc, 14
 sage.rings.big_oh, 145
 sage.rings.derivation, 157
 sage.rings.fraction_field, 83
 sage.rings.fraction_field_element, 89
 sage.rings.generic, 141
 sage.rings.homset, 61
 sage.rings.ideal, 23
 sage.rings.ideal_monoid, 38
 sage.rings.infinity, 146
 sage.rings.localization, 95
 sage.rings.morphism, 43
 sage.rings.noncommutative_ideals, 39
 sage.rings.numbers_abc, 155
 sage.rings.quotient_ring, 65
 sage.rings.quotient_ring_element, 78
 sage.rings.ring, 1
 sage.rings.ring_extension, 105
 sage.rings.ring_extension_element, 126
 sage.rings.ring_extension_morphism, 137
 modulus() (*sage.rings.ring_extension.RingExtensionWithGen method*), 112
 monomial_coefficients() (*sage.rings.derivation.RingDerivation WithoutTwist method*), 166
 monomials() (*sage.rings.quotient_ring_element.QuotientRingElement method*), 80
 morphism_from_cover() (*sage.rings.morphism.RingHomomorphism_from_quotient method*), 59
 multiplicative_order() (*sage.rings.ring_extension_element.RingExtensionElement method*), 128
- ## N
- natural_map() (*sage.rings.homset.RingHomset_generic method*), 61
 ngens() (*sage.rings.derivation.RingDerivationModule method*), 162
 ngens() (*sage.rings.fraction_field.FractionField_generic method*), 87
 ngens() (*sage.rings.ideal.Ideal_generic method*), 32
 ngens() (*sage.rings.infinity.InfinityRing_class method*), 151

- `ngens()` (*sage.rings.infinity.UnsignedInfinityRing_class method*), 153
`ngens()` (*sage.rings.localization.Localization method*), 101
`ngens()` (*sage.rings.quotient_ring.QuotientRing_nc method*), 76
`ngens()` (*sage.rings.ring_extension.RingExtension_generic method*), 122
`NoetherianRing` (*class in sage.rings.ring*), 6
`norm()` (*sage.rings.ideal.Ideal_generic method*), 32
`norm()` (*sage.rings.ring_extension_element.RingExtensionWithBasisElement method*), 133
`normalize_extra_units()` (*in module sage.rings.localization*), 102
`nth_root()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 90
`NumberField_cyclotomic` (*class in sage.rings.abc*), 17
`NumberField_quadratic` (*class in sage.rings.abc*), 18
`numerator()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 91
`numerator()` (*sage.rings.localization.LocalizationElement method*), 102
`numerator()` (*sage.rings.ring_extension_element.RingExtensionFractionFieldElement method*), 129
- O**
- `O()` (*in module sage.rings.big_oh*), 145
`one()` (*sage.rings.ring.Ring method*), 10
`Order` (*class in sage.rings.abc*), 18
`order()` (*sage.rings.ring.Ring method*), 11
- P**
- `pAdicField` (*class in sage.rings.abc*), 21
`pAdicRing` (*class in sage.rings.abc*), 21
`PlusInfinity` (*class in sage.rings.infinity*), 152
`polynomial()` (*sage.rings.ring_extension_element.RingExtensionWithBasisElement method*), 134
`postcompose()` (*sage.rings.derivation.RingDerivationWithoutTwist method*), 167
`postcompose()` (*sage.rings.derivation.RingDerivationWithTwist_generic method*), 164
`power()` (*sage.rings.morphism.FrobeniusEndomorphism_generic method*), 49
`precompose()` (*sage.rings.derivation.RingDerivationWithoutTwist method*), 167
`precompose()` (*sage.rings.derivation.RingDerivationWithTwist_generic method*), 165
`primary_decomposition()` (*sage.rings.ideal.Ideal_generic method*), 32
`prime_subfield()` (*sage.rings.ring.Field method*), 5
`principal_ideal()` (*sage.rings.ring.Ring method*), 11
`PrincipalIdealDomain` (*class in sage.rings.ring*), 6
`print_options()` (*sage.rings.ring_extension.RingExtension_generic method*), 123
`prod_with_derivative()` (*in module sage.rings.generic*), 143
`ProductTree` (*class in sage.rings.generic*), 141
`pth_power()` (*sage.rings.derivation.RingDerivationWithoutTwist method*), 168
`pushforward()` (*sage.rings.morphism.RingHomomorphism method*), 54
 Python Enhancement Proposals
 PEP 3141, 155
- Q**
- `QuotientRing()` (*in module sage.rings.quotient_ring*), 66
`QuotientRing_generic` (*class in sage.rings.quotient_ring*), 68
`QuotientRing_nc` (*class in sage.rings.quotient_ring*), 69
`QuotientRingElement` (*class in sage.rings.quotient_ring_element*), 78
`QuotientRingIdeal_generic` (*class in sage.rings.quotient_ring*), 68
`QuotientRingIdeal_principal` (*class in sage.rings.quotient_ring*), 68
- R**
- `random_element()` (*sage.rings.derivation.RingDerivationModule method*), 163
`random_element()` (*sage.rings.fraction_field_element.FractionField_generic method*), 87
`random_element()` (*sage.rings.ideal.Ideal_generic method*), 32
`random_element()` (*sage.rings.quotient_ring.QuotientRing_nc method*), 76
`random_element()` (*sage.rings.ring_extension.RingExtension_generic method*), 124
`random_element()` (*sage.rings.ring.Ring method*), 11
`RealBallField` (*class in sage.rings.abc*), 18
`RealDoubleField` (*class in sage.rings.abc*), 19
`RealField` (*class in sage.rings.abc*), 19
`RealIntervalField` (*class in sage.rings.abc*), 20
`reduce()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 91
`reduce()` (*sage.rings.fraction_field_element.FractionFieldElement_Ipoly_field method*), 92
`reduce()` (*sage.rings.ideal.Ideal_generic method*), 33
`reduce()` (*sage.rings.ideal.Ideal_pid method*), 35
`reduce()` (*sage.rings.quotient_ring_element.QuotientRingElement method*), 80

- relative_degree() (*sage.rings.ring_extension.RingExtension_generic method*), 124
 remainders() (*sage.rings.generic.ProductTree method*), 143
 residue_field() (*sage.rings.ideal.Ideal_pid method*), 35
 retract() (*sage.rings.quotient_ring.QuotientRing_nc method*), 77
 Ring (*class in sage.rings.ring*), 6
 ring() (*sage.rings.fraction_field.FractionField_generic method*), 88
 ring() (*sage.rings.ideal_monoid.IdealMonoid_c method*), 39
 ring() (*sage.rings.ideal.Ideal_generic method*), 33
 ring() (*sage.rings.ring_extension.RingExtensionFractionField method*), 107
 ring_of_constants() (*sage.rings.derivation.RingDerivationModule method*), 163
 ring_of_integers() (*sage.rings.fraction_field.FractionField_1poly_field method*), 86
 RingDerivation (*class in sage.rings.derivation*), 159
 RingDerivationModule (*class in sage.rings.derivation*), 160
 RingDerivationWithoutTwist (*class in sage.rings.derivation*), 165
 RingDerivationWithoutTwist_fraction_field (*class in sage.rings.derivation*), 169
 RingDerivationWithoutTwist_function (*class in sage.rings.derivation*), 169
 RingDerivationWithoutTwist_quotient (*class in sage.rings.derivation*), 170
 RingDerivationWithoutTwist_wrapper (*class in sage.rings.derivation*), 170
 RingDerivationWithoutTwist_zero (*class in sage.rings.derivation*), 170
 RingDerivationWithTwist_generic (*class in sage.rings.derivation*), 164
 RingExtension_generic (*class in sage.rings.ring_extension*), 112
 RingExtensionBackendIsomorphism (*class in sage.rings.ring_extension_morphism*), 138
 RingExtensionBackendReverseIsomorphism (*class in sage.rings.ring_extension_morphism*), 138
 RingExtensionElement (*class in sage.rings.ring_extension_element*), 126
 RingExtensionFactory (*class in sage.rings.ring_extension*), 107
 RingExtensionFractionField (*class in sage.rings.ring_extension*), 107
 RingExtensionFractionFieldElement (*class in sage.rings.ring_extension_element*), 129
 RingExtensionHomomorphism (*class in sage.rings.ring_extension_morphism*), 138
 RingExtensionWithBasis (*class in sage.rings.ring_extension*), 107
 RingExtensionWithBasisElement (*class in sage.rings.ring_extension_element*), 130
 RingExtensionWithGen (*class in sage.rings.ring_extension*), 111
 RingHomomorphism (*class in sage.rings.morphism*), 49
 RingHomomorphism_cover (*class in sage.rings.morphism*), 55
 RingHomomorphism_from_base (*class in sage.rings.morphism*), 55
 RingHomomorphism_from_fraction_field (*class in sage.rings.morphism*), 58
 RingHomomorphism_from_quotient (*class in sage.rings.morphism*), 58
 RingHomomorphism_im_gens (*class in sage.rings.morphism*), 59
 RingHomset() (*in module sage.rings.homset*), 61
 RingHomset_generic (*class in sage.rings.homset*), 61
 RingHomset_quo_ring (*class in sage.rings.homset*), 62
 RingMap (*class in sage.rings.morphism*), 60
 RingMap_lift (*class in sage.rings.morphism*), 60
 root() (*sage.rings.generic.ProductTree method*), 143
- ## S
- sage.rings.abc
 module, 14
 sage.rings.big_oh
 module, 145
 sage.rings.derivation
 module, 157
 sage.rings.fraction_field
 module, 83
 sage.rings.fraction_field_element
 module, 89
 sage.rings.generic
 module, 141
 sage.rings.homset
 module, 61
 sage.rings.ideal
 module, 23
 sage.rings.ideal_monoid
 module, 38
 sage.rings.infinity
 module, 146
 sage.rings.localization
 module, 95
 sage.rings.morphism
 module, 43
 sage.rings.noncommutative_ideals
 module, 39

`sage.rings.numbers_abc`
 module, 155
`sage.rings.quotient_ring`
 module, 65
`sage.rings.quotient_ring_element`
 module, 78
`sage.rings.ring`
 module, 1
`sage.rings.ring_extension`
 module, 105
`sage.rings.ring_extension_element`
 module, 126
`sage.rings.ring_extension_morphism`
 module, 137
`section()` (*sage.rings.fraction_field.FractionFieldEmbedding method*), 84
`side()` (*sage.rings.noncommutative_ideals.Ideal_nc method*), 40
`sign()` (*sage.rings.infinity.FiniteNumber method*), 150
`sign()` (*sage.rings.infinity.LessThanInfinity method*), 151
`SignError`, 152
`some_elements()` (*sage.rings.derivation.RingDerivationModule method*), 163
`some_elements()` (*sage.rings.fraction_field.FractionField_generic method*), 88
`specialization()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 91
`sqrt()` (*sage.rings.infinity.FiniteNumber method*), 150
`sqrt()` (*sage.rings.infinity.MinusInfinity method*), 151
`sqrt()` (*sage.rings.infinity.PlusInfinity method*), 152
`sqrt()` (*sage.rings.ring_extension_element.RingExtensionElement method*), 128
`subs()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 91
`support()` (*sage.rings.fraction_field_element.FractionFieldElement_1poly_field method*), 93
`SymbolicRing` (class in *sage.rings.abc*), 20

T

`term_order()` (*sage.rings.quotient_ring.QuotientRing_nc method*), 77
`test_comparison()` (in module *sage.rings.infinity*), 153
`test_signed_infinity()` (in module *sage.rings.infinity*), 154
`tower_bases()` (in module *sage.rings.ring_extension*), 125
`trace()` (*sage.rings.ring_extension_element.RingExtensionWithBasisElement method*), 135
`twisting_morphism()` (*sage.rings.derivation.RingDerivationModule method*), 163

U

`underlying_map()` (*sage.rings.morphism.RingHomo-*

morphism_from_base method), 57
`unit_ideal()` (*sage.rings.ring.Ring method*), 11
`UniversalCyclotomicField` (class in *sage.rings.abc*), 20
`UnsignedInfinity` (class in *sage.rings.infinity*), 152
`UnsignedInfinityRing_class` (class in *sage.rings.infinity*), 152

V

`valuation()` (*sage.rings.fraction_field_element.FractionFieldElement method*), 92
`variable_names()` (in module *sage.rings.ring_extension*), 126
`variables()` (*sage.rings.quotient_ring_element.QuotientRingElement method*), 81
`vector()` (*sage.rings.ring_extension_element.RingExtensionWithBasisElement method*), 136

Z

`zero()` (*sage.rings.homset.RingHomset_generic method*), 62
`zero()` (*sage.rings.ring.Ring method*), 11
`zero_ideal()` (*sage.rings.ring.Ring method*), 12
`zeta()` (*sage.rings.ring.Ring method*), 12
`zeta_order()` (*sage.rings.ring.Ring method*), 13